
GENERAL CATALOGUE 2025 PROTECTIVE WEAR









HB PROTECTIVE WEAR - DIE SCHUTZMARKE!

Dear Sir or Madam,
Dear business partners and customers,

With our 2025 general catalogue, we are presenting you four new collections and many new women's items with which we are comprehensively expanding our product lines. This year, our collections will once again be staged by our employees.

The new **HB-ArcSelect® Pro**, which is available in both protection classes 1 and 2, is designed to meet the special requirements of arc flash protection. The collection can be used in a wide range of applications fields thanks to improved visibility according to EN 17353. It is comfortable to wear and available in three colour combinations.

With **HB-WeldersFORCE®**, we have added to our range two specialised lines for welding protection in four colours and two weights. All versions are designed in the same look to ensure that employees are uniformly equipped.

The new **TEMPEX® COLD Pro** collection has been specially designed for use in leasing. It is certified in accordance with ISO 15797 and suitable for use down to –49 °C. A matching inner jacket can either be buttoned in for additional protection against the cold or alternatively worn on its own in the light cooling range.

HB-CHEMprotect is the first chemical protection made from recycled polyester in our range.

The comprehensive collection made from a pleasantly lightweight fabric also offers permanent antistatic properties, making it the ideal solution for many specialised manufacturing processes. Like all our products made from environmentally friendly materials, they also have the "Green Turtle" label

and are labelled with a turtle with a green leaf fin.

Further examples of our commitment to environmental protection and sustainability are our ISO 14001 certification, which we successfully completed this year, and our Ecovadis Bronze Medal award, which immediately placed us in the top 100 in the manufacturing industry.

in the manufacturing industry.

If you would like to find out more about our range, our activities and all the latest news about the company and the HB Protective Wear brand, please subscribe to our newsletter at www.hb-online.com/en/service/newsletter or follow us on social media. We will keep you up to date there.

And now I hope you enjoy enjoy exploring the wide range of offers in our new catalogue!

Klaus Berthold

L Bute

CEO

Owner of HB Protective Wear





CONTENT



| THE COMPAN' |
|-------------|
|-------------|

| Die Schutzmarke | Ub |
|-------------------------------------|----|
| This is HB Protective Wear | 08 |
| Quality, service and responsibility | 10 |
| Engaged for employees and society | 16 |
| All signs on green | 18 |
| Multi-risk protection from HB | 20 |



| ARC FLASH PROTECTION | 22 |
|--|----|
| HB-SecureAllround® Jacket, trousers, coverall, bib and brace | |
| trousers | 24 |
| HB-ArcSelect® Pro Blouson, trousers | 26 |
| HB-ArcSelect® Pro Bib and brace trousers | 28 |
| HB-ArcSelect® Pro Shirt, coat | 30 |
| HB-4arc® Blouson, trousers, bib and brace trousers | 32 |
| HB-MODarc [®] Blouson, trousers, bib and brace trousers | 34 |
| HB-MODarc® Blouson, trousers, bib and brace trousers with | |
| reflective stripes | 36 |
| HB-MODarc® Polo shirt, T-shirt, sweatshirt | 38 |
| HB-PROtection® Jacket, trousers, bib and brace trousers | 40 |
| HB-PROtection® Green Turtle Shirt | 42 |
| HB-MODarc&vis® Jacket, trousers, bib and brace trousers with | |
| reflective stripes | 44 |
| HB-MODarc&vis® Polo shirt, Warnweste FR | 46 |
| HB-MODarc&vis® Fleece jacket, sweatshirt with reflective stripes | 48 |
| HB-MODarc&vis® Fleece jacket, parka with liner | 50 |
| HB-MODarc&vis® Parka with direct laminate, brace trousers | 52 |
| HB-4Energy® Jacket, trousers, bib and brace trousers | 54 |
| HB-MultiPro FR® Parka | 56 |
| HB-MultiPro FR® Fleece jacket, bib and brace trousers | 58 |
| NOMEX® Viskose Blouson, trousers, bib and brace trousers | 60 |
| NOMEX® Comfort Blouson, jacket, coat | 62 |
| NOMEX® Comfort Trousers, bib and brace trousers, coverall | |
| INOTEC® Arc & Energy Jacket, trousers, bib and brace trousers | 66 |

HEAT, SPLASHES & WELDING

| HEAT, SPLASHES AND WELDING PROTECTION 68 |
|--|
| PROBAN $^{\otimes}$ Jacket, trousers, bib and brace trousers |
| HB-WeldersFORCE® Blouson, trousers |
| HB-WeldersFORCE® Bib and brace trousers |
| HB-4welders $^{\circ}$ 2.0 Blouson, trousers, bib and brace trousers 76 |
| HB-ComFlex® Jacket, trousers |
| $HB\text{-}ComFlex^{\scriptsize{\$}}\;$ Bib and brace trousers, apron with sleeves |
| SECAN $^{\circ}$ Securo 420 Jacket, trousers, bib and brace trousers 82 |
| HB-Iron Pro Jacket, trousers, bib and brace trousers, shirt 84 |
| MARLAN Jacket, trousers, bib and brace trousers, shirt 86 |
| HB-HeavyMetal Pro® Jacket, trousers |
| HB-HeavyMetal $Pro^{\$}$ Bib and brace trousers, shirt90 |
| $VINEX^{\circledast}\;$ Blouson, trousers, bib and brace trousers, shirt |
| Accessories Heat Cooling garments, knee pads, belt FR 94 |
| TEMPEX®-TREME HEAT Material overview |
| TEMPEX®-TREME HEAT CLASSIC KF-3/Z |
| TEMPEX®-TREME HEAT COMFORT AW-1/Y und CK-12/Z101 |
| TEMPEX®-TREME HEAT COMFORT Plus AW-1/Y und CK-12/Z \dots 104 |
| TEMPEX®-TREME HEAT Face- and head protection |
| TEMPEX®-TREME HEAT Hand protection |
| TEMPEX®-TREME HEAT Foot protection116 |



| CHEMICAL PROTECTION118 |
|--|
| HB-CHEMstandard Jacket, coat, shirt, trousers, bib and brace |
| trousers |
| HB-CHEMprotect Jacket, shirt, trousers, bib and brace trousers 122 |
| HB-CHEMprotect Coat |
| HB-CHEM Functional underwear Undershirt, underpants 125 |

HIVIS & WEATHER

| HIGH VISIBILITY AND WEATHER PROTECTION | 126 |
|--|-----|
| HI-VISION® Basic Polo shirt, T-shirt | 128 |
| HI-VISION® Basic Parka | 130 |
| HB-StormBase® Parka, brace trousers | 131 |



COLD PROTECTION

| COLD PROTECTION |
|---|
| TEMPEX® CLASSIC 2.0 COLD STORE Jacket, trousers |
| TEMPEX® CLASSIC CHILLROOM Jacket, vest, trousers |
| TEMPEX® CLASSIC COLD STORE Jacket, trousers, coat visitor, |
| coverall (order picker)138 |
| TEMPEX® CLASSIC COLD STORE PLUS Jacket, trousers |
| (forklift driver)140 |
| TEMPEX® COMFORT CHILLROOM Jacket |
| TEMPEX® COMFORT CHILLROOM Vest, trousers |
| TEMPEX® COMFORT COLD STORE Jacket, trousers (order picker) 143 |
| TEMPEX® COMFORT COLD STORE Coat visitor, coverall144 |
| TEMPEX® COMFORT COLD STORE Plus Jacket, trousers |
| (forklift driver) |
| TEMPEX® THERMO Fleece jacket, -vest, -shirt, -trousers |
| TEMPEX® THERMO Jacket, vest, trousers |
| TEMPEX® HYGIENE Jacket, vest, trousers, coat visitor (order picker). 150 |
| TEMPEX® THERMO HYGIENE Jacket, vest, trousers |
| $TEMPEX^{\scriptsize @}\ COLD\ Pro\ COLD\ STORE\ Jacket,\ inner\ jacket,\ trousers\\ 154$ |
| TEMPEX® THERMO Accessories Functional underwear 156 |
| TEMPEX® THERMO Accessories Face- and head protection 157 $$ |
| TEMPEX® THERMO Accessories Hand protection160 |
| TEMPEX® THERMO Accessories Foot protection |
| |

FIRE & RESCUE SERVICES

TECHNICAL ASSISTANCE, RESCUE, AREA FIRE FIGHTING AND STATION WEAR168 Flammgard® KLASSIK Green Turtle Polo shirt, blouse, shirt 174 Flammgard® NORDRHEIN-WESTFALEN Blouson, trousers....... 176 Flammgard® BADEN-WÜRTTEMBERG Blouson, jacket................. 178 Flammgard® BADEN-WÜRTTEMBERG Trousers, softshell-, fleece jacket180 Flammgard® SAARLAND Trousers, softshell-, fleece jacket 184 $HB-WILDFIRE \hbox{$^{\otimes}$ 2.0 Jacket, identification collar}192$

ESD ELECTRO-STATIC DISCHARGE

| ESD PRODUCT PROTECTION 196 |
|---|
| CONDUCTEX® Green Turtle Coat |
| CONDUCTEX® Cotton Knit Green Turtle Polo shirt, T-shirt 200 |
| CONDUCTEX® Coat |
| CONDUCTEX® Blouson, trousers |
| CONDUCTEX® Cotton Knit T-shirt, polo shirt |
| CONDUCTEX® Cotton Knit Polo shirt |
| CONDUCTEX® Cotton Knit Sweatshirt, sweat jacket 210 |
| CONDUCTEX® Pro Knit Polo shirt |
| CONDUCTEX® Pro Knit Sweat jacket |
| Naptex® 4.0 Blouson, trousers |
| Naptex® 4.0 Coat |
| HABETEX® ESD Comfort Coverall |
| HABETEX® ESD Comfort Coat |
| ACCESSORIES ESD Head cover |

CLEANROOM & DUST

| CLEANROOM PRODUCT PROTECTION | 220 |
|--|-----|
| HABETEX® climatic Pro Coat, coverall | 222 |
| HABETEX® Micronplus Coverall | 223 |
| HABETEX® Micronselect Coverall, coat | 224 |
| ACCESSORIES CLEANROOM Head and hand protection | 226 |

WORTH KNOWING

| Overview product lines | 226 |
|--|-----|
| Emblems and patches: Your logo on your PPE | 232 |
| Our Partners | 234 |
| 21 TO WEAR® 2 | 236 |
| TEMPEX®-TREME HEAT Modular system | 238 |
| READY TO WEAR | 240 |
| Insulation values Cold protection | 241 |
| Standards | 242 |
| Sizes and care | 244 |
| Legend 2 | 246 |
| Customer service | 247 |

DIE SCHIITA

OGONARARET. LEADING PRODUCTS AND STRONG CORRORATAL MARKET. SCHUTZ SCHUTZ MARKE



DIE SCHUTZMARKE


Desirable safety is our brand essence: for more than 70 years, we have been providing clothing that protects people from hazards in the workplace. During this time, we have grown continuously, strategically expanding our range of PPE and strengthening our international market position.

The consistent focus on protection and quality, the competence of our employees and the constant commitment to sustainability and corporate values shaped by medium-sized companies are the reasons for the continuing success of the HB Protective Wear brand.

Today, HB Protective Wear stands for a unique and highly specialised range of products and is one of the market leaders in Germany and Europe. We owe our high profile not least to our trademark – the turtle. With its shell, it has the most personal of all protective equipment and is optimally adapted to different dangerous situations.

In our endeavour to always offer the best possible solution, we pursue every day anew with great passion the goal of making our brand values tangible for our customers: personal, predictable and powerful.

Committed to the HB Protective Wear brand, we will continue on this path in the future: firmly connected to our site in Thalhausen, appreciative in our dealings with employees and business partners, innovative and ready for change, committed to society and the environment, and focused on protecting people at their workplace.





BE SAFE. WE CARE.



As the only manufacturer in Germany, we have always focused exclusively on the development of protective clothing. We have PPE in our DNA and know the diverse requirements. We continuously safeguard our standards, material and processing expertise through close cooperation with all important stakeholders and regularly keep our employees up to date.

The result is a versatile range of innovative protective clothing that is convincing not only in its breadth but also in its depth.

We place particular emphasis on flexibility and individuality: that is why we offer our customers protective clothing that naturally fulfils the required standard profile, but can also be tailored to the respective company Cl.

This is where our offers such as READY TO WEAR or our modular system for metallised heat protection come in, which make it very easy to adapt to the respective requirements and individual needs.





A HIGH LEVEL OF RESPONSIBILITY





Category III PPE items must be monitored as part of a conformity assessment procedure in accordance with the Personal Protective Equipment Regulation VO (EU) 2016/425. HB carries out this monitoring in accordance with the Module D procedure. In an annual audit and certification by a notified body, our entire production and quality assurance process is checked and confirmed. The certification according to Module D underlines the high demands that we, as a manufacturer with a high degree of specialisation in PPE, place on the quality and safety of our products.

Through the significantly extended scope of testing, we increase the safety and quality of our protective clothing and give the customer an even better feeling when deciding on our products. In addition to reducing costs, the conservation of resources is of particular importance. Furthermore, this process gives us increased flexibility and allows us to react more quickly to customer needs.





CLOSE TO THE CUSTOMER NOT ONLY IN TERMS OF DELIVERY

We are optimally positioned in every respect to live customer proximity. Our production sites are mainly concentrated in the European region. The central hub of all logistical processes are our warehouses of over 4,000 m², which offer space for up to 500,000 products. This enables us to quickly deliver more than 1.5 million garments per year.

If a garment is not available from stock, our high-speed 21 TO WEAR® delivery service ensures that the customer does not have to wait longer than 21 days for it. Additional flexibility is offered by our READY TO WEAR service, which supplies smaller customers with individually configurable PPE, or our web shop.

After all, we do not only want to supply our customers quickly, but also to reach the most diverse needs and demands through an unprecedentedly differentiated product range and customised service. That is why we always support our customers with competent advice and personal service.





FAIR AND RESPONSIBLE: OUR CORPORATE BEHAVIOUR

Fair dealings with employees and business partners have always been an integral part of our corporate culture.

And commercial virtues such as honesty, partnership-based thinking and a humane tone in business still determine our actions today. We have set out the overriding maxims of conduct that guide us as a company in our own Code of Conduct, which can be viewed on our website.

Our Code of Conduct commits us to conducting our business in harmony with the concerns of society. Through regular social audits, we ensure that it is implemented in all our production facilities. We also expect our suppliers to comply with the standards and principles we have formulated.





COMMITMENT TO EMPLOYEES AND SOCIETY



For us, success can only be sustainable if we let our employees share in it and give something back to society. We can only be good in the long term if the people who work for us are doing well. And we can only last if we see ourselves as part of society and get involved.

This means, for example, that we promote the balance between work and family through flexible working hours and our own day care centre, which is free of charge for our employees. We place special emphasis on our apprenticeships and our training and coaching programmes. And those who want to do something for their health can use our company gym - also free of charge. Long-term employee loyalty shows that people feel good at HB.

We show further commitment by supporting charitable institutions in our region with regular donations. But it is also a tradition for our international production companies to support charitable causes of their choice at their respective locations.





ALL SIGNS ON GREEN

Nature and environmental protection are already anchored in our brand logo: the green sea turtle is our trademark. We feel a lasting connection to it and contribute to its conservation as a long-standing supporter of a conservation programme. Complemented by a green leaf fin, you will find it in our sustainability logo and on our "Green Turtle" icon, your signpost to products made from recycled materials.

In addition to the proven durability and repairability of our products, we also focus on the use of sustainable fibres and ingredients such as organic cotton and recycled polyester. For selected items, we therefore also use the Organic 100 Content Standard (OCS), which specifies the use of at least 95% certified organic materials, as well as the Organic Blended Content Standard and the Global Recycled Standard, which focuses on the recovery of processed raw materials and the products contain at least 20% recycled materials.

In order to provide the wearers of our protective clothing with the best possible sustainable protection, the ARC & ENERGY, HEAT SPLASHES & WELDING, COLD PROTECTION, FIRE & RESCUE SERVICES, ELECTROSTATIC DISCHARGE and CLEANROOM & DUST ranges already include numerous products certified to OEKO-TEX® STANDARD 100 – which you can read in our certificates no. 23.HDE.11802, 23.HDE.53928, 24.HDE.87650, 24.HDE.50189 and 24.HDE.21094.













WHAT IS BETTER THAN PROTECTION? THE RIGHT PROTECTION

Our working world is becoming more and more complex, and the variety of tasks in the workplace is increasing. Multi-risk PPE makes sense in many cases because it can protect against multiple risks. However, it should be borne in mind that this also involves compromises. This is because the more standards that are fulfilled in a qualified manner, the more expensive the fabric usually becomes and the more complex the manufacture.

The decisive factor in choosing the right PPE is that it is appropriate for the specific work situation. It is not so much a question of how many standards the protective clothing covers, but rather where exactly it is to be used and how well it protects against the potential hazards at the site of operation.

A precise examination of the areas of use and hazards is therefore also essential for multi-risk clothing. Which protective functions are really needed to decide whether the "specialist" is more in demand or whether many standards make sense, we clarify in the personal consultation together with the customer. The only decisive factor is the best possible protection at the respective workplace.

Our multi-risk products therefore do not form a separate product segment, but are integrated into the individual categories – easily recognisable by the multi-risk logo.

ARC & ENERGY

YOU DON'T FOLLOW A HERD, YOU LEAD IT

With our extensive Arc & Energy range,
we offer the right clothing for many highly specialised work areas
and fields of application. It reliably protects against arc flash
and the risk of flammability, while impressing with a level of wearing comfort
that feels completely natural, and not just in the workplace.





HB-SecureAllround®

The proven multifunctional blended fabric covers a wide range of standards and convinces with its pleasant wearing comfort.

The versatile products can also be designed according to your own ideas: Simply choose your desired combination from 6 different colours.

COLOUR COLOUR NO. COLOUR NAME **REGULAR SIZES** dark blue/ 46-58 & 94-110 medium grey/red

FIELDS OF APPLICATION: Plant engineering and construction, energy suppliers, electric industry and installation, public services, electricians



JACKET 4kA

Arc flash class 1

Part number: 01128 10134 020 3026 Garment weight: approx. 1,240 g

Three-coloured • stand-up collar • front with zip fastener with attached closure band and covered snap fasteners • 2 attached breast pockets with flap and covered snap fasteners • 1 inner pocket • side pockets with zip and with flap and covered snap fasteners • snap fasteners for adjusting sleeve width • leasing label • FR standard pictograms on the front.

TROUSERS 4kA

Arc flash class 1


Part number: 01128 20081 050 3026 Garment weight: approx. 1,060 g

Three-coloured • waistband elasticated at the side • waistband fastening with covered patented buttons on both sides • front zip • 2 wingpockets • 1 back pocket with flap and covered snap fasteners • 1 thigh pocket with 1 interior mobile phone/pen pocket and flap with covered snap fasteners.



1 collection – more than 1,000 possibilities

(page 240) and at www.hb-ready-to-wear.com













Also reflective stripes available – and certification acc. to EN 17353 high-visibility protection $igoplus_{\mathbb{C}}$ included!







ARC & ENERGY



The equipment with different pockets and reflective stripes is freely selectable. With HB-SecureAllround® and our **READY TO WEAR** system, you can configure your PPE completely individually. And all delivered within 21* days.

Closure band with snap fasteners covered on both sides

COVERALL 4kA

Arc flash class 1

Part number: **01128 30014 050 3026** Garment weight: approx. 1,590 g

Three-coloured • turndown collar • front with snap fastening covered on both sides • 2 patched breast pockets with flap and covered snap fasteners • 1 inside breast pocket with hook&loop fastening • 2 side pockets with flaps • sleeve width adjustable with snap fasteners • neck label • 1 back pocket • 1 thigh pocket with 1 interior mobile phone/pen pocket – each with flap and covered snap fasteners • FR standard pictograms on the arms.



BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number: **01128 50061 050 3026** Garment weight: approx. 1,340 g

Three-coloured • stretch braces • front zip fastener • interior bib pocket with flap • 2 wing pockets • 2 side accesses with button fastening • 1 back pocket, 1 thigh pocket with 1 interior mobile phone/pen pocket – each with flap and covered snap fasteners • elasticated kidney protection.

* Outside Germany, delivery will take a few days longer. We accept no liability for delivery delays due to force majeure beyond the control of the seller.

MATERIAL: 75 % COTTON, 24 % POLYESTER, 1% CARBON // FC-Equipment: fluorocarbon finish ·

.....

FABRIC WEIGHT: approx. 350 g/m² ·

ATPV VALUE: 17.3 cal/cm² · 724.3 kJ/m² · **HAF VALUE:** 84.1%



HB-ArcSelect® Pro

Our new HB-ArcSelect® Pro collection is designed to meet the special requirements of electric arc protection and can be used in a wide range of activities. The high cotton content and soft feel of the material make it very comfortable to wear, comparable to leisurewear.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 4.3 | | | 4 | $\bigoplus_{\mathbb{C}}$ | PR PR OFF | REGULAR SIZES |
|------|--------|------------|------------------------|-----------------------------|------------------------------------|-------------------------------|-----------|--------------------------|-----------------|----------------|
| | | 2041 | navy/royal | IEC 61482-2 | | | | | | |
| 1 | | 2081 | anthracite/red | 1-ply: APC 1 | FN 100 11/10 | | | | | |
| | | 2382 | anthracite/medium grey | 2-ply: APC 2* | EN ISO 11612 A1+A2/B1/ C1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 17353 Type B2 | ISO 15797 | 46-58 & 94-110 |
| 2 7 | | 45 | navy | *Front part and sleeves/ | 01/11 | | | | | |
| 2 ,3 | | 58 | anthracite | front trousers | | | | · • • | | |

FIELDS OF APPLICATION: Electricians and electric industries, public services, plant engineering, pipeline and line construction, steel works, gas and water networks, metal industry, switch gear construction



BLOUSON 4kA

Arc flash class 1

Part number: 01228 10000 017 + COLOUR NO.

Garment weight: approx. 950 g

BLOUSON 7kA/4kA

Arc flash class 2

Part number: 01228 10000 018 + COLOUR NO.

Garment weight: approx. 1,100 g

Two-coloured • stand-up collar • covered front zip with covered snap fastener • 2 attached breast pockets with flaps and covered snap fasteners • side pockets with flaps and covered snap fastener • 1 inner pocket with hook & loop fastener • sleeve width adjustable via snap fasteners • leasing neck label • embroidered FR standard pictograms on the front • reflective elements suitable for industrial laundry on front, back and sleeves • no high-visibility protective clothing acc. to EN ISO 20471.







ARC & **ENERGY**



Standard pictograms as flameretardant direct embroidery



Industrially washable reflective stripes, certified to EN 17353 B2, provide improved visibility







TROUSERS 4kA

Arc flash class 1

Part number: **01228 20000 015 + COLOUR NO.**

Garment weight: approx. 760 g

TROUSERS 7kA/4kA

Arc flash class 2

.....

.....:

Part number: 01228 20000 016 + COLOUR NO.

Garment weight: approx. 870 g

Single-coloured • waistband with button and zip-fly • 2 slant pockets • 1 hip pocket with flap and covered snap fastener • 1 ruler pocket on the right with flap and snap fastener ullet 1 bellow pocket on the right with flap and snap fastener • knee pockets with hook & loop fastener • reflective elements • flame-retardant reflective stripes suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471.

MATERIAL: 87 % COTTON, 12 % POLYAMIDE, 1 % CARBON ·

FABRIC WEIGHT: approx. 340 g/m² (2-ply: + approx. 280 g/m²)

4kA: ATPV VALUE: 13.0 cal/cm²

HB-ArcSelect® Pro

The extensive protective performance, the care with industrial laundry and the improved visibility which has been added to the standard profile meet the highest demands on PPE and represent modern multifunctional protective clothing. The contemporary look and high-quality manufacture round off the perfect profile of this multi-risk collection.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 4.3 | | | 4 | $\bigoplus_{\mathbb{C}}$ | | REGULAR SIZES |
|------|--------|------------|------------------------|-----------------------------|------------------------------------|-------------------------------|-----------|--------------------------|-----------|----------------|
| | | 2041 | navy/royal | IEC 61482-2 | | | | | | |
| 1 | | 2081 | anthracite/red | 1-ply: APC 1 | FN 100 11/10 | | | | | |
| | | 2382 | anthracite/medium grey | 2-ply: APC 2* | EN ISO 11612 A1+A2/B1/ C1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 17353 Type B2 | ISO 15797 | 46-58 & 94-110 |
| 2 7 | | 45 | navy | *Front part and sleeves/ | 01/11 | | | | | |
| 2 ,3 | | 58 | anthracite | front trousers | | | | · • • | | |

FIELDS OF APPLICATION: Electricians and electric industries, public services, plant engineering, pipeline and line construction, steel works, gas and water networks, metal industry, switch gear construction

2 and 3 Front trousers available as 1-ply or 2-ply version

Electric Arc Flash protection 4kA or 7kA/4 kA





BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number: **01228 50100 013 + COLOUR NO.**

Garment weight: approx. 960 g

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

Part number: 01228 50100 014 + COLOUR NO.

Garment weight: approx. 1,050 g

Single-coloured • stretch straps with fix-lock clip • front with zip-fly • bib with outer pocket with flap and covered snap fastener • 2 slant pockets • 1 hip pocket with flap and covered snap fastener • 1 ruler pocket on the right with flap and snap fastener • 1 bellow pocket on the right with flap and snap fastener • knee pockets with hook & loop fastener • flame-retardant reflective stripes suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471.









POSSIBLE COMBINATIONS - IN 2 PROTECTION CLASSES



High performance combined with soft material: HB-ArcSelect® Pro offers reliable protection and a comfortable fit throughout the working day. Improved visibility according to EN 17353 is also provided. The repair-friendly design of the collection supports the concept of sustainability.

MATERIAL: 87 % COTTON, 12 % POLYAMIDE, 1 % CARBON ·

FABRIC WEIGHT: approx. 340 g/m² (2-ply: + approx. 280 g/m²)


4kA: ATPV VALUE: 13.0 cal/cm²



Our HB-ArcSelect® Pro shirt and the completely double-layered coat made of the popular cotton-polyamide blend increase safety at workplaces exposed to arc hazards as an additional layer of clothing. This makes them the perfect addition to many heat, flame and arc flash protection collections. The jacket also covers large areas of the body and provides the best possible 7kA all-round protection.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | | 4 | | REGULAR SIZES |
|------|--------|------------|-------------|----------------------|---------------------------------------|-------------------------------|-----------|---------------|---------------|
| | | 41 | royal | | EN ISO 11612 A1+A2/B1/C1/ E1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | ISO 15797 | |
| | | 45 | navy | IEC 61482-2 | | | | | 37/38 – 47/48 |
| 11 | | 52 | medium grey | APC 1 | | | | | |
| | | 22 | orange | | | | | | : |
| 2 | | 45 | navy | IEC 61482-2 APC 2 | EN ISO 11612 A1+A2/B1/ C1/F1 | | | Only Finisher | 46/48 – 58/60 |

FIELDS OF APPLICATION: Plant construction, pipeline and line construction, electricians, public services, steel works, switch gear construction, communication, gas and water networks







ARC & ENERGY







Moving pleat on the back

MEN'S COAT 7kA

Arc flash class 2

Part number: **01004 40030 001 45** Garment weight: approx. 1,650 g

Single-coloured • completely 2-layered • high band collar • front with covered 2-way zipper plus hook &loop fastener • 2 vertical side pockets with covered zipper • moving pleat for easy walking on the back • sleeve hem with adjustable hook &loop fastener • FR leasing label • standard pictograms on the left sleeve.

MATERIAL: 87 % COTTON, 12 % POLYAMIDE, 1 % CARBON

1 : ATPV VALUE: 12.3 cal/cm 2 · HAF VALUE: 82.3 % · FABRIC WEIGHT: approx. 280 g/m 2 ·

2: ATPV VALUE: 40.0 cal/cm² · HAF VALUE: 91.0 % · FABRIC WEIGHT: approx. 340 g/m² + approx. 265 g/m²

HB-4arc®

Our high-end electric arc protection HB-4arc® is suitable for extreme load thanks to its particular high ATPV. It meets the requirements of IEC 61482-2 class 2 (7kA/4kA) and additionally offers heat, flame and welder's protection as well as antistatic properties. The material is partly doubled, very stable and tear-resistant. Wearing HB-4arc® provides you with much comfort and safety.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | F | 4 | O O | REGULAR SIZES | | |
|----------|---|------------|------------------|--------------------------|---------------------------------------|-------------------------------|-----------|-----------|----------------|--|--|
| 1 | | 2205 | navy/medium grey | IEC 61482-2 | | | | | | | |
| | 458 | | navy | *Front part and sleeves/ | EN ISO 11612 A1+A2/B1/C1/ F3/F1 | EN ISO 11611 Class 2 A1+A2 | EN 1149-5 | ISO 15797 | 46-58 & 94-110 | | |
| 21,31 | | 52 | medium grey | front trousers | : | : | | : | | | |
| FIELDS C | FIELDS OF APPLICATION: Electrical installation, public services, energy suppliers, plant construction, electricians | | | | | | | | | | |









ARC & ENERGY





2 and 3 Ruler pocket with additional pen pocket



Flame-retardant stretch braces with useful fixlock buckle

Side entries with elastic knitted wedge



2 and **3** Front trousers 2-ply



TROUSERS 7kA/4kA

Arc flash class 2

Part number: 01237 20060 037 + COLOUR NO.

Garment weight: approx. 1,152 g

Single-coloured • front trousers 2-ply • stitching in contrast colour off-white • added waistband with covered buttoning • zip fly • 2 slant pockets • 1 hip pocket on the right, 1 ruler pocket on the right leg (+ pen pocket) and 1 cargo pocket on the left (+ mobile phone pocket) – each with flap and covered snap fastener • shaped knees • knee pockets with adjustable covered hook&loop fastener.

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

Part number: 01237 50041 068 + COLOUR NO.

Garment weight: approx. 1,361 g

Single-coloured • front trousers 2-ply • contrast stitching in off-White • fix lock stretch braces • bib with outer pocket and flap • zip-fly • two-side entries with elastic knitted wedge • 2 slant pockets • 1 hip pocket on the right, 1 ruler pocket on the right leg (+ pen pocket) and 1 cargo pocket on left leg – each with flap and covered snap fastener • shaped knees • knee pockets with adjustable covered hook&loop fastener.

MATERIAL: 89 % COTTON, 10 % POLYAMIDE, 1 % CARBON ·

FABRIC WEIGHT: approx. 390 g/m² + approx. 250 g/m² ·

ATPV VALUE: 20.0 cal/cm² · 836.8 kJ/m² · ELIM: 16.0 cal/cm²





HB-MODarc® is high-quality arc flash PPE that can be perfectly combined and adapted to different purposes. The soft and lightweight fabric offers a good fit with plenty of freedom of movement and, thanks to the cotton, a high level of wearer comfort. The 2-layer models are double-worked at crucial points.

| | ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | | 4 | | PRO OBS OBS OBS OBS OBS OBS OBS OBS OBS OB | REGULAR SIZES | |
|---|---|--------|------------|----------------|---|--------------|---------------|-----------|--------------------|--|----------------|--|
| | 1 | | 2251 | grey/black | IEC 61482-2 | | | : | : | | | |
| | | | 2251 | grey/black | 1-ply: APC 1 | EN ISO 11612 | EN 100 11/11 | : | EN 1202/ | ISO 15797 | | |
| | 2 ,3 | _ | 2188 | black/grey | 2-ply: APC 2* *Front part and sleeves/ front trousers | 41 40 (D1 / | Class 1 A1+A2 | EN 1149-5 | EN 13034 Type 6 | Washing temperature 60°C | 46-58 & 94-110 | |
| F | FIELDS OF APPLICATION: Public services, energy suppliers, plant construction, electrical installation | | | | | | | | | | | |



Ladies models as well as more colours available in just 21 days.

snap fastener

Completely manufactured in

roof-tile design

Pockets with handy tab to open

Formed elbows for more movement freedom



Front part and sleeve available as 1-ply or 2-ply version. **Electric Arc** Flash protection 4 kA or 7kA/4kA

BLOUSON 4kA

Arc flash class 1

Part number 4kA: 01072 10107 034 2251 Garment weight: approx. 835 g

BLOUSON 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: 01072 10107 035 2251 Garment weight: approx. 910 g

Two-coloured • raw white contrast stitching • stand-up collar with covered snap fastener • covered zip • 2 front pockets (one as an attached pocket) with flap, covered snap fastener and tab to open • 1 inner pocket left with snap fastener • 2 side pockets with zip • sleeve hem adjustable with snap fastener covered on inside • attached waistband with covered snap fastener • leasing label • standard pictograms on front as FR direct stitching.











ARC & ENERGY



TROUSERS 4kA

Arc flash class 1

Part number 4kA: **01072 20074 002 + COLOUR NO.**

Garment weight: approx. 730 g

TROUSERS 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: **01072 20074 003 + COLOUR NO.**

Garment weight: approx. 845 g

Two-coloured • raw white contrast stitching • waistband with covered button closure • zip fly • 2 slant pockets • 1 hip pocket on the right and 1 bellows pocket on the left with additional, attached pocket - each with flap, covered snap fastener and tab to open • 1 ruler pocket on the right (+pen pocket) • 2 knee pockets outside with hook & loop fastener.



2 and **3** Knee pockets with hook&loop fastener



BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01072 50055 002 + COLOUR NO.

Garment weight: approx. 855 g

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: **01072 50055 003 + COLOUR NO.**

Garment weight: approx. 970 g

Two-coloured • raw white contrast stitching • stretch braces with fixlock buckle • bib with outer pocket with flap and covered snap fastener • straight kidney protection • 2 side accesses with stretch gusset • zip fly • 2 slant pockets • hip pocket on the right and bellows pocket on the left with additional, attached pocket, each with flap and covered snap fastener • ruler pocket on the right (+pen pocket) • knee pockets.

2 and 3 |
Front trousers available
as 1-ply or 2-ply version.
Electric Arc
Flash protection
4 kA or 7 kA/4 kA

.....



MATERIAL: 55 % MODACRYLIC, 43 % COTTON, 2 % CARBON ·

FABRIC WEIGHT: approx. 275 g/m² (2-ply: + approx. 175 g/m²)

4kA: ATPV VALUE: $10.4 \text{ cal/cm}^2 + 468.9 \text{ kJ/m}^2 + \text{HAF VALUE: } 80.2\% + 10.4 \text{ cal/cm}^2 + 10.$

7kA/4kA: EBT50 VALUE: 20.0 cal/cm² · 837.3 kJ/m² · **HAF VALUE:** 88.9 %



HB-MODarc®

Our popular HB-MODarc® collection with reflective stripes is now certified acc. to EN 17353 for improved visibility. Again, the 2-layer models of this high-performance and modern arc-fault protective clothing are double-worked at the front, sleeves and front trousers and thus protect against electric arcs up to 7kA.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 47 | | F | 4 | | $\bigoplus_{\mathbb{C}}$ | | REGULAR SIZES |
|----------|--------|------------|----------------|-----------------------------|--------------------|-------------------------------|-----------|--------------------|--------------------------|--------------------------|---------------------|
| 1 | | 2251 | grey/black | IEC 61482-2 | | | | | | : | |
| <u>'</u> | | 2041 | navy/royal | 1-ply: APC 1 | EN ISO 11612 | | | • | | ISO 15797 | 14 50 0 |
| : | | 2251 | grey/black | 2-ply: APC 2* | A1+A2/B1/ C1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 13034 Type 6 | EN 17353 Type B3 | Washing temperature 60°C | 46-58 & : 94-110 |
| 2 ,3 | | 2188 | black/grey | *Front part and sleeves/ | | | | • | | 0U L | |
| | | 45 | navy | front trousers | | | | | | | |

FIELDS OF APPLICATION: Public services, energy suppliers, plant construction, electrical installation



Ladies models as well as more colours available in just 21 days. See page 236.

Higher visibility:

Patched flame-retardant reflective stripes suited for industrial laundry, certified acc. to EN 17353

Completely manufactured in roof-tile design

Reflective stripes, suited for industrial laundry



BLOUSON 4kA REFLECTIVE STRIPES

Arc flash class 1

Part number 4kA: 01072 10107 050 + COLOUR NO. Garment weight: approx. 895 g

BLOUSON 7kA/4kA REFLECTIVE STRIPES

Arc flash class 2

Part number 7kA/4kA: 01072 10107 051 + COLOUR NO. Garment weight: approx. 970 g

Two-coloured • raw white contrast stitching • stand-up collar with covered snap fastener • covered zip • 2 front pockets (1 as an attached pocket) with flap, covered snap fastener and tab to open • 1 inner pocket left with snap fastener • 2 side pockets with zip • sleeve hem adjustable with snap fastener covered on inside • attached waistband with covered snap fastener • leasing label • standard pictograms on front as FR direct stitching • flame-retardant reflective stripes suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471.











ARC & ENERGY







TROUSERS 4kA REFLECTIVE STRIPES

Arc flash class 1

Part number 4kA: **01072 20074 037 + COLOUR NO.**

01072 20074 039 45

Garment weight: approx. 765 g

TROUSERS 7kA/4kA REFLECTIVE STRIPES

Arc flash class 2

Part number 7kA/4kA: **01072 20074 038 + COLOUR NO. 01072 20074 040 45**

Garment weight: approx. 880 g

Two-coloured • raw white contrast stitching • waistband with covered button closure • zip fly • 2 slant pockets • 1 hip pocket on the right and 1 bellows pocket on the left with additional attached pocket – each with flap, covered snap fastener and tab to open • 1 ruler pocket on the right (+pen pocket) • knee pockets with hook & loop fastener • flame-retardant reflective stripes suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471.

BIB AND BRACE TROUSERS 4kA REFLECTIVE STRIPES

Arc flash class 1

Part number 4kA: **01072 50055 031 + COLOUR NO.**

01072 50055 033 45

Garment weight: approx. 890 g

BIB AND BRACE TROUSERS 7kA/4kA REFLECTIVE STRIPES

Arc flash class 2

.....

Part number 7kA/4kA: 01072 50055 032 + COLOUR NO. 01072 50055 034 45

Garment weight: approx. 1,005 g

Two-coloured • raw white contrast stitching • stretch braces with fixlock buckle • bib with outer pocket with flap and covered snap fastener • straight kidney protection • 2 side accesses with stretch gusset • zip fly • 2 slant pockets • hip pocket on the right and bellows pocket on the left with additional attached pocket – each with flap and covered snap fastener • ruler pocket on the right (+pen pocket) • knee pockets • flame-retardant reflective stripes suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471.

MATERIAL: 55 % MODARCRYLIC, 43 % COTTON, 2 % CARBON ·

FABRIC WEIGHT: approx. 275 g/m² (2-ply: + approx. 175 g/m²)

4kA: ATPV VALUE: 10.4 cal/cm² · 468.9 kJ/m² · **HAF VALUE:** 80.2 % · **7kA/4kA: EBT50 VALUE:** 20.0 cal/cm² · 837.3 kJ/m² · **HAF VALUE:** 88.9 %



HB-MODarc®

Now also for women: As an additional layer of clothing, our shirts increase the protective function and thus extend the possible uses of PPE. The intelligent clothing solutions in our extensive HB-MODarc® collection thus cover many areas of work. Our new sweatshirt even offers arc fault class 2 and stands for a contemporary PPE look.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 43 | | 4 | 40+ | O S S S S S S S S S S S S S S S S S S S | REGULAR SIZES |
|-------|--------|------------|-------------|----------------------|------------------------------------|------------|-------------|---|---------------|
| 1 2 | | 45 | navy | | : | : | | | |
| 11,21 | | 521 | cement grey | | FN 100 11/10 | | | | S–2XL |
| | | 228 | orange | IEC 61482-2 APC 1 | EN ISO 11612 A1+A2/B1/ C1/F1 | 511.4410.5 | 511.40750.0 | - | 3-Z/L |
| 21 | | 50 | light grey | | | EN 1149-5 | EN 13758-2 | | |
| 3 ,4 | | 45 | | | | | | | 2XS-L |
| 5 | | 45 | navy | IEC 61482-2 APC 2 | EN ISO 11612 A1/B1/C1 | : : | | ISO 15797 | S-2XL |

FIELDS OF APPLICATION: Plant construction, pipeline and line construction, electricians, public services, steel works, switch gear construction, communication, gas and water networks, network engineers



POLO SHIRT 4kA, LONG SLEEVE

Arc flash class 1

Part number: 01244 80011 011 + COLOUR NO.

Garment weight: approx. 300 g

Single-coloured • piqué polo-shirt • collar with board and covered snap fasteners • sleeve cuff with modern covering seam • leasing label • seams in contrast colour • standard pictograms as flame retardant direct embroidery on the right sleeve cuff.

1 and 2 Standards pictograms as flame retardant embroidery



T-SHIRT 4kA, LONG SLEEVE

Arc flash class 1

Part number: 01244 80010 007 + COLOUR NO.

Garment weight: approx. 295 g

Single-coloured • piqué T-shirt • round neck • sleeve cuff with modern covering seam • leasing label • seams in contrast colour • standard pictograms as flame retardant direct embroidery on the right sleeve cuff.













LADIES POLO SHIRT 4kA, LONG SLEEVE

Arc flash class 1

Part number: 01244 80022 000 45 Garment weight: approx. 270 g

Single-coloured • piqué polo-shirt • collar with board and covered snap fasteners • sleeve cuff with modern covering seam • leasing label • seams in contrast colour • standard pictograms as flame retardant direct embroidery on the right sleeve cuff.





LADIES T-SHIRT 4kA, LONG SLEEVE

Arc flash class 1

Part number: 01244 80022 002 45 Garment weight: approx. 265 g

Single-coloured • piqué T-shirt • round neck • sleeve cuff with modern covering seam • leasing label • seams in contrast colour • standard pictograms as flame retardant direct embroidery on the right sleeve cuff.

SWEATSHIRT 7kA

Arc flash class 2

Part number: **01279 80023 005 45** Garment weight: approx. 650 g

Single-coloured • round neck • sleeve with knitted cuffs • knitted waistband • standard pictograms as FR direct embroidery on the lower left sleeve • leasing label.

1 to 4 MATERIAL: 54% MODACRYLIC, 44% COTTON, 2% CARBON

ATPV VALUE: 6.4 cal/cm² · **HAF VALUE:** 70.1 % · **FABRIC WEIGHT:** approx. 215 g/m² ·

5 MATERIAL: 54% MODACRYLIC, 44% COTTON, 2% CARBON .

More sizes available - see size table on page 244

ATPV VALUE: $6.4 \text{ cal/cm}^2 \cdot 794.96 \text{ kJ/m}^2 \cdot \text{FABRIC WEIGHT: approx. } 405 \text{ g/m}^2$



HB-PROtection®

Modern and comfortable arc fault protection: that is HB-PROtection®. The lightweight material mix convinces in arc flash performance. The extremely soft fabric ensures a good fit and plenty of freedom of movement. The processed cotton creates a pleasant wearing sensation. The 2-layer 7kA/4kA models are double-worked at the front and sleeves.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 43 | | | 4 | | | REGULAR SIZES |
|------|--------|------------|----------------|---|------------------------------------|-------------------------------|-----------|--------------------|-------------|----------------|
| 1 | | 2177 | navy/dark grey | IEC 61482-2 1-ply: APC 1 | | | | | • | |
| 2 ,3 | | 2175 | dark grey/navy | 2-ply: APC 2* *Front part and sleeves/ front trousers | EN ISO 11612 A1+A2/B1/ C1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 13034 Type 6 | ISO 15797 | 46-58 & 94-110 |
| 1 | | 2177 | navy/dark grey | IEC 61482-2 | | | | | | |
| 2 | | 2175 | dark grey/navy | APC 2 | | | | | : : : | |

FIELDS OF APPLICATION: Metal industry, public services, electricians, pipeline and line construction, communication, gas and water networks



Also ladies models available – in just 21 days. See page 236.



The 7kA version is completely doubled



JACKET 4kA

Arc flash class 1

Part number 4kA: **01072 10112 020 2177** Garment weight: approx. 835 g

JACKET 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: **01072 10112 018 2177** Garment weight: approx. 910 g

JACKET 7kA

Arc flash class 2

Part number 7kA: **01072 10112 019 2177** Garment weight: approx. 945 g

Two-coloured • stand-up collar with covered snap fastener • covered zip • 2 breast pockets with covered zip fastener, left pocket with tap to open • 1 inner breast pocket with additional pen pocket and hook&loop fastener • 2 side pockets with zip fastener • sleeve hem with reflective pipes • no high-visibility protective clothing acc. to EN ISO 2047 and EN 17353 • back with 2 movement pleats • enlongated back as kidney protection • sleeve opening with gusset • sleeve hem with gusset and covered hook&loop fastener • added waistband • FR standard pictograms on the front.









ARC & **ENERGY**





TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01072 20074 017 2175

Garment weight: approx. 730 g

TROUSERS 7kA/4kA

Arc flash class 2

Part number partially 7kA/4kA: 01072 20074 018 2175

Garment weight: approx. 795 g

TROUSERS 7kA

Arc flash class 2

Part number 7kA: 01072 20074 035 2175

Garment weight: approx. 860 g

Two-coloured • waistband with covered button closure • zip fly • ergonomic knees • 2 slant pockets • 2 hip pockets and 2 bellow pockets - each with flap and covered snap fasteners • knee pockets with reflective pipes • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.



BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number 4kA: **01072 50055 015 2175**

Garment weight: approx. 855 g

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

.....

Part number partially 7kA/4kA: 01072 50055 016 2175

Garment weight: approx. 970 g

Two-coloured • stretch braces with fixlock buckle • straight kidney protection • elastic waistband all around • 2 side access with gusset • slit with zip • ergonomic knees • 2 slant pockets • bib pocket with covered snap fastener • 2 hip pockets • 2 bellow pockets - each with flap and covered snap fastener • knee pockets with reflective pipes • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

MATERIAL: 55 % MODACRYLIC, 43 % COTTON, 2 % CARBON ·

FABRIC WEIGHT: approx. 275 g/m² (2-ply: + approx. 175 g/m²) .

[HB-PROtection] **4kA: ATPV VALUE:** 10.4 cal/cm² · 435 kJ/m² · **HAF VALUE:** 80.2 % ·

7kA/4kA: EBT50 VALUE: 20.0 cal/cm² · 837.3 kJ/m² · **HAF VALUE:** 88.9 %





HB-PROtection® Green Turtle

Our HB-PROtection® Green Turtle shirt is made with organic cotton. It offers modern design as well as a comfortable, ergonomically improved "Comfort Fit". The fabric has a very low weight and provides most high wearing comfort – and inherent flame retardancy. Additionally it offers reliable protection against Arc Flash and antistatic properities. Therefore, it is suited for many working areas and the perfect complement for many HB product lines.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | 4 | 40+ | | REGULAR SIZES |
|------|--------|------------|-------------|----------------------|------------------------------------|-----------|------------|-----------|---------------|
| | | 45 | navy | | 5W 100 44 440 | | | | 39/40-47/48 |
| 11 | | 52 | medium grey | IEC 61482-2 APC 1 | EN ISO 11612 A1+A2/B1/ C1/F1 | EN 1149-5 | EN 13758-2 | ISO 15797 | 39/40-4//46 |
| 2 | | 45 | navy | | 01/11 | | : | : | 36-48 |

FIELDS OF APPLICATION: Heat and flame exposed workplaces, energy suppliers, public services, plant engineering and construction, electricians



Band collar with



1 On request the shirt is also available in tight fitting "Body Fit".

Part number: **01251 60025 000 + COLOUR-NO.**

45 navy 52 middle grey



Arc flash class 1

Part number: **01251 60026 000 + COLOUR-NO.** Garment weight: approx. 440 g

Single-coloured • Comfort Fit • turn-down collar with snap fastener • front zipper with covered snap fastener on both sides • preformed sleeves • chest pocket with flap and sleeve cuff with gusset – each with covered snap fastener • FR Leasing label • standard pictograms as FR embroidery an right sleeve cuff.



Embroiderd standard pictograms







ARC & **ENERGY**



What is the Organic Content Standard?



Organically grown cotton according to OCS 100 has been used in this shirt. Organic Content Standard 100 enables independent assessment, verification and traceability of the exact organic fiber content in the

product. The OCS 100 certificate confirms that the orga-





LADIES SHIRT 4kA

Arc flash class 1

Part number: 01251 60029 000 45 Garment weight: approx. 390 g

Single-coloured • Comfort Fit • turn-down collar with snap fastener • front zipper with covered snap fastener on both sides • preformed sleeves • dart at chest height • chest pocket with flap and sleeve cuff with gusset – each with covered snap fastener ullet FR Leasing label • standard pictograms as FR embroidery an right sleeve cuff.

MATERIAL: 54% MODACRYLIC, 44% COTTON (organic), 2% CARBON ·

FABRIC WEIGHT: approx. 195 g/m²

ATPV VALUE: 6.9 cal/cm² · 288.7 kJ/m² · EBT50 VALUE: 7.1 cal/cm² · ELIM: 6.4 cal/cm²

.....

(HB-PROtection*)

HB-MODarc&vis®

HB-MODarc&vis® stands for modern multifunctional PPE and is suitable for work applications that require several standards in combination with warning and arc flash protection. The combination of blouson and trousers or bib and brace trousers achieves high visibility protection class 3. The two-layer models are doubled at the front, sleeves and front trousers and offer protection against electric arcs up to 7kA/class 2.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 43 | | | 4 | | PROPERTY. | REGULAR SIZES |
|---------------|---|------------|-------------------------------------|---|--|------------------------------------|-------------------------------|-----------|--------------------|---|----------------|
| 1 , 2 , 3 | | 2112 | fluores- cent yellow/ navy | EN ISO 20471 Blouson: Class 2 Trousers, Bib and brace trousers: Class 1 | IEC 61482-2 1-ply: APC 1 2-ply: APC 2* *Front part and sleeves/ front trousers | EN ISO 11612 A1+A2/B1/ C1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 13034 Type 6 | ISO 15797 Washing temperature 60°C | 46–58 & 94–110 |
| FIELDS C | FIELDS OF APPLICATION: Public services, public transport and construction, electricians, energy suppliers | | | | | | | | | | |



Also ladies models available – in just 21 days. See page 236.



suitable for industrial laundry

Reflective stripes,



Pockets with handy tab to open

BLOUSON 4kA

Arc flash class 1 Part number 4kA: **01072 10107 028 2112** Garment weight: approx. 940 g

BLOUSON 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: **01072 10107 033 2112** Garment weight: approx. 1,055 g

Two-coloured • parts subject to heavy soiling in blue • raw white contrast stitching • stand-up collar with covered snap fastener • covered 2-way zip • 2 front pockets with flaps, covered snap fasteners and tab to open • 1 inner pocket left with snap fastener • 2 side pockets with zip • sleeve hem adjustable with snap fastener covered on inside • attached waistband with covered snap fastener • standard pictograms on front as FR direct stitching • flame-retardant reflective stripes suitable for industrial laundry.

Front part and sleeve available as 1-ply or 2-ply version

Electric Arc Flash protection 4kA or 7kA/4kA











ARC & **ENERGY**





1, 2 and 3 Achieves as suit (blouson combined with trousers or bib and brace trousers)

EN ISO 20471 Class 3

TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01072 20074 000 2112 Garment weight: approx. 815 g

TROUSERS 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: 01072 20074 001 2112 Garment weight: approx. 915 g

Two-coloured • parts subject to heavy soiling in blue • raw white contrast stitching • attached waistband with covered button closure • slit with zip-fly • 2 slant pockets • 1 hip pocket on the right and 1 bellows pocket on the left with additional attached pocket- each with flap, covered snap fastener and tab to open • 1 pocket for folding rule on the right (+ pen pocket) with flap • knee pockets with hook&loop fastener • flame-retardant reflective stripes suitable for industrial laundry.

BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01072 50055 000 2112 Garment weight: approx. 910 g

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: 01072 50055 001 2112

Garment weight: approx. 1,040 g

Two-coloured • parts subject to heavy soiling in blue • stretch braces with fixlock buckle • straight kidney protection • 2x side access with stretch gusset • slit with zip • 2 slant pockets • bib pocket, hip pocket on the right and bellows pocket on the left with additional attached pocket - each with flap and covered snap fastener • folding rule pocket on the right (+ pen pocket) with flap • knee pockets • flame-retardant reflective stripes suitable for industrial laundry.



2 and 3 Front trousers available as 1-ply or

Electric Arc Flash protection 4kA or 7kA/4kA

.....



MATERIAL: 55% MODACRYLIC, 43% COTTON, 2% CARBON .

FABRIC WEIGHT: approx. 275 g/m² (2-ply: + approx. 175 g/m²)

4kA: ATPV VALUE: 10.4 cal/cm² · 435.4 kJ/m² · **HAF VALUE:** 80.2 % · **7kA/4kA: EBT50 VALUE:** 20.0 cal/cm² · 837.3 kJ/m² · **HAF VALUE:** 88.9 %



HB-MODarc&vis®

Our most comprehensive product line HB-MODarc&vis®, which we present on the following pages, is a universal talent. The shirts offer multi-risk protection for underneath – and in summer also for outside! They are suitable for work areas that require multiple standards in combination with UV and high visibility. The FR vest with hi-vis protection is the ideal complement for many applications.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 13 | | 4 | 40+ | O I I | REGULAR SIZES |
|----------|--------|------------|-----------------------------|-------------------------|-------------|--|-----------|------------|-----------|---------------|
| 1 2 | | 2397 | fluorescent orange/ navy | | IEC 61482-2 | EN ISO 11612 A1/B1/C1/F1 | | EN 197EO 9 | | S–2XL |
| 3 4 | | 2112 | fluorescent yellow/navy | EN ISO 20471 Class 2 | APC 1 | EN ISO 11612 A1+A2/B1/ C1/F1 | EN 1149-5 | EN 13758-2 | - | XS-L |
| 5 | | 2112 | fluorescent yellow/navy | | - | EN ISO 11612 A1+A2/B1/ C1/F1 Partial body protection | | - | ISO 15797 | 1–4 |

FIELDS OF APPLICATION: Plant construction, pipeline and line construction, electricians, public services, steel works, switch gear construction, communication, gas and water networks







POLO-SHIRT 4kA LONG SLEEVE

Arc flash class 1 Part number: **01270 80012 003 2397** Garment weight: approx. 350 g With reflective stripes circumferentially.

POLO-SHIRT 4kA LONG SLEEVE

Arc flash class 1 Part number: **01270 80012 006 2397** Garment weight: approx. 350 g With reflective stripes like braces.

Two-coloured • long sleeves • collar with polo placket • closure band with flame-retardant snap fasteners • contrast stitching in raw white • flexible segmented and flame-retardant reflective stripes • standard pictograms as direct stitching on the bottom of the right sleeve • leasing label inside on the back.











ARC & ENERGY



POLO-SHIRT 4kA LONG SLEEVE

Arc flash class 1

Part number: **01244 80012 003 2112** Garment weight: approx. 300 g

LADIES POLO-SHIRT 4kA LONG SLEEVE

Arc flash class 1

Part number: **01244 80022 001 2112** Garment weight: approx. 250 g

Two-coloured • long sleeves • collar with polo placket • closure band with flame-retardant snap fasteners • contrast stitching in raw white • flexible segmented and flame-retardant reflective stripes • standard pictograms as direct stitching on the bottom of the right sleeve • leasing label inside on the back.







VEST HIGH VIS FR

High-Visibility FR

Part number: **01072 10129 001 2112** Garment weight: approx. 435 g

Two-coloured • round design, contrast stitchings in off-white • front closure via hook&loop fastener • HB logo as direct embroidery on back • flame-retardant reflective stripes attached in body language.





1 look & loop Tusteriei

Reflective stripes,

1 | , 2 | MATERIAL: 49% POLYESTER, 30% MODACRYLIC, 20% COTTON, 1% CARBON .

FABRIC WEIGHT: approx. 245 g/m² ·

ATPV VALUE: 8.9 cal/cm² ELIM: 6.8 cal/cm²

3 , 4 | MATERIAL: 54% MODACRYLIC, 44% COTTON, 2% CARBON · FABRIC WEIGHT: approx. 225 g/m² ·

ATPV VALUE: 6.4 cal/cm² · 267.78 kJ/m² · HAF VALUE: 70.1% ·

5 | **MATERIAL:** 55 % MODACRYLIC, 43 % COTTON, 2 % CARBON · **FABRIC WEIGHT:** approx. 275 g/m²



HI-VISION®

HB-MODarc&vis®

Breathable, windproof and highly functional – these are the softshell and fleece jackets in our versatile HB-MODarc&vis® range. Whether multi-risk protection plus welding protection or flame protection plus protection for cooler days: the jacket can be used flexibly and is thus the ideal clothing for every season, suitable for many different work applications. NEW: our sweatshirt as modern alternative for inside and outside works.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | 43 | | 4 | 40+ | P | REGULAR SIZES |
|------|--------|------------|---------------------------------|--------------|---------------------|----------------------|-----------------------------|-----------|------------|-----------|---------------|
| 1 | | 2007 | fluorescent yellow/dark blue | EN ISO 20471 | EN 14058 Class 1 | | EN ISO 11612 A1/B1/C2/F1 | | - | - | S-2XL |
| 2 | | 2112 | fluorescent yellow/navy | Class 2 | | IEC 61482-2 APC 2 | EN ISO 11612 A1/B1/C1 | EN 1147-3 | EN 13758-2 | ISO 15797 | XS-4XL |

FIELDS OF APPLICATION: For electricians, mains technicians and plant engineers, network engineers, in particular with public utility companies/energy suppliers



FLEECE JACKET 4kA

Arc flash class 1

Part number: **07015 19080 001 2007** Garment weight: approx. 1,090 g

Two-coloured • standard pictograms on the stand-up collar as flame-retardant direct embroidery • covered two-way zip below snap-fastener closure band • 2 side pockets with zip • sleeves with additional inner knitted wristband and wind-blocker • extended back with drawstring • flame-retardant reflective stripes in body-language for perfect all-around visibility.











Comfortable knitted cuffs

Standard pictograms as direct embroidery on the collar



SWEATSHIRT 7kA

Arc flash class 2

Part number: **01279 80023 004 2112** Garment weight: approx. 670 g

3-coloured • round neck • sleeve cuff with knitted cuffs • knitted waistband • stretchable and segmented flame retardant reflective stripes • standard pictograms as FR direct embroidery on the lower left sleeve • leasing label.

1 MATERIAL: 48% MODACRYLIC, 32% COTTON, 18% POLYESTER, 2% CARBON FABRIC WT.: approx. 360 g/m²

2 MATERIAL: 54 % MODACRYLIC, 44 % COTTON, 2 % CARBON FABRIC WEIGHT: approx. 405 g/m²

2 ATPV VALUE: 19.0 cal/cm² · 794.96 kJ/m²

HI-VISION®

HB-MODarc&vis®

The HB-MODarc&vis® parka with liner is suitable for a wide range of applications and thanks to the elaborate roof tile processing also for handling liquid metals. With the zip-in inner fleece it is unbeatable in cold weather. For optimum protection, the collar is reinforced with aramid fabric on the inside.

| ITEN | 1 COLOUR | COLOUR NO. | COLOUR NAME | | (†) | 13 | | | 4 | | | REGULAR SIZES |
|------|----------|------------|----------------------------|--|---------------------|----------------------|---------------------------------------|-------------------------------------|-----------|-------------------------|---------------------|---------------|
| 1 | | 2047 | black/navy | - | - | - | - | - | - | - | EN 14058 Class 1 | |
| 2 | | 2112 | fluorescent yellow/navy | EN ISO 20471 Class 2 | EN 343 Class 3/3 | IEC 61482-2 APC 2 | EN ISO 11612 A1+A2/B1/ C1/E1/F1 | EN ISO 11611 Class 1 A1+A2 | EN 1149-5 | EN 13034 Type PB [6] | - | S–2XL |
| 3 | | 45 | navy | Certification only in combination with parka | | | | | | | | |

FIELDS OF APPLICATION: Energy suppliers, public services, plant responsible, liquid metal works, steel works, metal construction, electricians, public transport areas, petrochemistry, catenary construction







FLEECE JACKET FR

Outdoor

Part number: **07015 19095 000 2047** Garment weight: approx. 700 g

Two-coloured • high band collar • closure band with zip fastener for closing or zipping into our HB-MODarc&vis® parkas • various buttons for fixation in parka • elastic wristband • material certified acc. to EN ISO 11612 A1/B1/C1/F1.



2







3 Combinable with zippable Inner fleece FR (1) on left page.

FR standard pictograms embroidered on the collar

PARKA7kA

Arc flash class 2

Part number: 01072 19098 000 2112 Garment weight: approx. 1,630 g

Two-coloured • flame-retardant upper material with liner • sealed seams • high band collar with covered buttons for hood attachment • hood suitable for wearing with or without helmet • covered 2-way zip fastener plus drip moulding with snap fasteners • 1 front pocket on the left, 1 mobile phone pocket (bellows) on the right, covered with laminated weather protection, and 2 side pockets (bellows) - each with flap and covered snap fastener • flame-retardant reflective stripes, suitable for industrial laundry • wristbands with strap and hook&loop fastener • FR standard pictograms on the collar.

HOOD

Arc flash class 2

Part number: 01072 79004 000 45 Garment weight: approx. 140 g

Single-coloured • flame-retardant upper material with liner • sealed seams • to be attached via buttons, and suitable to be worn with or without helmet • attached visor • field of vision adjustable via cord • height adjustable via cord at back of head • certification only in combination with parka.



1 MATERIAL: 48 % MODACRYLIC, 32 % COTTON, 18 % POLYESTER, 2 % CARBON .

FABRIC WEIGHT: approx. 360 g/m² · 2 | MATERIAL: 55 % MODACRYLIC, 43 % COTTON, 2 % CARBON // With liner ·

FABRIC WEIGHT: approx. 275 g/m² ·

OUTER PLY: **ATPV VALUE:** 10.4 cal/cm² · 435.4 kJ/m² · **HAF VALUE:** 80.2 %



Patchable reflective

stripes


Optimised Fit

HB-MODarc&vis®

Safety even in problematic weather plus antistatic as well as additional protection against chemicals, heat, flames, welding spatter and electric arcs. This high-visibility and weather protection outfit with direct laminate is lightweight, windproof and 100% water repellent. It can be perfectly combined with many other models of the HB-MODarc&vis® series.

| | ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | | T | 13 | | | 4 | | REGULAR SIZES |
|---|------|--------|------------|----------------------------|---------------------------|---------------------|----------------------|------------------|----------------|---------------------------|--------------------|---------------|
| | 1 | | | ci . | EN ISO 20471 : Class 3 | EN 343 Class 3/4 | IEC 61482-2 APC 2 | EN ISO 11612 | EN ISO 11611 | FN 11/0 F | EN 13034 Type 6 | S-2XI |
| : | 2 | | 2112 | fluorescent yellow/navy | EN ISO 20471 Class 1 | Class 3/4 | IEC 61482-2 APC 1 | A1/B1/ C1/F1 | Class 1 A1 | EN 1149-5 | Туре 6 | 3-ZAL |
| : | 3 | | | | : | | Certification o | inly in combinat | ion with parka | • • • • • • • • • • • • • | | One size |

FIELDS OF APPLICATION: Work in public places with additional hazards by arcs and flames, energy providers (also Off-shore industry), alternative energie providers, petrol chemistry, steelworks, electricians



Wristband adjustable via hook&loop fastener

on the front.





ARC & ENERGY





1 to 3 | 100% water-repellent

BIB TROUSERS 4kA

Arc flash class 1

Part number: **05019 29000 006 2112** Garment weight: approx. 1,060 g

Two-coloured • flame-retardant upper material as direct laminate • selaed seams • parts subject to heavy soiling in navy blue • adjustable elastic braces • high kidney protection with elastic • elasticated side access • 2 slant pockets • 1 hip and 1 bellows leg pocket – each with flap, covered hook & loop fastening and tab to open • adjustable foot width thanks to additional material and zip.

Reflective stripes, suitable for industrial laundry



Foot width adjustable with PCV-Zip thanks to additional material



HOOD

Arc flash class 2

Part number: **05019 79006 001 2112** Garment weight: approx. 200 g

Two-coloured • flame-retardant upper material as direct laminate • sealed seams • design with round shapes • separate hood, attachable via zip fastener and suited for wearing with/without helmet, with added peak • hood's field of vision adjustable via cord • hood height adjustable via hook & loop fastener at back of head.





MATERIAL: 55 % MODACRYLIC, 43 % COTTON, 2 % CARBON, POLYURETHAN-MEMBRANE ·

FABRIC WEIGHT: approx. 300 g/m² ·

OUTER PLY: **ATPV VALUE:** 22.2 cal/cm² · 929.3 kJ/m² · **HAF VALUE:** 87.8 %



HB-4Energy®

Great look, pleasant material and highly functional: HB-4Energy® combines lightweight rip-stop fabric with stretchy and abrasion-resistant elements to protect in all the right places. Elastic parts provide exceptionally high wearing comfort with plenty of freedom of movement. This modern multi-risk collection meets the current zeitgeist as it covers many work areas and is a real eye-catcher because of the different material structures.

| ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | 13 | | | 4 | | | | REGULAR SIZES |
|-------|--------|------------|--|--|------------------------------------|-------------------------------|------------------|--------------------|-------------------------|---|----------------|
| 1 | | 4027 | fluorescent yellow/ dark blue/navy | IEC 61482-2 1-ply: APC 1 | | • | | | EN ISO 20471 Class 2 | | |
| -1 -1 | | 4027 | fluorescent yellow/ dark blue/navy | 2-ply: APC 2* *Front part | EN ISO 11612 A1/B1/ C1/F1 | EN ISO 11611 Class 1 A1 | EN 1149-5 | EN 13034 Type 6 | | ISO 15797 Washing temperature 60°C | 46-58 & 94-110 |
| 2 ,3 | | 4028 | dark blue/fluores- cent yellow/navy | and sleeves/ front trousers 1 | 51711 | • | · · · · | | Class 1 | | |

:

FIELDS OF APPLICATION: Plant construction, electric installation, public services, electricians, pipeline construction, switch gear construction, networks (communication, gas, water), renewable energies



Jacket combined with light trousers achieves as suit

EN ISO 20471 Class 3.



chest-armpit area and in the shoulder blade

Elastic elements in the

Resistant and dirtrepellent material on shoulders, upper arms, elbows and cuffs



JACKET 4kA

Arc flash class 1

Part number: **01288 10219 000 4027** Garment weight: approx. 950 g

JACKET 7kA/4kA

Arc flash class 2

Part number: **01288 10219 001 4027** Garment weight: approx. 1,170 g

2-coloured • stand-up collar • covered zip with covered snap fasteners • 2 breast pockets with covered snap fasteners and flap • 2 breast pockets with covered snap fasteners and flap • 1 inner breast pocket with snap fastener • 2 side pockets with zip • reflective elements on breast pockets • back extension as additional kidney protection • sleeves with knitted cuffs as wind guard inside and outside with adjustable hook & loop fastener • segmented reflective stripes • standard pictograms as FR direct embroidery on front left.

1, 2 and 3

In the models with arc fault protection class 2, the material is doubled at the front sides and on the sleeves as well as on the front legs, and offers 7kA protection there









2 and 3

Elastic elements at the sides of the waistband, in the pocket opening, at the back of the trousers and in the crotch provide relief during kneeling activities



Side entry with elastic wedge



2 and 3

Resistant and dirt-repellent material on knee pockets and at the bottom of the inner leg

TROUSERS 4kA BIB AND BRACE TROUSERS 4kA

Arc flash class 1 Arc flash class 1

 Part number: 01288 20156 002 4027
 Part number: 01288 50106 002 4027

 Part number: 01288 20156 000 4028
 Part number: 01288 50106 000 4028

 Garment weight: approx. 770 g
 Garment weight: approx. 920 g

TROUSERS 7kA/4kA BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2
Part number: **01288 20156 003 4027**Arc flash class 2
Part number: **01288 50106 003 4027**Part number: **01288 50106 003 4027**

Part number: 01288 20156 001 4028
Garment weight: approx. 950 g

Part number: 01288 50106 001 4028
Garment weight: approx. 1,050 g

2-coloured • waistband raised at the back • reinforced belt loops • slit with zip • 2 wing pockets with trim and reflective elements • 2 back pockets with flap and press studs • 1 ergonomic ruler pocket on the right, 1 leg pocket on the left - both free-hanging and with flap, the leg pocket as bellows pocket with inside mobile phone pocket • knee pocket with Velcro fastening • segmented reflective stripes.

2-coloured • stretch straps with fixlock buckles • bib with bib pocket and flap with snap fastener • high kidney protection • slit with zip • 2 wing pockets with trimming and reflective elements • 2 hip pockets with flap and snap fasteners • 1 ergonomic ruler pocket on the right, 1 leg pocket on the left - both free-hanging and with flap, the leg pocket as bellow pocket with inside mobile phone pocket • knee pocket with hook &loop fastener • segmented reflective stripes.

MATERIAL: 44% MODACRYLIC, 30% COTTON, 20% POLYAMIDE, 5% ARAMIDE, 1% CARBON ·

<u>......</u>

FABRIC WEIGHT: approx. 260 g/m² (2-ply: + approx. 180 g/m²)

4kA: ATPV VALUE: 11.0 cal/cm² · 460.24 kJ/m² · **ELIM:** 10.0 cal/cm² · **7kA/4kA: ATPV VALUE:** 31.0 cal/cm² · 1297.04 kJ/m² · **ELIM:** 18.0 cal/cm²



➤ HB-MultiPro FR®

Windproof, water-repellent and breathable:

MultiPro FR® is the perfect all-round protection for autumn and winter: Eight certified standards offer an exceptionally high level of protection suited for many different work areas and applications. Our all-rounder also impresses with its contemporary look and stands for modern and hard-wearing PPE.

| ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | | T | 13 | | | 4 | | | REGULAR SIZES |
|------|--------|------------|---------------------------------|--------------|-----------|-------------|---|-----------------|-----------|----------------|---|---------------|
| | | 2425 | fluoresc. yellow/ stone grey | | | | | | | | | |
| اه | | 2143 | fluoresc. yellow/ dark blue | EN ISO 20471 | EN 343 | IEC 61482-2 | EN ISO 11612 A1/B1/C1/ E1/F1 | EN ISO 11611 | EN 1149-5 | EN 13034 | | S–2XL |
| 11 | | 2408 | fluoresc. orange/ stone grey | Class 3 | Class 3/4 | APC 2 | E1/F1 | Class 2 A1 | EN 1147-3 | Type PB [6] | - | 3-ZVL |
| | | 2147 | fluoresc. orange/ dark blue | | | | | | | | | |
| 2 | | 17 | fluoresc. yellow | | | Cartifi | | | | | | One size |
| 21 | | 18 | fluoresc. orange | | | | ertification only in combination with parka | | | parka | | One size |

FIELDS OF APPLICATION: Petrochemistry, catenary construction, energy suppliers



zipper

PARKA7kA

Arc flash class 2

Part number: 01121 19018 000 + COLOUR NO.

Garment weight: approx. 1,780 g

2-coloured • flame retardant outer fabric with liner, welded seams • stand-up collar with concealed push buttons, chin guard and zipper for hood • covered 2-way zip plus drip moulding • 2 chest pockets with flap and covered snap fastener • 2 side pockets with zipper • 1 inside pocket on the left with Velcro closure • extended back • waist and hem width adjustable via cord • inside zipper to hook the fleece jacket • sleeves bottom width adjustable with hook & loop closure • flame retardant, segmented FR reflective stripes • standard pictograms as FR embroidery at the front.

Stand-up collar with concealed push buttons, chin guard and zipper for hood









Additionally available hood





Elongated back



Segmented reflective stripes, flame retardant

HOOD

Arc flash class 2

Part number: 01121 79006 004 + COLOUR NO.

Garment weight: approx. 195 g

Single-coloured • flame-retardant upper material with liner • sealed seams • separate hood, attachable via zipper • field of vision adjustable via cord • hood height adjustable via hook &loop fastener at the back of the head • certification only in combination with parka.



MATERIAL: 31% POLYESTER, 28% MODACRYLIC, 20% ARAMIDE, 20% VISCOSE, 1% CARBON // With liner

FABRIC WEIGHT: approx. 320 g/m²

ATPV VALUE: 8.8 cal/cm² · 368.19 kJ/m² · ELIM: 8.0 cal/cm²



HB-MultiPro FR®


Just like the parka, the dungarees have many convenient features such as a chin guard, moisture barrier and numerous well-designed pockets. For even more effective protection against the cold, a matching fleece jacket can be added or, if required, worn on its own in the 4kA or 7kA version.

| ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | | (j | 13 | | | 4 | | | REGULAR SIZES |
|------|--------|------------|---------------------------------|-----------------|----------------|-----------------|---|-----------------|-----------|------------------|---------------------|---------------|
| 3 | | 48 | dark blue | - | - | 1-ply: APC 1 | EN ISO 11612 A1/B1/ C2/F1 EN ISO 11612 | _ | | - | EN 14058 Class 1 | |
| | | 528 | dark grey | | | 2-ply: APC 2 | A1/B2/ C2/F1 | | | | | |
| | | 2425 | fluoresc. yellow/ stone grey | | | | | | EN 1149-5 | | | S–2XL |
| 4 | | 2143 | fluoresc. yellow/ dark blue | EN ISO 20471 | EN 343 | LLG 01402-2 | EN ISO 11612 A1/B1/C1/ | EN ISO 11611 | EN 1147-3 | EN 13034 Type | _ | 3-ZAL |
| 4 | | 2408 | fluoresc. orange/ stone grey | Class 1 | Class 3/4 | APC 2 | E1/F1 | Class 2 A1 | | PB [6] | | |
| | | 2147 | fluoresc. orange/ dark blue | | | | | | | | | |

FIELDS OF APPLICATION: Petrochemistry, catenary construction, energy suppliers









Stand-up collar with fastening loop for hooking into parka HB-MultiPro FR® – for additional cold protection





FLEECE JACKET 4kA
Arc flash class 1
07015 19019 000 + COLOUR NO.
Garment weight: approx. 970 g

FLEECE JACKET 7kA

Arc flash class 2

07015 19019 001 + COLOUR NO. Garment weight: approx. 1,290 g

Single-coloured • stand-up collar with fastening loop for hooking into the outer jacket, to wear high necked or open • covered front zipper • 2 side pockets with covered zipper • hem adjustable with drawstring • sleeves bottom with knitted cuffs and 2 fastening loops each for hooking into the outer jacket • standards pictograms as direct embroidery on the front above the waistband.









Bib pocket with inside pen pocket with flap and covered snap fasteners



Comfortable knitted wedges at the waistband

Hook&loop fastening at the leg hem for

easy entry


BIB AND BRACE TROUSERS 7kA

Arc flash class 2

Part number: 01121 59006 000 + COLOUR NO.

Garment weight: approx. 1,430 g

Two-coloured • flame retardant outer fabric with liner, welded seams • adjustable length straps • diamond shaped kidney protection • 1 bib pocket with inside pen pocket with flap and covered snap fasteners • 2 wing pockets • inside back pockets with flap and concealed push buttons • 1 free-hanging folding rule pocket on the right and 1 bellows pocket on the left with inside cell phone pocket – each with flap and covered snap fasteners • entry on both sides with knitted wedge • slit with zipper • hook&loop fastener at the bottom of the trouser leg for easier entry • leg cuff with wetness barrier • flame retardant, segmented FR reflective stripes.



Segmented reflective stripes, flame retardant

1 MATERIAL: 48% MODACRYLIC, 32% COTTON, 18% POLYESTER, 2% CARBON · FABRIC WT.: approx. 360 g/m² 2 , 3 , 4 MATERIAL: 31% POLYESTER, 28% MODACRYLIC, 20% ARAMIDE, 20% VISCOSE, 1% CARBON // With liner ·

<u>.....</u>

FABRIC WEIGHT: approx. 320 g/m² ·

More sizes available - see size table on page 244

 $\textbf{ATPV VALUE: } 8.8 \text{ cal/cm}^2 \quad \cdot \quad 368.19 \text{ kJ/m}^2 \quad \cdot \quad \textbf{ELIM: } 8.0 \text{ cal/cm}^2$



NOMEX® Viskose

NOMEX® Viskose combines pleasant wearing comfort with reliable protection. Despite its light weight, the fabric offers high durability and good moisture absorption. Suitable for those who frequently change their posture when working. Finished with generous pockets. The outside knee pockets are made of particularly abrasion-resistant aramid.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | F | 4 | REGULAR SIZES |
|--------|-----------|------------|-------------|----------------------|-----------------------------|----------------------------|-----------|----------------|
| 1,2,3 | | 2030 | royal/navy | IEC 61482-2 APC 1 | EN ISO 11612 A1/B1/C1/F1 | EN ISO 11611 Class 1 A1 | EN 1149-5 | 46-58 & 94-110 |
| FIFLES | E ABBLICA | TION F | 1. 1.1. | | | | | |

FIELDS OF APPLICATION: Energy suppliers, public services, plant engineering and construction, electricians Many reflective pipings Inner mobile phone pocket with hook&loop fastener Closure band with covered zip fastener and covered hook&loop fasteners **BLOUSON 4kA** Arc flash class 1

E 3 4KA

Standards pictograms on the front as FR direct embroidery

Part number: 01031 10036 005 2030 Garment weight: approx. 770 g

Two-coloured • front part partially with 2 layers • front, back, sleeve and pocket flaps with FR reflective piping, suitable for industrial laundry • high band collar with strap and hook&loop fastener • 2 front and 2 side pockets – each with flap and covered hook&loop fastener • 1 inner mobile phone pocket on the right and 1 inner pocket on the left, each with hook & loop fastener • waistband with elastic band in side parts • wristband with covered snap fasteners • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.





ARC & ENERGY





TROUSERS 4kA

Arc flash class 1

Part number: **01031 20022 013 2030** Garment weight: approx. 700 g

Two-coloured • waistband with covered button and lateral elastic bands • zip fly • 2 slant pockets • 1 hip pocket and 1 ruler pocket on the right – each with flap • 1 bellow pocket on left leg with flap and hook&loop fastener • knee pockets with hook&loop fastener • FR reflective stripes at legs, suitable for industrial laundry • reflective piping on flaps • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number: **01031 50026 014 2030** Garment weight: approx. 840 g

Two-coloured • stretch braces with fixlock buckle • high-cut kidney protection • bib with outer pocket, ball-pen compartment and flap • zip fly • 2 slant pockets • 1 hip pocket and 1 ruler pocket on the right, 1 bellow pocket on left leg – each with flap and covered hook & loop fastener • side access on the left, adjustable via buttons • knee pockets with hook & loop fastener • FR reflective stripes at legs, and reflective piping on bib and flaps, suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

MATERIAL: 50% VISCOSE, 49% ARAMIDE, 1% CARBON · FABRIC WEIGHT: approx. 260 g/m²

ATPV VALUE: 9.9 cal/cm² · 414.4 kJ/m² · **HAF VALUE:** 79.0 %



NOMEX® Comfort

The NOMEX® Comfort fabric is fibre-inherently flame retardant and thus offers exceptionally high flame protection. With proper care, the protective function is maintained even after many washes. Due to the low material weight, NOMEX® Comfort offers protection and freedom of movement even in very uncomfortable workplaces with a particularly high risk potential.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 4.3 | | 4 | REGULAR SIZES |
|---------------|--------|------------|-------------|----------------------|-----------------------------|-----------|----------------|
| 1 2 , 3 | | 41 | royal | IEC 61482-2 APC 1 | EN ISO 11612 A1/B1/C1/F1 | EN 1149-5 | 46-58 & 94-110 |

 $\textbf{FIELDS OF APPLICATION:} \ \textbf{Plant engineering and construction, energy suppliers,}$

electric installation, public services, electricians





Front pocket with flap and covered snap fastener

Inner front pocket with flap and snap fasteners

BLOUSON 4kA

Arc flash class 1

Part number: **01042 10011 001 41** Garment weight: approx. 545 g

Single-coloured • turn-down collar • closure band with covered snap fasteners on both sides • 1 front pocket on the left with flap and covered snap fastener • 1 inner front pocket on the right with flap and snap fasteners • sleeve hem width adjustable via snap fasteners, covered inwards • added waistband • standard pictograms as FR direct embroidery on front • FR leasing label.







JACKET 4kA

Arc flash class 1

Part number: 01042 10003 001 41 Garment weight: approx. 580 g

Single-coloured • turn-down collar • closure band with snap fasteners covered on both sides • 1 front pocket on the left with flap and 2 piped pockets with covered pocket mouths, all with covered snap fasteners • 1 inner front pocket on the right with flap and snap fasteners • sleeve hem width adjustable via snap fasteners, covered inwards • standard pictograms as flame retardant embroidery • FR leasing label.

COAT 4kA

Arc flash class 1

Part number: 01042 40002 002 41 Garment weight: approx. 720 g

Single-coloured • lapel collar • closure band with snap fasteners covered on both sides • 1 front pocket on the left and 2 side pockets, each with flap and covered snap fastener • 1 inner front pocket on the right • sleeve hem width adjustable via covered snap fasteners • FR leasing label.

MATERIAL: 98 % ARAMIDE, 2 % CARBON FABRIC WEIGHT: approx. 260 g/m²

ATPV VALUE: 9.0 cal/cm² · 376.8 kJ/m² · **HAF VALUE:** 71.6 %



NOMEX® Comfort

The NOMEX® Comfort fabric is fibre-inherently flame retardant and thus offers exceptionally high flame protection. With proper care, the protective function is maintained even after many washes. Due to the low material weight, NOMEX® Comfort offers protection and freedom of movement even in very uncomfortable workplaces with a particularly high risk potential.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 4.3 | | 4 | REGULAR SIZES |
|---------|--------|------------|-------------|-------------|-----------------------------|-----------|----------------|
| 1 , 2 | | 41 | roval | IEC 61482-2 | EN ISO 11612 A1/B1/C1/F1 | EN 1149-5 | 46-58 & 94-110 |
| 3 | | •• | 10,41 | APC 1 | AI/BI/CI/FI | | 10 30 471 110 |

 $\textbf{FIELDS OF APPLICATION:} \ \textbf{Plant engineering and construction, energy suppliers,}$

electric installation, public services, electricians





TROUSERS 4kA

Arc flash class 1

Part number: **01042 20003 006 41** Garment weight: approx. 510 g

Single-coloured • added waistband with 7 belt loops • 2 side seam pockets • 1 hip pocket on the right with flap and snap fasteners • button fly • 1 ruler pocket on the right.

BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number: **01042 50002 012 41** Garment weight: approx. 655 g

Single-coloured • stretch braces with clamp-on clips • straightcut kidney protection • 1 outer bib pocket with covered snap fastener • side access on the left with buttoning • button fly • 2 side seam pockets with covered snap fastener • 1 hip pocket on the right with fl ap and covered snap fastener • 1 ruler pocket on the right.







COVERALL 4KA

Arc flash class 1

Part number: 01042 30017 001 41 Garment weight: approx. 990 g

Single-coloured ${ullet}$ turn-down collar, closure band with snap fasteners covered on both sides • 1 front pocket on the left, 1 side pocket on the left and 1 pocket pass-through on the left – each with covered snap fastener • 1 ruler pocket on the right • elastic waistband all round • sleeve hem width adjustable via snap fastener, covered inwards.

MATERIAL: 98 % ARAMIDE, 2 % CARBON · FABRIC WEIGHT: approx. 260 g/m² ·

ATPV VALUE: 9.0 cal/cm² · 376.8 kJ/m² · **HAF VALUE:** 71.6 %



INOTEC® Arc & Energy

Extraordinary protection and comfort, combined with low weight: INOTEC® Arc & Energy offers fibre-inherent flame protection, excellent arc flash protection, antiststatic properties plus retro-reflective stripes. The lightweight material and the clever cut provide wearers with an easy freedom of movement. Available as 1-ply or 2-ply version.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | 13 | | 4 | | | REGULAR SIZES |
|------|--------|------------|-------------|---|-----------------------------|-----------|--------------------|------------------|----------------|
| | | | | IEC 61482-2 1-ply: APC 1 | | | • | · · · · | |
| 1,2, | 5 | 2027 | royal/navy | 2-ply: APC 2* *Front part and sleeves/ front trousers | EN ISO 11612 A1/B1/C1/F1 | EN 1149-5 | EN 13034 Type 6 | ISO 15797 | 46–58 & 94–110 |

FIELDS OF APPLICATION: Plant engineering and construction, energy suppliers, electric installation, public services, electricians



2-ply version **Electric Arc Flash protection** 4kA or 7kA/4kA

Front part and sleeve available as 1-ply or

clothing according to EN ISO 20471 and EN 17353.







Matching bib and brace trousers:



Zip-in membrane as liner trousers for additional moisture protection made of 190 g/m² light-weight material double-layer laminate FR Part number: **05065 29004 000 519**



2 and 3 Flame-retardant reflective stripes, suitable for industrial laundry



TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01043 20000 004 2027

Garment weight: approx. 650 g

TROUSERS 7kA/4kA

Arc flash class 2

Part number 7kA/4kA: 01043 20000 005 2027

Garment weight: approx. 765 g

Two-coloured • attached waistband • 2 slant pockets • fly with covered zip • 2 back pockets with flap and snap fasteners • 1 folding rule pocket on the right • 1 leg pocket on the left with bellows pleat at the back, flap and snap fastener • reflective piping on saddle seam of back trousers • 2 reflective stripes at the bottom of the legs • no high-visibility clothing according to EN ISO 20471 and EN 17353.

BIB AND BRACE TROUSERS 4kA

Arc flash class 1

Part number 4kA: 01043 50100 004 2027

Garment weight: approx. 800 g

BIB AND BRACE TROUSERS 7kA/4kA

Arc flash class 2

.....

Part number 7kA/4kA: 01043 50103 000 2027

Garment weight: approx. 920 g

Two-coloured • stretch straps with fixlock buckles • high-cut kidney protection • outside bib pocket with flap, reflective piping and covered snap fasteners • 1 side entry on the left, adjustable with buttons • fly with zip • 2 wing pockets • 2 seat pockets and 1 bellows leg pocket on the left, each with flap and snap fasteners • 1 reinforced folding rule pocket on the right with flap and snap fasteners • no high-visibility clothing according to EN ISO 20471 and EN 17353.

MATERIAL: 98 % ARAMIDE, 2 % CARBON // FC-Equipment: fluorocarbon finish ·

Electric Arc Flash protection 4kA or 7kA/4kA

FABRIC WEIGHT: approx. 260 g/m² · 7kA/4kA: FABRIC WEIGHT: approx. 260 g/m² + approx. 180 g/m²


4kA: ATPV VALUE: 9.0 cal/cm² · 376.8 kJ/m² · **HAF VALUE:** 71.6 %







There are situations where you have to be able to rely one hundred percent on your protective equipment. Our products in the Heat, Splashes & Welding category offer the highest level of safety whenever things get hot – in direct contact with sparks and splashes of liquid metal as well as in extreme heat exposure.








Mainly perfect for classical welding work – and now with additional protection against liquid iron. The PROBAN® cotton is particularly strong and made with a unique FR equipment, offering high wearing comfort and breathability. It provides welders with reliable protection against heat, sparks and welding splatters according to EN ISO 11611. The flame resistance persists even after repeated laundry and cleaning cycles.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | <u></u> | | P P P P P P P P P P P P P P P P P P P | REGULAR SIZES |
|---------------|--------|------------|-------------|----------------------------|--------------------------------|---------------------------------------|----------------|
| 1 , 2 , 3 | | 52 | medium grey | EN ISO 11611 Class 2 A1 | EN ISO 11612 A1/B1/C1/E3/F1 | ISO 15797 | 46-58 & 94-110 |

 $\textbf{FIELDS OF APPLICATION:} \ \textbf{Steel works, metalworking industry, welding companies,} \\$

plant construction, foundries







Sleeve hem width adjustable via snap fasteners covered inside

JACKET

Welding protection class 2 Part number: **01272 10046 000 52** Garment weight: approx. 895 g Fabric weight: approx. 470 g/m²

Single-coloured • turn-down collar • closure band with snap fasteners on both sides • 1 chest pocket on the left and 2 side pockets, each reinforced and with flap and covered snap fastener • 1 inner front pocket on the right • sleeve hem width adjustable via covered inner snap fasteners • embroidered flame-retardant standard pictograms on the front.

HEAT, SPLASHES & WELDING



TROUSERS

Welding protection class 2 Part number: **01272 20084 003 52** Garment weight: approx. 905 g Fabric weight: approx. 470 g/m2

Single-coloured • added waistband with covered buttoning • covered button fly • 2 slant pockets • 1 hip pocket on the right with flap and covered snap fastener and 1 ruler pocket on the right, each reinforced.



BIB AND BRACE TROUSERS

Welding protection class 2 Part number: **01272 50062 001 52** Garment weight: approx. 1,105 g Fabric weight: approx. 470 g/m²

Single-coloured • stretch braces with clamp-on clips • straight kidney protection • 1 bib pocket and 1 reinforced hip pocket on the right, each with flap and covered snap fastener • covered button fly • 2 side seam pockets and 1 ruler pocket on the right, each reinforced.



Stretch braces with clamp-on clips

Side accesses

with buttoning

.....

i.....i



MATERIAL: 100 % COTTON .

FABRIC WEIGHT: approx. $470 \, g/m^2$

HB-WeldersFORCE®

Modern and comfortable PPE in several colour combinations:
With HB-WeldersFORCE®, we are adding two specialised fabrics for welding protection to our range.
Two qualities for flexible use: a 450 g/m² version for permanent welding work with larger amounts of sparks and higher radiant heat, and a lighter 350 g/m² version for occasional welding work with smaller sparks.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | MATERIAL WEIGHT | | | 4 | | REGULAR SIZES |
|----------|--------|--------------|---|--------------------|---------------------------------------|-------------------------------|-----------|-----------|----------------|
| | | 2027 2041 | royal/navy navy/royal | 350 g/m² | EN ISO 11612 A1+A2/B1/C1/ E2/F1 | EN ISO 11611 Class 1 A1+A2 | | ISO 15797 | 46-58 & 94-110 |
| 1 | | 2043 | navy/medium grey anthracite/medium grey | 450 g/m² | | EN ISO 11611 Class 2 A1+A2 | EN 1149-5 | | |
| 3 | | 45 | navy | 350 g/m² | | EN ISO 11611 Class 1 A1+A2 | | | |
| | | 58 | anthracite | 450 g/m² | • | EN ISO 11611 Class 2 A1+A2 | | | |

FIELDS OF APPLICATION: Steel works, metalworking industry, plant construction



Specially arranged pockets make it easier to reach in with gloves

BLOUSON 350

Welding protection class 1

Part number: **01144 10000 015 + COLOUR NO.**

Garment weight: 820g

BLOUSON 450

Welding protection class 2

Part number: 01209 10000 015 + COLOUR NO.

Garment weight: 1.070g

Two-coloured • stand-up collar • front with snap fasteners, covered on both sides • 2 breast pockets and 2 integrated side pockets, each with flap and covered snap fastener • FR let-in collar • sleeve hem width adjustable with plastic snap fastener • standard pictograms as FR direct embroidery on the front • manufactured in roof tile design.









2 Attached knee pockets and the free-hanging folding rule pocket make it easier to work when kneeling



Elastic waistband



2



TROUSERS 350

Welding protection class 1

Part number: **01144 20000 012 + COLOUR NO.**

Garment weight: 765g

TROUSERS 450

i.....i

Welding protection class. 2

Part number: **01209 20000 012 + COLOUR NO.**

Garment weight: 980g

Single-coloured • attached waistband with elastic band on both sides and button fastening on the outside • fly with covered zipper • 2 wing pockets • 2 back pockets, 1 ruler pocket on the right • each with flap and covered snap fastener • 1 mobile phone pocket on the left with flap and hook&loop fastener • knee pockets with covered hook&loop fastener • manufactured in roof tile design.

MATERIAL: 79 % COTTON, 10 % POLYESTER, 1 % CARBON • **FABRIC WEIGHT:** approx. 350 g/m² • approx. 450 g/m²



Both versions are designed in the same look to ensure that employees are uniformly equipped in line with requirements. The flame-retardant and reinforced cotton ensures good wearing properties and the addition of polyester for greater strength and dimensional stability, so that the jacket, trousers and bib & brace can withstand many industrial washes.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | MATERIAL WEIGHT | | | 4 | PR OBS OBS OBS OBS | REGULAR SIZES |
|------|----------|--------------|---|--------------------|---------------------------------------|-------------------------------|-----------|--------------------------------|----------------|
| | | 2027 2041 | royal/navy navy/royal | 350 g/m² | | EN ISO 11611 Class 1 A1+A2 | | | |
| 1 | | 2043 2382 | navy/medium grey anthracite/medium grey | 450 g/m² | EN ISO 11612 A1+A2/B1/C1/ E2/F1 | EN ISO 11611 Class 2 A1+A2 | EN 1149-5 | ISO 15797 | 46-58 & 94-110 |
| 2 ,3 | | 45 | navy | 350 g/m² | : : | EN ISO 11611 Class 1 A1+A2 | | | |
| | E ADDUCA | 58 | anthracite | 450 g/m² | · · · · · · · · · · · · · · · · · · · | EN ISO 11611 Class 2 A1+A2 | | | |

FIELDS OF APPLICATION: Steel works, metalworking industry, plant construction



Elastic knitted inserts on the dungarees make it easier to put on and take off and to work in uncomfortable positions



BIB AND BRACE TROUSERS 350

Welding protection class 1

Part number: 01144 50100 000 + COLOUR NO.

Garment weight: 900g

BIB AND BRACE TROUSERS 450

Welding protection class 2

Part number: 01209 50100 000 + COLOUR NO.

Garment weight: 1.165g

Single-coloured • flame-retardant stretch braces with Fixlock buckles • straight kidney protection • 2 side slits with knitted gusset • 2 side seam pockets • 1 outer bib pocket, 2 back pockets, 1 ruler pocket on the right • each with flap and covered snap fastener • 1 cell phone pocket on the left with flap and hook&loop fastener • slit processing with covered zipper • knee pockets with covered hook&loop fastener • manufactured in roof tile construction.





POSSIBLE COLOUR COMBINATIONS - AVAILABLE IN TWO DIFFERENT FABRIC WEIGHTS



Thanks to the smooth surface and elaborate roof tile manufacture, beads of sweat and metal splashes do not stick to the clothing, but roll off downwards.

MATERIAL: 79 % COTTON, 10 % POLYESTER, 1 % CARBON **FABRIC WEIGHT:** approx. 350 g/m² · approx. 450 g/m²

HB-4welders® 2.0

Feel safe when welding: HB-4welders® 2.0 provides high-quality PPE for welders working under extreme conditions. It is perfectly suited for heavy duty welding work. SECAN® quality textiles have been tried and tested for many years, including extensively in the industrial laundry sector. Protection against molten metal splashes, sparks, welding beads and radiant heat.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | 4 | 13 | | REGULAR SIZES |
|---|--------|------------|-----------------------|-------------------------------|---------------------------------------|-----------|----------------------|-----------|----------------|
| 1 | | 2205 | dark navy/medium grey | | | | | • | |
| 2 7 | | 458 | dark navy | EN ISO 11611 Class 2 A1+A2 | EN ISO 11612 A1+A2/B1/C1/ F3/F1 | EN 1149-5 | IEC 61482-2 APC 1 | ISO 15797 | 46-58 & 94-110 |
| 21,31 | | 52 | medium grey | | 20/11 | | | | |
| FIELDS OF APPLICATION: Welding companies, steel works, metalworking industry, foundries, plant construction | | | | | | | | | |





1, 2 and 3 Ergonomic cut for more freedom of movement

BLOUSON

Welding protection class 2 Part number: **01237 10125 001 2205** Garment weight: approx. 1,175 g

Two-coloured • seamed with contrast colour off-white • band collar with covered snap fastener • closure band with covered PVC zip and covered snap fastener • 2 front pockets (+ mobile phone pocket on the right) with flap and covered snap fasteners • additional border on the lower arms • sleeve hems with adjustable covered snap fasteners • standard pictograms as direct FR embroidery















2

2 and 3 Ruler pocket with additional pen pocket

Flame-retardant stretch braces with useful fixlock buckle

Side entry with elastic knit wedge

2 and 3 Bellow pocket with additional mobile phone pocket inside





TROUSERS

Welding protection class 2
Part number: **01237 20060 034 + COLOUR NO.**

Garment weight: approx. 970 g

Single-coloured • seamed with contrast colour off-white • added waistband with covered buttoning • fly with zip • 2 slant pockets • 1 hip pocket and 1 ruler pocket on the right (+ pen pocket) • 1 bellow pocket on the left (+ mobile phone pocket inside) – each with flap and covered snap fastener • knee pockets with adjustable hook & loop fastener.



Also models for ladies available - delivered in just 21 days.

See page 236.

.....

......

BIB AND BRACE TROUSERS

Welding protection class 2

Part number: **01237 50041 065 + COLOUR NO.**

Garment weight: approx. 1,130 g

Two-coloured • seamed with contrast colour offwhite • stretch braces with fixlock buckle • straight kidney protection • two-side access • PVC zip fly • 2 slant pockets • bib with outer pocket, flap and covered snap fastener • 1 hip pocket, 1 ruler pocket (+ pen pocket) and 1 bellows pocket (+ mobile phone pocket) – each with flap and covered snap fastener • knee pad pockets with adjustable covered hook &loop fastener.

MATERIAL: 89 % COTTON, 10 % POLYAMIDE, 1 % CARBON ·

FABRIC WEIGHT: approx. 390 g/m²





HB-ComFlex®

Comfortable, resilient and flexible: HB-ComFlex® combines elastic denim with resistant high-tech fabric in particularly exposed areas, for permanent intensive welding and heavy flex works as well as risky work situations such as overhead welding. The elastic denim provides the necessary freedom of movement and high wearing comfort. Worn solo, the denim is suitable for less exposed areas and medium to heavy welding work.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | PRO Order Orde Orde | REGULAR SIZES |
|---------|--------|------------|----------------------|----------------|-------------------------------|--|----------------|
| ا ما ما | | 397 | dark denim | EN ISO 11612 | EN ISO 11611 Class 2 A1+A2 | ISO 15797 | 46-58 & 94-110 |
| 11,21 | | 2404 | dark denim/dark navy | A1+A2/B1/C1/E2 | Class 2 A1+A2 | 130 13777 | 40-36 & 94-110 |

FIELDS OF APPLICATION: Welding companies, metalworking industry, plant construction, ship building









The denim gets a very individual used look after washing



Elasticated side

Free hanging pocket pouches on both pockets

Trim made of hightech fabric

Knee pockets





TROUSERS

Welding protection class 2

Part number: **01281 20000 007 397** (Denim)

Garment weight: approx. 930 g

Part number: 01281 20000 006 2404

(Denim + high-tech fabric)

Garment weight: approx. 940 g

Trim of high-tech fabric on front trousers • knee pocket with adjustable hook & loop fastener • pocket pouch of folding rule • leg pocket hanging free.

Single-coloured/two-coloured • set-in waistband with side elastic band and patent button to the outside • slit with zip • 2 wing pockets • 2 hip pockets, 1 folding rule pocket on the right and one leg pocket on the left, each with flap and covered snap fastener • mobile phone pocket in left leg pocket • ergonomically shaped knees due to darts • roof tile manufacture.



Elastic denim allows comfortable working with every movement

MATERIAL DENIM: 94 % COTTON, 4 % POLYESTER, 2 % ELASTANE · FABRIC WEIGHT: approx. 425 g/m² ·

MATERIAL HIGH-TECH FABRIC: 40 % ARAMIDE, 30 % MODACRYLIC, 20 % LYOCELL, 9 % POLYAMIDE, 1% CARBON ·

.....

FABRIC WEIGHT: approx. 430 g/m²



HB-ComFlex® is a modern industrial washable mix&match PPE that can be adapted to different areas of use and workplaces. All jacket, trouser and bib&brace garments can be combined with each other. The collection is complemented by a vegan welding apron that meets the requirements of the leasing industry to a particularly high degree.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | | REGULAR SIZES |
|------|--------|------------|----------------------|--------------------------------|-------------------------------|-----------|----------------|
| -1 | | 397 | dark denim | | | | 46-58 & 94-110 |
| 31 | | 2404 | dark denim/dark navy | EN ISO 11612 A1+A2/B1/C1/E2 | EN ISO 11611 Class 2 A1+A2 | ISO 15797 | 40-36 & 94-110 |
| 4 | | 458 | dark navy | | | | 46/48-58/60 |

FIELDS OF APPLICATION: Welding companies, metalworking industry, plant construction, ship building



BIB AND BRACE TROUSERS

Welding protection class 2

Part number: **01281 50100 008 397** (Denim)

Garment weight: approx. 1,040 g

Part number: **01281 50100 007 2404** (Denim+high-tech fabric)


Garment weight: approx. 1,190 g

Trim of high-tech fabric on front trousers • knee pocket with

adjustable hook & loop fastener • pocket pouch of folding rule • leg pocket

hanging free.

Single-coloured/two-coloured • flame-retardant stretch straps with fixlock buckle • high-cut kidney protection • 2 comfortable side entrances made of knitted material • 2 wing pockets • 2 back pockets, one reinforced ruler pocket on the right and one reinforced leg pocket on the left – each with flap and covered snap fastener • mobile phone pocket in left leg pocket • shaped knees due to darts • roof tile manufacture.











The vegan welding apron



Back belt adjustable with press studs

APRON WITH SLEEVES

Welding protection class 2

Part number: **01285 70069 000 458** (High-tech fabric)

Garment weight: approx. 1,020 g

Single-coloured • stand-up collar with concealed press stud • polo closure with concealed press studs • sack yoke • FR leasing collar • back belt adjustable with press studs • sleeve hem width adjustable with inside press stud • standards pictograms as FR direct embroidery • roof tile manufacture.

MATERIAL DENIM: 94 % COTTON, 4 % POLYESTER, 2 % ELASTANE · FABRIC WEIGHT: approx. 425 g/m² ·

MATERIAL HIGH-TECH FABRIC: 40 % ARAMIDE, 30 % MODACRYLIC, 20 % LYOCELL, 9 % POLYAMIDE, 1% CARBON ·

FABRIC WEIGHT: approx. 430 g/m²



This SECAN® collection offers reliable protection against liquid iron splashes (E3). The robust material with antistatic properties is also ideal for heavy welding work.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | 4 | PRO OFFI OFFI OFFI OFFI OFFI OFFI OFFI OF | REGULAR SIZES |
|-------|--------|------------|-------------|-------------------------------|---------------------------------------|-----------|---|----------------|
| 1,2,3 | | 52 | medium grey | EN ISO 11611 Class 2 A1+A2 | EN ISO 11612 A1+A2/B1/C1/ E3/F1 | EN 1149-5 | ISO 15797 | 46-58 & 94-110 |

FIELDS OF APPLICATION: Steel works, metalworking industry, welding companies, foundries, plant construction, heat exposured workplaces



Standard pictograms as direct embroidery



Adjustable sleeve hem

JACKET

Liquid metal Fe

Part number: **01248 10048 001 52** Garment weight: approx. 870 g

Single-coloured • turn-down collar • closure band with snap fasteners covered on both sides • 1 inner front pocket on the right • 1 front pocket on the left and 2 side pockets – each with flap and covered snap fasteners • sleeve hem width adjustable via inside covered snap fastener • standard pictograms as direct embroidery on the front • FR leasing label.





TROUSERS

Liquid metal Fe

Part number: **01248 20003 026 52** Garment weight: approx. 810 g

Single-coloured • added waistband with covered buttoning • covered button fly • 2 side seam pockets • 1 hip pocket on the right and 1 ruler pocket on the right – each with flap and covered snap fastener.





2 and 3 Hip pocket and ruler pocket – each with flap and covered snap fastener

BIB AND BRACE TROUSERS

Liquid metal Fe

Part number: **01248 50002 049 52** Garment weight: approx. 950 g

Single-coloured • stretch braces with clamp-on clips • straight kidney protection • 1 outer bib pocket with flap and covered snap fastener • side access on the left and fly, each with buttoning • 2 side seam pockets with covered snap fastener • 1 hip pocket on the right and 1 ruler pocket on the right – each with flap and covered hook&loop fastener.



MATERIAL: 98 % COTTON, 2 % CARBON FABRIC WEIGHT: approx. 420 g/m²



HB-Iron Pro

Our bestseller for protection against liquid iron splashes (E3). The SECAN® quality guarantees flame resistance up to 50 industrial washes and the reflective strips increase visibility. The ergonomic fit and modern design are just as impressive as the performance with maximum protection against heat radiation, welding splatters and large quantities of molten iron. NEW: a matching shirt made of lighter fabric, also with roof tile manufacture.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | F | 4 | 43 | $\bigoplus_{\mathbb{C}}$ | | REGULAR SIZES |
|---------|--------|------------|---|---------------------------------------|-------------------------------|-----------|----------------------|--------------------------|-----------|----------------|
| 1 ,2 ,3 | | 3011 | medium grey/orange/ fluorescent yellow | EN ISO 11612 A1+A2/B1/C1/ E3/F1 | EN ISO 11611 Class 2 A1+A2 | | IEC 61482-2 APC 1 | EN 17353 | | 46-58 & 94-110 |
| 4 | | 22 | pure orange | EN ISO 11612 A1+A2/B1/C1/ | EN ISO 11611 | EN 1149-5 | | Type B2 | ISO 15797 | 39/40 – 47/48 |
| . 4 | | 52 | middle grey | E1/F1 | Klasse 1 A1+A2 | | - | | • | 37/40-4//40 |

FIELDS OF APPLICATION: Steel works, metalworking industry, welding companies, foundries, plant construction, heat exposured workplaces



side pockets

JACKET

Liquid metal Fe

Part number: **01248 10000 011 3011** Garment weight: approx. 1,070 g

Three-coloured • stand-up collar with plastic snap fastener • fastening strip with snap fasteners, covered on both sides • 2 breast pockets with flap and covered snap fasteners • 2 set-in side pockets with plastic zipper • ergonomically shaped sleeves • sleeve hem width adjustable via plastic snap fasteners • flame-retardant reflective stripes with fluorescent yellow backing, suited for industrial laundry • no high-visibility protective clothing according to EN ISO 20471 • FR leasing label • standard pictograms as FR direct embroidery on the front • roof tile manufacture.



Higher visibility:

Patched flame-retardant reflective stripes with fluorescent backing, suited for industrial laundry, certified acc. to EN 17353



TROUSERS

Liquid metal Fe

Part number: **01248 20000 000 3011** Garment weight: approx. 840 g

Three-coloured • fitted waistband with covered button fastening • fly with zip • 2 side seam pockets • 1 back pocket on the right, 1 folding rule pocket on the right and one leg pocket on the left • each with flap and covered snap fastener • shaped knees due to darts • flame-retardant reflective stripes on the leg with fluorescent yellow backing, suited for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 • roof tile manufacture.







HEAT, SPLASHES & WELDING



TTO WEAR

Trousers + bib and brace trousers also available with knee pockets in just 21 days. See page 237.



NEW: The matching shirt – with reflective striping in accordance with EN 17353 for increased visibility





BIB AND BRACE TROUSERS

Liquid metal Fe

Part number: **01248 50100 005 3011** Garment weight: approx. 1,100 g

Three-coloured • flame-retardant stretch braces with fixlock buckle • high-cut kidney protection • 2 side entrances with elastic knitted wedge • slit with zip • 2 side seam pockets • 1 bib pocket with flap and covered snap fastener • 1 hip pocket on the right, 1 ruler pocket on the right and one leg pocket on the left • each with flap and covered snap fastener • shaped knees due to darts • flame-retardant reflective stripes on the leg with fluorescent yellow backing, suited for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 • roof tile manufacture.

SHIRT

Liquid metal Fe

Part number: **01116 60026 005 + COLOUR NO.**

Garment weight: approx. 495 g

Single-colored • Comfort fit • turn-down collar with bar and covered snap fastener • collar with additional plastic snap fastener to close the raised collar • closure with snap fasteners covered on both sides • ergonomically shaped sleeves • chest pockets with flaps and sleeve cuffs with gusset, each with covered snap fasteners • FR reflective stripes with yellow backing, suited for industrial laundry • no high-visibility clothing protective acc. to EN ISO 20471 • FR leasing collar • standard pictograms as FR direct embroidery on right cuff • roof tile manufacture.

MATERIAL: 98 % COTTON, 2 % CARBON

FABRIC WEIGHT: 1 to 3 approx. 420 g/m² · 4 approx. 250 g/m²





Fans of natural fibres should try out this work clothing with low flammability: Marlan contains 30 % wool and 50 % viscose. This fibre combination offers efficient protection against liquid aluminium and iron as metal splashes easily drip off. The polyamide part of the fabric improves the mechanical resistance.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | PRO PRO PRO PRO PRO PRO PRO PRO PRO PRO | REGULAR SIZES | | |
|---------------|---|------------|-------------|----------------------------|---------------------------------------|--|-------------------------|--|--|
| 1 , 2 , 3 | | 45 | navy | EN ISO 11611 Class 1 A1 | EN ISO 11612 A1/B1/C1/D3/ E3/F1 | ISO 15797 | 46-58 & 94-110 46-58 | | |
| FIELDS C | FIELDS OF APPLICATION: Aluminium working industry, foundries, metalworks, heat exposed workplaces | | | | | | | | |







JACKET

Liquid metal Al + Fe

Part number: **01180 10214 000 45** Garment weight: approx. 838 g

Single-coloured • turn-down collar • contrast stitching on shoulders and on the sides • set-in sleeve with pivot spacing • 1 breast pocket on left with flap • front pocket on right with flap • front closure with snap fasteners • manufactured in roof tile design.

TROUSERS

Liquid metal Al + Fe

Part number: **01180 20148 000 45** Garment weight: approx. 791g

Single-coloured • 2 slant pockets • covered front closure with snap fasteners • right-side ruler pocket • right-side back pocket.







BIB AND BRACE TROUSERS

Liquid metal Al + Fe

Part number: **01180 50101 000 45** Garment weight: approx. 963 g

Single-coloured • adjustable braces • bib pocket • size-adjustable hip width • side pockets • covered front closure with snap fasteners • right-side ruler pocket • right-side back pocket • manufactured in roof tile design.

SHIRT

.....

Liquid metal Al + Fe

Part number: **01180 60028 000 45** Garment weight: approx. 647 g

Single-coloured • mandarin collar • set-in sleeve with pivot spacing • covered front closure with hook&loop fastener FR • manufactured in roof tile design.

MATERIAL: 50 % VISCOSE FR · 30 % WOOL · 20 % POLYAMIDE ·

FABRIC WEIGHT: approx. $365 \, g/m^2$





HB-HeavyMetal Pro®, available in two weight classes, is the answer to the special requirements for PPE for working with high temperatures or molten metal. The material has good moisture management and is also very comfortable to wear thanks to its balanced composition. Just like the reflective stripes, it is suited for industrial laundry.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | FABRIC WEIGHT | | | 4 | 13 | $\bigoplus_{\mathbb{C}}$ | PRO DE CONTRACTOR DE CONTRACTO | REGULAR SIZES |
|------|--------|------------|---------------------------------|---------------------|--|------------------|-----------|----------------------|--------------------------|--|----------------|
| | | 2080 | anthracite grey/ pure orange | approx. 340 g/m² | EN ISO 11612 A1+A2/ B1/C1/D2/ E2/F1 | | | | | | |
| 1,2 | | 2138 | anthracite grey/ petrol | approx. 430 g/m² | EN ISO 11612 A1+A2/ | | EN 1149-5 | IEC 61482-2 APC 1 | EN 17353 Type B2 | ISO 15797 | 46-58 & 94-110 |
| | | 2204 | navy/ anthracite grey | 430 g/m² | B1/C1/D3/ E3/F1 | Class 2 A1+A2 | | | | | |

FIELDS OF APPLICATION: Aluminium working industrie, foundries, steelworks, heat-exposed workplaces



Side pockets with covered PVC zip

JACKET 340

Liquid metal Al + Fe

Part number: 01221 10000 012 + COLOUR NO. (340 g/m²)

Garment weight: approx. 830 g

JACKET 430

Liquid metal Al + Fe

Part number: **01218 10000 012 + COLOUR NO.** (430 g/m²)

Garment weight: approx. 1,050 g

Two-coloured • stand-up collar with covered snap fastener • covered front closure with snap fasteners • 2 attached breast pockets with flaps and covered snap fasteners • 2 side pockets with covered PVC zip • ergonomically formed sleeves • sleeve width adjustable via snap fasteners • segmented FR reflective stripes, suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 • leasing neck label • embroidered FR standard pictograms on the front • manufactured with roof tile design.











2

1 and 2 Enjoy more freedom of movement thanks to the ergonomic cut

Leg pocket with mobile phone pocket inside

Knee pockets with adjustable hook&loop fastening





TROUSERS 340

Liquid metal Al + Fe

Part number: **01221 20000 009 + COLOUR NO.** (340 g/m²)

Garment weight: approx. 730 g

TROUSERS 430

Liquid metal Al + Fe

Part number: **01218 20000 009 + COLOUR NO.** (430 g/m²)

Garment weight: approx. 990g

Two-coloured • added waistband with buttoning • covered zip fly • 2 side seam pockets • 2 back pockets, 1 ruler pocket on the right and 1 leg pocket on the left - each with flap and covered snap fastener • free hanging pocket pouch of ruler and leg pocket (+ mobile phone pocket inside) • knee pockets with adjustable hook \& loop fastener ${}^{\bullet}$ segmented FR reflective stripes, suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 • manufactured with roof tile design.

MATERIAL: 01221 50 % COTTON, 39 % MODACRYLIC, 10 % VISCOSE, 1 % CARBON · MATERIAL: 01218 52 % COTTON, 37 % MODACRYLIC, 10 % VISCOSE, 1 % CARBON ·

.....

<u>.....</u>

FABRIC WEIGHT: approx. 340 g/m² (01221) · approx. 430 g/m² (01218)





The dynamic design of HB-HeavyMetal Pro® in trendy colours and ergonomic features stands for modern PPE with a high protection level. The standard profile also includes increased visibility certified according to EN 17353. The flame-retardant reflective strips are segmented and patched for optimum freedom of movement.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | FABRIC WEIGHT | | | 4 | 4.3 | $\bigoplus_{\mathbb{C}}$ | PRO EST OFF OFF OFF OFF OFF OFF OFF OFF OFF OF | REGULAR SIZES |
|-------|--------|------------|---------------------------------|---------------------|--|----------------------------------|---|----------------------|--------------------------|---|----------------|
| | | 2080 | anthracite grey/ pure orange | approx. 340 g/m² | EN ISO 11612 A1+A2/ B1/C1/D2/ E2/F1 | EN ISO 11611 Class 1 A1+A2 | | | | | |
| 1,2,3 | | 2138 | anthracite grey/ petrol | approx. 430 g/m² | EN ISO 11612 A1+A2/ | EN ISO 11611 Class 2 | | IEC 61482-2 APC 1 | EN 17353 Type B2 | ISO 15797 | 46-58 & 94-110 |
| | | 2204 | navy/ anthracite grey | 430 g/m² | E3/F1 | A1+A2 | | | | | |
| 4 | | 45 | navy | approx. | EN ISO 11612 A1+A2/ | EN ISO 11611 | | _ | _ | | 39/40-47/48 |
| 4 | | 58 | navy anthracite grey | 250 g/m² | B1/C1/D1/ E2/F1 | Class 1 A1+A2 | | | | | 37/40-4//40 |

FIELDS OF APPLICATION: Aluminium working industrie, foundries, steelworks, heat-exposed workplaces



2 and 3 Pocket pouch of ruler and leg pocket free hanging

Enjoy more freedom of movement thanks to the ergonomic cut

1 to 4





BIB AND BRACE TROUSERS 340

Liquid metal Al + Fe

Part number: **01221 50100 009 + COLOUR NO.** (340 g/m²)

Garment weight: approx. 900 g

BIB AND BRACE TROUSERS 430

Liquid metal Al + Fe

Part number: **01218 50100 009 + COLOUR NO.** (430 g/m²)

Garment weight: approx. 1,170 g

Two-coloured • fix-lock stretch braces • breast bib pocket • high-cut kidney protection • one-side access • covered zip fly • 2 side seam pockets • 2 back pockets, 1 ruler pocket on the right and 1 leg pocket on the left - each with flap and covered snap fastener • free hanging pocket pouch of ruler and leg pocket (+mobile phone pocket inside) • knee pockets with adjustable hook &loop fastener • segmented FR reflective stripes, suitable for industrial laundry • no high-visibility protective clothing acc. to EN ISO 20471 • manufactured with roof tile design.







1 to 3 | Better visibility thanks to modern patched reflective stripes, flame retardant and suitable for industrial laundry, certified acc. to EN 17353





SHIRT

Liquid metal Al + Fe

Part number: 01109 60026 003 + COLOUR NO.

Garment weight: approx. 490 g

Single-coloured • Comfort Fit • turn-down collar with snap fastener • collar additionally with a plastic snap fastener to close when the collar is turned up • front zipper with covered snap fastener on both sides • preformed sleeves • chest pocket with flap and sleeve cuff with gusset – each with covered snap fastener • FR leasing label • standard pictograms as FR embroidery on right sleeve cuff • manufactured with roof tile design.

MATERIAL: 01221 and 01109 50 % COTTON, 39 % MODACRYLIC, 10 % VISCOSE, 1 % CARBON ·

MATERIAL: 01218 52 % COTTON, 37 % MODACRYLIC, 10 % VISCOSE, 1 % CARBON ·

FABRIC WEIGHT: approx. 340 g/m² (01221) · approx. 430 g/m² (01218) · approx. 250 g/m² (01109)

.....

.....





Prime selection with liquid aluminium and iron: VINEX® impresses by its extraordinary and highly efficient protective properties while working with liquid metals and being exposed to metal splashes. The inherent flame-retardant fabric offers with D3 / EN 11612 the most high certified protection against aluminium splashes. In addition the fabric is very soft and offers high wearing comfort. Now also with Electric Arc Flash protection.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4. | 989 100 100 100 100 100 100 100 100 100 10 | REGULAR SIZES |
|-------|--------|------------|-------------|--|----------------------|--|----------------|
| 1,2,3 | | 48 | dark blue | EN ISO 11612 A1+A2/B1/C1/D3/ E3/F1 | IEC 61482-2 APC 1 | ISO 15797 | 46-58 & 94-110 |
| 4 | | 40 | | EN ISO 11612 A1+A2/B1/C1/D1/ E1/F1 | - | 130 13777 | 39/40-47/48 |

 $\textbf{FIELDS OF APPLICATION:} \ \text{Aluminium industry, steel and metal works, foundries,} \\$

heat exposed workplaces



BLOUSON

Liquid metal Al + Fe

Part number: **01058 10015 005 48**Garment weight: approx. 960 g

Single-coloured • high band collar with covered hook & loop fastener • closure band with snap fasteners covered on both sides • 1 front pocket on the left and 2 side pockets – each with flap and covered snap fasteners • 1 inner pouch pocket on the right with snap fastener • FR leasing label • sleeve hem width adjustable via inwards covered snap fasteners.

TROUSERS

Liquid metal Al + Fe

Part number: **01058 20013 003 48** Garment weight: approx. 1,005 g

Single-coloured • added waistband with 7 belt loops and covered buttoning • covered snap fastener fly • 2 side seam pockets • 1 hip pocket and 1 ruler pocket on the right with flap and covered snap fastener • trouser leg manufactured in roof tile design.







Stand-up collar with flap and covered hook & loop fastener

2 and 3 Roof tile design makes liquid metal splashes easily drip off

BIB AND BRACE TROUSERS

Liquid metal Al + Fe

Part number: **01058 50012 003 48** Garment weight: approx. 1,130 g

Single-coloured • stretch braces with clamp-on clips • 1 inner bib pocket with snap fastener • 2 side seam pockets with covered snap fasteners, 1 hip pocket on the right and 1 ruler pocket on the right – each with flap and covered snap fastener • 1 side access on the left and button fly • trouser leg manufactured in roof tile design.

SHIRT, WITH STAND-UP COLLAR

Liquid metal Al + Fe

Part number: **01057 60002 004 48** Garment weight: approx. 540 g

Single-coloured • stand up collar with hook &loop fastening • front zipper with snap fasteners covered on both sides • left hand side chest pocket with flap and covered snap fasteners • sleeves with adjustable wristbands via covered snap fastener.

MATERIAL: 85 % VINYLAL, 15 % MODAL ·

FABRIC WEIGHT: 1 to 3 approx. 390 g/m² · 4 approx. 285 g/m²







Health protection for PPE wearers on hot days:

Our cooling garments reduce heat stress in extreme temperatures. The cooling effect, which lasts for several hours, is activated simply under the tap. The surface is dry again in a few seconds and the product is immediately ready for use.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | SIZES |
|---------|--------|------------|-----------------|-----------------------------|--|
| 1 , 2 | | 45 | navy | - | S–2XL |
| 3 | | 58 | anthracite grey | - | approx. 240 x 165 x 18 mm |
| 4 | | 46 | black | EN ISO 11612-A1 Material | Length: 90 cm/110 cm/130 cm; Width: 38 mm |

FIELDS OF APPLICATION: Heat and flame exposed workplaces, energy suppliers,

public services, plant engineering and construction, electricians

3-D COOL® Technology: Fast and long-lasting cooling in the right places and for several hours. The material stores the water and provides a clear cooling effect for several hours via

COOLING VEST

Accessories

Part number: **90026 16021 000 45** Garment weight: approx. 260 g

Single-coloured • V-neck • covered hook &loop fastener for variable width adjustment • body in short shape for health protection: the kidney area remains free of cooling • in a few seconds the product is evenly activated with water and the surface is dry again and the vest is ready for use • does not drip and there is no condensation • lowers the body temperature to a normal physiological level • 3D-high-tech microfiber fleece • outer fabric antibacterial thanks to natural silver ions • pleasantly light and sweat-absorbing • can be worn under any clothing • machine washable in the household laundry.



1 and 2 Antibacterial outer fabric

COOLING BANDANA

Accessories

Part number: **90026 76026 000 45** Garment weight: approx. 90 g

Single-coloured • with ties in the back area • back with tab for cooling the neck area • in a few seconds the product is evenly activated with water and the surface is dry again and the bandana is ready for use • does not drip and does not release condensation • 3D-high-tech microfiber fleece • outer fabric antibacterial thanks to natural silver ions • pleasantly light and sweat-absorbing • can be worn under any helmet or hood • machine washable in the household laundry.



HEAT, SPLASHES & WELDING



KNEE PADS

Accessories

Part number: **04033 76013 000 58** Garment weight: approx. 70 g

The lightweight and sturdy knee pads protect the knees and increase comfort during activities that require kneeling. Suitable for all HB trousers equipped with knee pockets. Even withstands several domestic washings if it remains in the knee pockets (Note: no industrial laundry).

Sale unit: 1 pair



BELT FR

Accessories

Part number: **01113 76012 000 46** Garment weight: approx. 80 g

Stretch belt made of flame-retardant knitted material with plastic buckle, suited for heat protection clothing. The certified material meets the requirements regarding combustion behaviour and heat resistance and shrinkage with industrial laundry according to EN ISO 11612-A1.



Flame-retardant plastic buckle

.....

i.....i

MATERIAL: 1 and 2 Outer material: 100% POLYESTER, inner material: 100% COOLINE® POLYESTER .

FABRIC WEIGHT: 1 and 2 approx. 580 g/m²



For works in high-temperature environments, we offer aluminised heat protection clothing from head to toe in four different materials, including two lightweight and very high-performance qualities. They complete our product range, including CLASSIC, COMFORT and COMFORT-Plus versions with numerous feature options. For example, the foundry coat is available in 84 and the heat protection jacket in 42 variants.









TEMPEX®-TREME HEAT MATERIAL OVERVIEW

The materials differ in terms of the composition and construction of the carrier material, the type of aluminisation, the weight and the specific protective properties against the various forms of heat load. Wearing comfort and mechanical strength also vary.

| Material name | CK-12/Z | AW-1/Y | KF-3/Z | CK-4/Z |
|-----------------------|--|---|--|---|
| Material number | 12014 | 12008 | 12003 | 12015 |
| Collection/Products | TEMPEX®-TREME HEAT COMFORT/COMFORT Plus | TEMPEX®-TREME HEAT COMFORT/COMFORT Plus | TEMPEX®-TREME HEAT CLASSIC | Gaiters and gloves |
| Material | 70 % preox, 30 % para-aramide | 100% aramide (70% recycled meta-aramide, 30% para-aramide) | 100% para-aramide | 70 % preox, 30 % para-aramide |
| Material weight | approx. 360 g/m² | approx. 420 g/m² | approx. 475 g/m² | approx. 690 g/m² |
| Carrier material | Twill | Knitted fabric with roughened nap | Herringbone twill | Twill |
| Aluminisation | Aluminum pigmented transfer film | PES film aluminised on both sides | Aluminum pigmented transfer film | Aluminum pigmented transfer film |
| Standards | EN ISO 11612 A1/B1/C3/D3/E3/F1 | EN ISO 11612 A1/B1/C4/D3/E3/F2 | EN ISO 11612 A1/B1/C3/D3/E3/F1 | EN ISO 11612 A1/B1/C3/D3/E3/F1 |
| Protection properties | High protection against radiant heat Very good protection from liquid metal spatters Very lightweight and soft design for high wearing comfort Good mechanical strength | Highest protection against radiant heat (C4) Very high thermal insulation and heat barrier Very good protection from liquid metal spatters Lightweight and very soft design for high wearing comfort | High protection against radiant heat Very good protection from liquid metal spatters Very high mechanical strength | High protection against radiant heat High protection against contact heat Very good protection from liquid metal spatters Very high mechanical strength |
| Detailed photo | | | | |

FIELDS OF APPLICATION:

Steelworks, aluminium-processing industry, foundries, heat-exposed workplaces, metal processing industry




TEMPEX®-TREME HEAT CLASSIC

We offer jacket, trousers, foundry coat and sleeve apron in the resistant material KF-3/Z in various designs. Choose between hook&loop- and Ruck-Zuck-fastening as well as different coat and jacket lengths (see model overview on page 240).

| ITEM | MAT. NO. | MATERIAL | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|----------------------|----------|----------|--------|------------|-------------|-----------------------------------|---------------|
| 1 to 4 | 12003 | KF-3/Z | | 15 | silver | EN ISO 11612 A1/B1/C3/D3/E3/F1 | 46/48-58/60 |









FOUNDRY COAT

Metalized heatprotection (C3) Part number: **12003 41030 000 15 (KF-3/Z)** Garment weight: approx. 1,520 g

Inner collar with flame-retardant cotton lining • front with covered hook&loop fastener FR • FR seams • length: approx. 130 cm.
Further available length: 140 cm.

APRON WITH SLEEVES

Metalized heatprotection (C3)
Part number: **12003 71130 000 15 (KF-3/Z)**

Garment weight: approx. 1,125 g

Neckline with FR molleton • opening with covered hook & loop fastener • hook & loop fastener on the back • ergonomic sleeves • sleeve width adjustable via snap fastener inside • all seams with FR thread • length: approx. 130 cm.









More lengths and variants available in just 21 days. See page 238.

JACKET

Metalized heatprotection (C3) Part number: **12003 11080 000 15 (KF-3/Z)** Garment weight: approx. 1,025 g

Inner collar with flame-retardant cotton lining • front with covered hook & loop fastener FR • FR seams • length: approx. 80 cm.
Further available lengths: 90 cm/100 cm.

TROUSERS

Metalized heatprotection (C3) Part number: **12003 2H003 000 15 (KF-3/Z)** Garment weight: approx. 1,131 g

Sewn-in adjustable suspenders • covered zip fly with snap fastener closure • FR seams.



TEMPEX®-TREME HEAT CLASSIC

Our bib and half apron are also available in the robust KF-3/Z material and are equipped with an adjustable hook & loop fastener for faster donning and doffing.

| ITEM | MAT. NO. | MATERIAL | COLOUR | COLOUR NO. | COLOUR NAME | | SIZES |
|---------|----------|----------|--------|------------|-------------|-----------------------------------|----------|
| 5 , 6 | 12003 | KF-3/Z | | 15 | silver | EN ISO 11612 A1/B1/C3/D3/E3/F1 | One size |





BIB APRON

Metalized heatprotection (C3) Part number: 12003 71131 000 15 (KF-3/Z) Garment weight: approx. 642 g

Neck strap • hook&loop fastener for closing • all seams with FR thread • length: approx. 130 cm.

HALF APRON

Metalized heatprotection (C3) Part number: 12003 71100 000 15 (KF-3/Z) Garment weight: approx. 511 g

Hook&loop fastening \bullet all seams with FR thread • length: approx. 100 cm.



2TO ZIWEAR

HEAT. **SPLASHES &** WELDING



Our COMFORT program stands for particularly high protection and optimised wearing comfort. All variants are available from stock in the very light material CK-12/Z and via our high-speed delivery service 21 TO WEAR® in the soft and highly insulating AW-1/Y. The aprons are available in several lengths.

| ITEM | MAT. NO. | MATERIAL | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|----------|----------|--------|------------|-------------|-----------------------------------|------------------------------------|
| 1,2 | 12014 | CK-12/Z | | 15 | silver | EN ISO 11612 A1/B1/C3/D3/E3/F1 | 46/48–58/60 Bib apron: One size |

.....



APRON WITH SLEEVES

Metalized heatprotection (C3)

Part number: 12014 71130 000 15 (CK-12/Z)

Garment weight: approx. 960 g

Neckline with FR molleton • opening with covered hook&loop fastener • hook&loop fastener on the back • ergonomic sleeves • sleeve width adjustable via snap fastener inside • all seams with FR thread • length: approx. 130 cm.

Further available length: 110 cm.

BIB APRON

Metalized heatprotection (C3) Part number: 12014 71131 000 15 (CK-12/Z) Garment weight: approx. 470 g

Neck strap • hook&loop fastener for closing • all seams with FR thread • length: approx. 130 cm. Further available length: 110 cm.



More lengths as well as variants in material AW-1/Y available within just **21 days.** See page 238.



TEMPEX®-TREME HEAT COMFORT

The COMFORT range includes jacket and foundry coat with ergonomically shaped sleeves (width-adjustable for the jacket), walking slit for the coat and several lengths and fastening options for both. The trousers have a comfort waistband and a hem-length fastener. All models offer excellent protection against larger iron and aluminium splashes (D3 and E3) and the AW-1/Y material offers maximum protection against radiant heat (C4).

| ITEM | MAT NO | MATERIAL | COLOUR | COLOUR NO | COLOUR NAME | | REGIII AR SIZES |
|---------------|----------|----------|--------|------------|-------------|-----------------------------------|-----------------|
| IILIVI | MAI. NO. | MAILKIAL | COLOOK | COLOOK NO. | COLOOK NAME | | REGOLAR SIZES |
| 3 , 4 , 5 | 12014 | CK-12/Z | | 15 | silver | EN ISO 11612 A1/B1/C3/D3/E3/F1 | 46/48-58/60 |



FOUNDRY COAT

Metalized heatprotection (C3)

Part number: 12014 41130 001 15 (CK-12/Z)

Garment weight: approx. 1,110 g

Ergonomic sleeves, width adjustable via snap fastener inside • inner collar with flame-retardant cotton lining • front with covered hook&loop fastener FR • walking slit • FR seams • length: approx. 130 cm. Further available lengths: 110 cm/120 cm/140 cm.









JACKET

Metalized heatprotection (C3)

Part number: 12014 11180 000 15 (CK-12/Z)

Garment weight: approx. 800 g

Ergonomic sleeves, width adjustable via snap fastener inside • inner collar with flame-retardant cotton lining \bullet front with covered hook & loop fastener FR \bullet FR seams • length: approx. 80 cm. Further available lengths: 90 cm/100 cm.

TROUSERS

Metalized heatprotection (C3)

Part number: 12014 21000 001 15 (CK-12/Z)

Garment weight: approx. 890 g

Sewn-in adjustable braces • covered zip fly with snap fastener • covered zip fly with hook&loop fastener • comfort waistband with side elastic band ullet inner waistband with FR molleton • quick access thanks to hook&loop fasteners at both sides of the legs • all seams with FR thread.



TEMPEX®-TREME HEAT COMFORT Plus

The COMFORT Plus program comprises the most comfortable equipment: the COMFORT versions are supplemented by additional features. In addition to the standard underarm ventilation, we offer optional additional back ventilation and, in the case of the caster coat, also the choice between a walking slit and the more comfortable concealed walking pleat for the best possible freedom of movement with optimum protection even when in action.

| | ITEM | MAT. NO. | MATERIAL | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|---|---------------|----------|----------|--------|------------|-------------|---------------------------------------|---------------|
| : | 1 , 2 , 3 | | AW-1/Y | : — : | 15 | silver | EN ISO 11612 A1/B1/C4/D3/ E3/F2 | 46/48-58/60 |



FOUNDRY COAT

Metalized heatprotection (C4) Part number: 12008 41130 022 15 (AW-1/Y) Garment weight: approx. 1,470 g

Ergonomic sleeves, width adjustable via snap fastener inside • inner collar with flame-retardant cotton lining • front with covered hook&loop fastener FR • with underarm and back ventilation • FR seams • walking slit • length: approx. 130 cm. Further available lengths: 110 cm/120 cm/140 cm.











All seams with FR thread

JACKET

Metalized heatprotection (C4)

Part number: 12008 11180 020 15 (AW-1/Y)

Garment weight: approx. 945 g

Ergonomic sleeves, width adjustable via snap fastener inside • inner collar with flame-retardant cotton lining • front with covered hook&loop fastener FR • with underarm and back ventilation • FR seams • length: approx. 80 cm. Further available lengths: 90 cm/100 cm.

TROUSERS

Metalized heatprotection (C4)

Part number: 12008 21000 001 15 (AW-1/Y)

Garment weight: approx. 995 g

Sewn-in adjustable braces • covered zip fly with snap fastener • covered zip fly with hook&loop fastener • comfort waistband with side elastic band ullet inner waistband with FR molleton • quick access thanks to hook&loop fasteners at both sides of the legs • all seams with FR thread.



TEMPEX®-TREME HEAT

The aluminized heat protection clothing is complemented by compatible face and head protection, individually combinable. These include head protection hoods in various designs – also with ventilation openings – as well as the matching visors and heat protection glasses.

| ITEM | MAT. NO. | MATERIAL | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|---------------------|----------|----------|--------|------------|-------------|---------------------------------------|---------------|
| 1 , 2 , 4 , 6 | 12003 | KF-3/Z | | | • | EN ISO 11612 A1/B1/C3/D3/E3/F1 | |
| 3 ,5 | 12008 | AW-1/Y | | 15 | silver | EN ISO 11612 A1/B1/C4/D3/ E3/F2 | One size |

PROTECTIVE HOOD, CHEST PROTECTION

Accessories

Part number: 12003 7H007 000 15 (KF-3/Z)

Garment weight: approx. 508 g

Shaped shoulder and chest area • elastic band in back • protective glass frame made of aluminum • storage loop • FR seams • approx. 600 mm long from the edge of the helmet (front and back side) • fits with helmets Phenol (item 90021 7Z006 011 68) and Poly (item 90022 7Z006 012 10) • fits with heat protection glass • sized 100 x 220 mm.



PROTECTIVE HOOD

Accessories

Part number: 12003 7H007 001 15 (KF-3/Z)

Garment weight: approx. 297 g

Elastic band in back • protective glass frame made of aluminum • storage loop • FR seams • approx. 150 mm long (back side) • fits with helmets Phenol (item 90021 7Z006 011 68) and Poly (item 90022 7Z006 012 10) • fits with heat protection glass • sized 100 x 220 mm.





PROTECTIVE HOOD, CHEST PROTECTION

Accessories

Part number: 12008 71001 002 15 (AW-1/Y)

Garment weight: approx. 415 g

Shaped shoulder and chest area • with two covered ventilation openings at the sides • elastic band in back • protective glass frame made from aluminium • storage loop • all seams with FR thread • side height approx. 50 cm from storage loop across shoulder • compatible with Phenol (item 90021 7Z006 011 68) and Poly helmet (item 90022 7Z006 012 10) • compatible with heat protection glass in size 100 x 220 mm.



21TO 21WEAR

HEAT, **SPLASHES &** WELDING



HELMET COVER

Accessories

Part number: 12003 7H009 000 15 (KF-3/Z)

Garment weight: approx. 184 g

Shaped neck protection • side snap fasteners for attaching a face shield • FR seams • fits with helmets Phenol (item 90021 7Z006 011 68) and Poly (item 90022 7Z006 012 10) • fits with face guard (item 12008 71010 000 15).



FACE GUARD

Accessories

Part number: 12008 71010 000 15 (KF-4/Z)

Garment weight: approx. 283 g

Protective glass frame made of aluminum • bendable wire for adjusting to head shape • side snap fasteners for attaching neck protection • FR seams • fits with helmet cover (item 12003 7H009 000 15) • fits with heat protection glass sized 100 x 220 mm.









CUFFS

Accessories

Part number: 12003 7H003 000 15 (KF-3/Z) Cuff made of aluminised Aramide • elastic band on both ends • length approx. 430 mm.



Elastic band on both ends

TEMPEX®-TREME HEAT

The aluminized heat protection clothing is complemented by compatible face and head protection which can be individually combined. This includes safety helmets, Bochum goggles and matching visors and heat protection glasses.

PROTECTIVE HELMET PHENOL

Accessories

Part number: 90021 7Z006 011 68

Straight shell • manufactured from phenolic resin fabric • 6-point webbed harness with genuine leather sweatband, foam cushion band and lock ratchet • antistatic, for use in hot zones (metal splashing), temperatures from -30 °C up to +150 °C • fits with all head protection hoods • fits with Flip-Up Mounting (item 90002 7Z019 004 15).

One size (51-64 cm)

gold Standards:





Fits with all head protection hoods

PROTECTIVE HELMET POLY

Accessories

Part number: 90022 7Z006 012 + COLOUR NO.

Straight shell with rain gutter • manufactured from fibreglassreinforced polycarbonate • 6-point webbed harness with genuine leather sweatband, foam cushion band and lock ratchet • for use in hot zones and electrical insulation (1000 V), temperatures from -30 °C up to +150 °C • fits with all head protection hoods • fits with Flip-Up Mounting (item 90002 7Z019 004 15).

One size (51-64 cm)

____ 10 white

25 red

Standards:

EN 50365



ference with practical twist lock

HEAT, **SPLASHES &** WELDING



FLIP-UP MOUNTING

Accessories

Part number: 90002 7Z019 004 15

For fastening face guard to protective helmet • with 2 flap closures and a plastic-coated suspension spring • fits with helmets Phenol (90021 7Z006 011 68) and Poly (90022 7Z006 012 10) • fits with all all-around visors sized 500 x 250 mm.

One size silver



BOCHUM GOGGLES

Accessories

Part number: 90001 7Z024 000 15

Aluminum edging • blackened wire mesh inside • protective glass holder • fits with Flip-Up Mounting (item 90002 7Z019 004 15) • fits with heat protection glass sized 120×60 mm.

silver Standards:





BOCHUM GOGGLES WITHOUT GLASS HOLDER

Accessories

Part number: 90001 7Z024 001 15

Aluminum edging • blackened wire mesh inside • fits with Flip-Up Mounting (item 90002 7Z019 004 15).

silver





The aluminized heat protection clothing is complemented by compatible face and head protection which can be individually combined. This includes safety helmets, Bochum goggles and matching visors and heat protection glasses.

PROTECTIVE WIRE SCREEN

Accessories

Part number: 90001 7Z025 001 15

Crimped edge • blackened wire mesh inside • fits with Flip-Up Mounting (item 90002 7Z019 004 15) • shape: 500 x 300 mm.



FURNACE VIEWING GLASS, CURVED

Accessories

Part number: 90005 7Z023 004 48

Curved laminated safety glass • special blue-coloured filter • colour-correcting • protection from radiant heat • protection from radiant heat • protection from short wave IR radiation • protection level 4-7 A-DIN • fits with head protection hoods (item 12003 7H007 000 15 or 12003 7H007 001 15) • fits with Face Guard (item 12008 71010 000 15) • shape: 100 x 220 mm.



LAMINATED SAFETY GLASS, GOLD

Accessories

Part number: 90006 7Z023 000 68

Curved laminated safety glass • gold-plated • protection from radiant heat • fits with head protection hoods (item 12003 7H007 000 15 or 12003 7H007 001 15) • fits with Face Guard (item 12008 71010 000 15) • shape: 100 x 220 mm.





POLYCARBONATE SCREEN GREEN, GOLD

Accessories

Part number: **90018 7Z023 002 68**

Curved laminated safety screen• gold-plated • protection from radiant heat • fits with head protection hoods (item 12003 7H007 000 15 or 12003 7H007 001 15) • fits with Face Guard (item 12008 71010 000 15) • shape: 100 x 220 mm.





EN 171









HEAT, SPLASHES & WELDING



ALL-AROUND VISOR CLEAR

Accessories

Part number: 90004 7Z010 002 00

Clear, flexible polycarbonate plate \bullet rounded shape: 500 x 250 x 1mm \bullet fits with Flip-Up Mounting (item 90002 7Z019 004 15).

neutral Standards:



FN 166

ALL-AROUND VISOR CLEAR, GOLD

Accessories

Part number: 90004 7Z010 000 68

Clear, flexible polycarbonate plate \bullet gold-plated \bullet protection from radiant heat (protection level 4-4) \bullet rounded shape: 500 x 250 x 1 mm \bullet fits with Flip-Up Mounting (item 90002 7Z019 004 15).

gold Standards:



EN 166

EN 171

ALL-AROUND VISOR GREEN, GOLD

Accessories

Part number: 90004 7Z010 001 33

Green-tinted, flexible polycarbonate plate \bullet gold-plated \bullet protection from radiant heat (Protection level 4-5) \bullet rounded shape: 500 x 250 x 1mm \bullet fits with Flip-Up Mounting (item 90002 7Z019 004 15).

green
Standards:



FN 166

EN 171

FURNACE VIEWING GLASS WITH COLOURED FILTER

Accessories

Part number: 90005 7Z023 001 48

Composite safety glass • special blue-coloured filter • colour-correcting • protection from radiant heat • protection from blinding light • protection from short-term IR radiation • protection level 4-7 A-DIN • fits with Bochum Goggles (item 90001 7Z024 000 15) • shape: $120 \times 60 \, \text{mm}$.

dark blue










TEMPEX®-TREME HEAT

Our new heat protection gloves are available in different variants, lengths and sizes and offer protection against thermal risks according to EN 407 as well as mechanical hazards according to EN 388 thanks to selected material combinations and insulation layers.

Protective gloves against thermal risks EN 407:2020

Protective gloves tested according to this standard protect against heat and/or fire. The actual protective performance depends on the test performed during certification and the level of performance achieved, with 1 being the lowest and 4 the highest. "X" means not tested.



| Test | Performance Level | | | | | | |
|--|-------------------|---------------|-------------|-------------|--|--|--|
| | 1 | 2 | 3 | 4 | | | |
| Combustion behavior Afterflame time (in sec.) Afterglow time (in sec.) | < 20 n.r. | < 10 < 120 | < 3 < 25 | < 2 < 5 | | | |
| Contact heat Contact temperature Tc (in °C) Threshold t1 (in sec.) | 100 > 15 | 250 > 15 | 350 > 15 | 500 > 15 | | | |
| Convective Heat Heat Transfer Index HTI (in sec.) | > 4 | > 7 | > 10 | > 18 | | | |
| Radiant heat Radiant heat transfer t24 (in sec.) | > 7 | > 20 | > 50 | > 95 | | | |
| Small splashes of molten metal Number of splashes | > 10 | > 15 | > 25 | > 35 | | | |
| Large splashes of molten metal Liquid iron splashes (in g) | 30 | 60 | 120 | 200 | | | |


⁴ means the highest and 1 means the lowest performance level. n.r. means "no requirement".

X means "not tested". 0 means "below the minimum requirements".

For higher durability in contact heat, we rely on selected materials and different insulation layers, especially in the palm area, so that protection against heat up to 500 °C can be reached there. High resistance to radiant heat and splashes of molten metal is achieved primarily through the use of aluminised materials.

Protective gloves against mechanical risks EN 388:2016

This standard specifies the test methods and performance requirements of protective gloves against mechanical risks. The specific protective performance depends on which test is carried out during certification and which performance level is achieved, 1 being the lowest and 5 the highest performance level. "X" means not tested.



| Test | Performance Level | | | | | | |
|--|-------------------|-----|------|------|----|--|--|
| | 1 | 4 | 5 | | | | |
| Abrasion resistance (Number of cycles) | 100 | 500 | 2000 | 8000 | | | |
| Cutting resistance (Factor) | 1,2 | 2,5 | 5,0 | 10,0 | 20 | | |
| Tear strength (in newton) | 10 | 25 | 50 | 75 | | | |
| Cutting strength (in newton) | 20 | 60 | 100 | 150 | | | |

5 means the highest and 1 means the lowest performance level. X means "not tested". 0 means "below the minimum requirements".

The choice of materials in the palm has a decisive influence on the mechanical properties and wear. The abrasion resistance and tear resistance are the focus of our requirements.



METALLISED HEAT PROTECTION GLOVES UP TO 500 °C CONTACT HEAT

| | | | MATERIAL LAYER CONSTRUCTION | | | | | |
|------|-----------------------|---------------------|---|-----------|-----------|----------------|-------|--|
| ITEM | | | UPPER | ISOLATION | LINING | LENGTH | SIZES | |
| 1 | | | Polyacrylnitril (Preox), Aramide, chrome split leather | 1-ply | | approx. 410 mm | | |
| 2 | EN 407 4 1 3 3 4 4 | EN 388 2 X 4 X X | Polyacrylnitril (Preox), Aramide, Para-Aramide | : | Cotton FR | approx. 450 mm | 11 | |
| 3 | | | Polyacrylnitril (Preox), Aramide, Para-Aramide | 2-ply | | approx. 440 mm | | |







3-FINGER GLOVES 410 + LEATHER

Accessories

Part number: **12015 71005 000 2271**

Two-coloured • 3-layer construction of the glove inside • good thermal insulation of the palm • very good protection against radiant heat • high abrasion resistance of the palm.

silver/stone grey

3-FINGER GLOVES 450 + ARAMIDE

Accessories

Part number: **12015 71003 001 2269**

Two-coloured • 4-layer construction of thumb and palm • very good thermal insulation of the palm • very good protection against radiant heat • good abrasion resistance of the palm.

silver/yellow

MITTENS 440 + ARAMIDE

Accessories

Part number: **12015 71004 002 2269**

Two-coloured • 4-layer construction of thumb and palm • very good thermal insulation of the palm • very good protection against radiant heat • good abrasion resistance of the palm.

silver/yellow



Our new heat protection gloves are available in different variants, lengths and sizes and offer protection against thermal risks according to EN 407 as well as mechanical hazards according to EN 388 thanks to selected material combinations and insulation layers.

METALLISED HEAT PROTECTION GLOVES UP TO 250 °C CONTACT HEAT

| | | | MATERIAL LAYER CONSTRUCTION | | | | |
|------|--------|-----------|-----------------------------|-----------|--------|----------------------------------|----------|
| ITEM | | | UPPER | ISOLATION | LINING | LENGTH | SIZES |
| 1 | EN 407 | | Aramide, Sebatan leather | - | | approx. 365 mm approx. 385 mm | 11 12 |
| 2 | 413244 | EN 388 | Aramid, Sebatan leather | - | | approx. 435 mm approx. 455 mm | 11 12 |
| 3 | EN 407 | 1 X 2 X X | Aramide, Para-Aramide | - | | approx. 380 mm approx. 400 mm | 11 12 |
| 4 | 423244 | | Aramide, Para-Aramide | - | | approx. 465 mm approx. 485 mm | 11 12 |



5-FINGER GLOVES 370 + LEATHER

Accessories Part number: 12008 71011 002 2268

5-FINGER GLOVES 440 + LEATHER

Accessories

Part number: 12008 71011 001 2268

Two-coloured • leather sebatan pulse reinforcement • very good protection against radiant heat • high abrasion resistance and tear resistance of the palm • very good dexterity and high wearing comfort.





5-FINGER GLOVES 390 + ARAMIDE

Accessories

Part number: 12008 71012 003 2269

5-FINGER GLOVES 470 + ARAMIDE

Accessories

Part number: 12008 71012 002 2269

Two-coloured • leather sebatan pulse reinforcement • good heat insulation of the palm • very good protection against radiant heat • high tear resistance of the palm • very good dexterity and high wearing comfort.







HEAT PROTECTION GLOVES UP TO 500 °C CONTACT HEAT

| | M | | MATERIAL LAYER | MATERIAL LAYER CONSTRUCTION | | | |
|------|-----------------------|---------------------|------------------------------------|-----------------------------|--------|----------------------------------|-------|
| ITEM | | | UPPER | ISOLATION | LINING | LENGTH | SIZES |
| 1 | EN 407 | EN 388 | Para-Aramide | 1-ply | | approx. 375 mm approx. 395 mm | |
| 2 | 4232XX | 2 X 4 X X | Para-Aramide | | | approx. 460 mm approx. 480 mm | |
| 3 | EN 407 4332XX | EN 388 2 X 4 X X | Para-Aramide | | | approx. 390 mm | 11 |
| 4 | EN 407 4 2 3 2 X X | EN 388 1 X 4 X X | Glass/Aramide/PBI, Para-Aramide | 2-ply | | approx. 390 mm | 11 |







5-FINGER GLOVES 370, ARAMIDE

Accessories

Part number: 01267 71012 001 20

5-FINGER GLOVES 470, ARAMIDE

Accessories

Part number: **01267 71012 000 20**

Single-coloured • finger and palm 3-ply • good thermal insulation of the palm • very high mechanical load capacity • good abrasion resistance • very good dexterity.

yellow

MITTENS GLOVE 390, ARAMIDE

Accessories

Part number: 01267 71007 000 20

Single-coloured • 3-layer construction • thumb inserted on the side • can be worn on both sides • good thermal insulation all around • very high mechanical load capacity • good abrasion resistance.

yellow

MITTENS 390 PBI/ARAMIDE

Accessories

Part number: 01191 71013 000 20

Two-coloured • 4-layer construction of hand and thumb • thumb inserted on the side • can be worn on both sides • good thermal insulation in the hands area • very high mechanical load capacity.

yellow/light brown



The heat protection equipment is rounded out by matching footwear with various aluminized gaiter models and a foundry boot certified to the EN ISO 20349-1:2017 foundry standard for molten iron and aluminum.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | MATERIAL | | | REGULAR SIZES |
|------------|--------|------------|-------------|-------------------|---|----------------|---|
| 1 ,2 3 | | 15 | silver | preox/Aramide | EN ISO 11612 A1/B1/C3/D3/E3/F1 (Partial body protection) | - | One size 1 (= up to size 43) 2 (= from size 44) |
| 4 | | 2276 | white/grey | full calf leather | - | EN ISO 20349-1 | 39–48 |

GAITERS, HOOK & LOOP FASTENING

Accessories

Part number: 12015 71008 000 15

Flame-inhibiting hook&loop fastener • adjustable width • approx. 38 cm high.

Sale unit: 1 pair



GAITERS, SNAP FASTENING

Accessories

Part number: 12015 71008 001 15

Snap fasteners closures • adjustable width • approx. 38 cm high.

Sale unit: 1 pair



SPRING GAITERS

Accessories

Part number: 12015 71009 001 15

2 covered, vertical springs in the legs • vamp with instep spring • approx. 35 cm high.

Sale unit: 1 pair



HEAT, SPLASHES & WELDING



Nitrile rubber soles with heat-insulated substructure



FOUNDRY BOOTS

Accessories

Part number: **14003 76025 000 2276**

Aluminised upper leather (the metallic surface reflects heat radiation) • full calf leather • bootleg constructed like roof tiles • holding rivets • Kevlar $^{\$}$ stitching thread • quick fastener • steel cap • aluminised inlay sole • nitrile bearing sole type MÜNCHEN ROT, approx. 300 °C contact heat resistant • approx. 28 cm high.

CHEMICALS

WHEN HAS RELIABLE PROTECTION EVER GIVEN YOU SO MUCH FREEDOM?

There are many dangers in the workplace: if chemicals are involved, for example, they are sometimes barely perceptible. Reliable PPE prevents from accidentally penetrating the skin when coming into contact with hazardous substances. At the same time, it should be light and comfortable to wear over a long working day. That's why we only use materials that fulfil the relevant safety standards as well as our high standards of comfort. A feeling of freedom included.







HB-CHEMstandard

Comfortable in dangerous environments: HB-CHEMstandard combines reliable chemical protection in accordance with EN 13034: type 6 and extraordinary wearing properties that even have the benefit of being slightly warming due to the characteristics of the material.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|---------|--------|------------|-------------|--------------------|-------------------------------|
| 1,2,4,5 | | 56 | iron grey | EN 13034 Type 6 | 46-58 & 94-110 39/40-47/48 |

FIELDS OF APPLICATION: Chemical and petrochemical industry, steel industry, automotive industry, battery factories, laboratories and electroplating

JACKET

Chemical protection type 6 Part number: 02001 10136 001 56 Garment weight: approx. 535 g

Single-coloured • turn-down collar • closure band with covered snap fasteners on both sides • 1 front pocket on the left and 2 side pockets with flaps and covered snap fasteners • 1 inner front pocket on the right • sleeve hem width adjustable via inner covered snap fasteners.



Side pockets with flaps and covered snap fasteners



COAT

Chemical protection type 6 Part number: **02001 40032 001 56** Garment weight: approx. 690 g

Single-coloured • lapel collar, also worn tightly closed • closure band with covered snap fasteners on both sides • 1 front pocket on the left and 2 side pockets – each with flaps and covered snap fasteners • 1 inner front pocket on the right • sleeve hem width adjustable via inner covered snap fasteners.





SHIRT

Chemical protection type 6 Part number: 02001 60000 004 56 Garment weight: approx. 490 g

Single-coloured • turn-down collar • closure band with buttons • 1 front pocket on the left with flap and buttoning • wristband with buttoning.

TROUSERS

Chemical protection type 6 Part number: 02001 20085 001 56 Garment weight: approx. 535 g

Single-coloured • added waistband with 7 belt loops • 2 slant pockets, 1 hip pocket on the right with flap and covered hook&loop fastener • 1 ruler pocket on the right with flap • covered button fly.







Ruler pocket



Chemical protection type 6 Part number: **02001 50063 001 56** Garment weight: approx. 665 g

Single-coloured • stretch braces with clampon clips • 1 outer bib pocket and 1 hip pocket on the right – each with ap and covered hook&loop fastener • 2 side seam pockets • 1 ruler pocket on the right with flap • covered button fly • 2 side accesses adjustable via buttons.





MATERIAL: 100 % POLYACRYLIC, FC-EQUIPMENT · FABRIC WEIGHT: approx. 270 g/m² ·

REPELLENCY AND PENETRATION INDEXES: Repellency index A (%): Sulphuric acid 30 %: 99.8, Sodium hydroxide solution 10%: 99.5, o-Xylene: 96.2, Butan-1-ol: 96.3, hydrochloric acid 36%: 99.0, Nitric acid 65%: 97.7;

<u>.....</u>

Penetration index P (%): Sulphuric acid 30 %: 0.0, Sodium hydroxide solution 10 %: 0.0, o-Xylene: 0.6,

Butan-1-ol: 0.5, hydrochloric acid 36 %: 0.4, Nitric acid 65 %: 0.0

(HB-CHEM)




HB-CHEMprotect

With this new collection, we are offering chemical protection made from recycled material for the first time. The pleasantly lightweight fabric also offers permanent antistatic properties, making it the ideal solution for many specialised manufacturing processes. HB-CHEMprotect also impresses with its modern look and comfortable, easy-to-wear cut.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4 | REGULAR SIZES | |
|---------|--------|------------|----------------------|----------|-----------|----------------|--|
| 1 7 4 | | 2030 | royal/dark blue | | | 46-58 & 94-110 | |
| 1 ,3 ,4 | | 2082 | anthracite/dark blue | EN 13034 | EN 1149-5 | 40-30 & 74-110 | |
| ما | | 41 | royal | Туре 6 | LN 1147-3 | 39/40-47/48 | |
| 21 | 58 | | anthracite | | | 39/40-4//40 | |

FIELDS OF APPLICATION: Chemical industry, steel industry, automotive industry, battery factories, laboratories, electroplating







JACKET

Chemical protection type 6

Part number: 02018 10000 014 + COLOUR NO.

Garment weight: approx. 510 g

Two-coloured • turn-down collar • covered front closure with snap fasteners • 2 attached breast pockets and 2 side pockets with flaps and covered snap fasteners • sleeve width adjustable via snap fasteners • leasing neck label • embroidered FR standard pictograms on the front.

SHIRT

Chemical protection type 6

Part number: 02018 60026 004 + COLOUR NO.

Garment weight: approx. 470 g

Single-coloured • Comfort Fit • turn-down collar with snap fastener • front with covered snap fastener on both sides • chest pocket with flap and sleeve cuff with gusset - each with covered snap fastener • preformed sleeves • FR Leasing label • standard pictograms as FR embroidery an right sleeve cuff.







3 and 4 Mobile phone pocket on the right with flap and hook&loop



Elasticated sideband



TROUSERS

Chemical protection type 6

Part number: 02018 20000 011 + COLOUR NO.

Garment weight: approx. 500 g

Two-coloured • added waistband (half elastic) with button • covered zip fly ullet 2 slant pockets ullet 1 back pocket with flap and snap fastener • 1 mobile phone pocket on the right – with flap and hook&loop.

BIB AND BRACE TROUSERS

Chemical protection type 6

Part number: **02018 50100 012 + COLOUR NO.**

Garment weight: approx. 595 g

Two-coloured • stretch straps with fixlock buckles • straight kidney protection • slit with covered zip • 1 side entry on the left with button • 2 side seam pockets • 1 outer bib pocket • 1 back pocket with flap and snap fastener • 1 mobile phone pocket on the right with flap and hook&loop fastening.

MATERIAL: 99 % POLYESTER, 1% CARBON, FC-EQUIPMENT .

FABRIC WEIGHT: approx. 240 g/m² ·

REPELLENCY AND PENETRATION INDEXES: Repellency index A (%): Sulphuric acid 30 %: 99.8, Sodium hydroxide solution 10 %: 99.6, o-Xylene: 87.8, Butan-1-ol: 95.3; Penetration index P (%): Sulphuric acid 30 %: 0.0, Sodium hydroxide solution 10 %: 0.0, o-Xylene: 7.6, Butan-1-ol: 1.1





➤ HB-CHEMprotect





The new and equally lightweight HB-CHEMprotect coats for men and women also offer reliable chemical protection plus antistatic properties. They are suitable for use in many different branches of industry and, like jackets and trousers, are available in several colours.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4 | REGULAR SIZES |
|------|--------|------------|----------------------|----------|-----------|----------------|
| 5 | | 10 | white | | • | 36/38-44/46 |
| | | 10 | white | EN 13034 | EN 1149-5 | |
| 6 | | 2030 | royal/dark blue | Туре 6 | EN 1147-3 | 46-58 & 94-110 |
| | | 2082 | anthracite/dark blue | | • | |

FIELDS OF APPLICATION: Chemical industry, steel industry, automotive industry, battery factories, laboratories, electroplating



LADIES COAT

Chemical protection type 6 Part number: 02018 40073 001 10 Garment weight: approx. 580 g

Single-coloured • turn-down collar • covered front closure with snap fasteners • 2 attached breast pockets and 2 side pockets with flaps and covered snap fasteners • sleeve width adjustable via snap fasteners • leasing neck label • embroidered FR standard pictograms on the front.



Ladies coat available in further colours in just 21 days. See page 237.



MEN'S COAT

Chemical protection type 6 Part number: 02018 40021 001 10 Garment weight: approx. 640 g

MEN'S COAT

Chemical protection type 6

Part number: **02018 40021 000 + COLOUR NO.**

Garment weight: approx. 640 g

Single- or two-coloured • turn-down collar • covered front closure with snap fasteners • 2 attached breast pockets and 2 side pockets with flaps and covered snap fasteners • sleeve width adjustable via snap fasteners • leasing neck label • embroidered FR standard pictograms on the front.

MATERIAL: 99 % POLYESTER, 1% CARBON, FC-EQUIPMENT .

FABRIC WEIGHT: approx. 240 g/m²

REPELLENCY AND PENETRATION INDEXES: Repellency index A (%): Sulphuric acid 30 %: 99.8, Sodium hydroxide solution 10 %: 99.6, o-Xylene: 87.8, Butan-1-ol: 95.3; Penetration index P (%): Sulphuric acid 30 %: 0.0, Sodium hydroxide solution 10 %: 0.0, o-Xylene: 7.6, Butan-1-ol: 1.1

(HB-CHEM)







Underwear is an important supplement to ensure comprehensive chemical protection. The low humidity absorption and the slight warming effect allow for optimal wearing comfort - an important component of an optimal protection system.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | SIZES |
|---------------|------------|--|------------------------|-------|
| 1 , 2 , 3 | | 11 | off-white | 6–8 |
| | DDI ICATIO | ······································ | er abassisal is duetry | |

.....

FIELDS OF APPLICATION: Underwear for: chemical industry, steel industry, automotive industry, battery factories, laboratories, electroplating

UNDERSHIRT LONG-SLEEVED

Chemical protection type 6 Part number: **02008 76008 000 11** Garment weight: approx. 200 g

Edged neckline • short-sleeved opening with stretchy double-stitched seam • hem with stretchy double-stitched seam.

UNDERSHIRT SHORT-SLEEVED

Chemical protection type 6 Part number: **02008 76009 000 11** Garment weight: approx. 170 g

Edged neckline • short-sleeved opening with stretchy double-stitched seam • hem with stretchy double-stitched seam.

UNDERPANTS LONG

Chemical protection type 6 Part number: **02008 76010 000 11** Garment weight: approx. 200 g

Elastic waistband • double-sided fly • leg opening with knitted cuffs.



MATERIAL: 100 % POLYACRYLIC .

FABRIC WEIGHT: approx. 170 g/m² · CHARACTERISTICS: Rib knit, modern and form-fitting design







WELCOME TO YOUR PERSONAL COMFORT ZONE!

The best thing about our HiVis & Weather collections:

comfortable fit and modern design give you a great feeling in your outfit and make you look really good.

And not just in good weather, but especially in wet, cold, foggy, drizzly and dark conditions.

With bright colours and cleverly placed reflective stripes, our high visibility and weather protection clothing sends out strong signals that can't be missed.



>> HI-VISION® Basic

The shirts with segmented reflective stripes combine effective high-visibility protection with UV protection, design and wearing comfort. Polyester on the outside and cotton on the inside ensure optimal moisture transport. UV protection 50+ is the highest protection according to the European classification and better than the standard requires: the fabric lets only 2% of UV rays through. Now also available for ladies.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 40+ | REGULAR SIZES |
|-------|--------|------------|------------------------------------|--------------|------------------------------------|---------------|
| 4 2 | | 2161 | fluorescent orange-red/hydron blue | | | S-2XL |
| 11,21 | | 2162 | fluorescent yellow/hydron blue | EN ISO 20471 | EN 13758-2 tested upon UV50+ | J-Z/L |
| -1 41 | | 17 | fluorescent yellow | Class 2 | | VC I |
| 3 ,4 | | 18 | fluorescent orange | | | XS-L |

FIELDS OF APPLICATION: All summer work in factory and public places; suitable for public utility companies, supply and disposal contractors

1 to 4

HB Logo as direct embroidery on the back 2

POLO-SHIRT SHORT SLEEVE

High-Visibility

Part number: 04025 80009 002 + COLOUR NO.

Garment weight: approx. 330 g

Two-coloured • round design and cut with contrast stitching in off-white • polo opening with zip fastener with encased zipper • reflective film in body language, attached as patch, stretchy (segmented) • HB logo as direct embroidery on back • standard pictograms as direct embroidery on right sleeve hem.

T-SHIRT SHORT SLEEVE

High-Visibility

Part number: 04025 80008 003 + COLOUR NO.

Garment weight: approx. 310 g

Two-coloured • round design and cut with contrast stitching in off-white • round neck opening • reflective film in body language, attached as patch, stretchy (segmented) • HB logo as direct embroidery on back • standard pictograms as direct embroidery on right sleeve hem.



HIVIS & **WEATHER**



Standard pictograms as direct embroidery, proven to UV 50+



1 to 4





LADIES POLO-SHIRT SHORT SLEEVE

High-Visibility

Part number: 04025 80025 000 + COLOUR NO.

Garment weight: approx. 300 g

Two-coloured \bullet round design and cut with contrast stitching in off-white • polo opening with zip fastener with encased zipper • reflective film in body language, attached as patch, stretchy (segmented) • HB logo as direct embroidery on back • standard pictograms as direct embroidery on right sleeve hem.

LADIES T-SHIRT SHORT SLEEVE

High-Visibility

Part number: 04025 80025 001 + COLOUR NO.

Garment weight: approx. 280 g

Two-coloured • round design and cut with contrast stitching in off-white • round neck opening • reflective film in body language, attached as patch, stretchy (segmented) • HB logo as direct embroidery on back • standard pictograms as direct embroidery on right sleeve hem.

MATERIAL: 55 % COTTON, 45 % POLYESTER ·

FABRIC WEIGHT: approx. 185 g/m² ·

PROPERTIES: Offers UV protection 50+ and is therefore better than the EN standard requires. It only lets pass 2% of the UV rays. That means "very high protection" according to the European Classification.

.....

HI-VISION®



The HI-VISION® Basic Parka with removable thermal jacket is the right solution for bad weather conditions as well as for dark working environments and at dusk and dawn. In addition to hi-visibility and weather protection, it also offers protection against moisture thanks to welded seams and a high stand-up collar with integrated hood.

| ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | | " | 4 | REGULAR SIZES |
|------|--------|------------|---------------------------------|--------------------------|--------------|-----------|---------------|
| 4 | | 2112 | fluorescent yellow/navy | EN ISO 20471 Class 2* | EN 343 | EN 1149-5 | 46/48-58/60 |
| 11 | | 2165 | fluorescent orange- red/navy | *from size 42/44 | Class 3/3 | LN 1147-3 | 40/40-36/00 |

FIELDS OF APPLICATION: Technical retailers, suppliers, disposers, works in the factory or public traffic area, car wash, logistic centres



.....i.

MATERIAL: 99 % POLYESTER, 1% CARBON, Fluorcarbon Finish ·

FABRIC WEIGHT: approx. 150 g/m²

HI-VISION®

HIVIS & **WEATHER**



This flexible weather protection collection doesn't leave you out in the rain. Thanks to welded seams and reflective stripes, it offers reliable protection in wind and weather and poor visibility. Certified according to EN 343 class 3/3 - the highest protection class against precipitation and ground moisture. With removable thermal insert.

| | ITEM | COLOUR | COLOUR-NO. | COLOUR NAME | Ť | 4 | REGULAR SIZES |
|---|------|--------|------------|-------------|-----------|-----------|---------------|
| : | 1 | | 2041 | navy/royal | EN 343 | EN 1149-5 | 46/48-58/60 |
| | 2 | | 45 | navy | Class 3/3 | LN 1147-3 | 40/40-30/00 |

FIELDS OF APPLICATION: Technical retailers, suppliers, disposers, works in the factory or public traffic area, car wash, logistic centres



PARKA INCL. QUILTED JACKET

Weather Protection

Part number: 05028 19001 001 2041 Garment weight: approx. 1,440 g

Two-coloured • outer material as direct laminate • with welded seams • with removable thermal jacket • high stand-up collar with built-in hood • fastener strip with concealed 2-way zip • chest pocket on left with built-in pen compartment • chest pocket on right with built-in mobile phone compartment • 2 side pockets with flaps and press stud closures • inside pocket on left with hook&loop fastener • hem can be adjusted with drawstring • sleeve width can be adjusted with press stud • with reflective strips • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.

BRACE TROUSERS INCL. QUILTED TROUSERS

Weather Protection

Part number: 05028 29003 000 45 Garment weight: approx. 1,060 g

Single-coloured • outer material in the form of direct laminate • with welded seams • with removable thermal trousers • adjustable stretch straps with clamping buckles • 2 leg pockets • 1 pocket for folding rule on right • slit with zip • waist can be adjusted with elastic band • knee-high side slit with zip • with reflective strips • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.

MATERIAL: 99 % POLYESTER, 1% CARBON, Fluorcarbon Finish ·

MATERIAL WEIGHT: approx. 150 g/m²







COLD STORE

PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work.

INTENSITY OF MOVEMENT: intensive to normal



FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants,















Zip-through leg zippers with inner cover



TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: **01174 2K012 000 45** Garment weight: approx. 1,400 g

LADIES TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: 01174 2K017 000 45 Garment weight: approx. 1,200 g

Without front zip • entry via zip-flies on both sides.

Single-coloured • ErgoPlus ergonomically tailored • adjustable length suspenders • elastic waistband in the back • roomy side pockets • embroidered logo on the back • preformed $legs \bullet zip\text{-through leg zippers covered inwards} \bullet covered front$ zipper with inner flap • raised waistband at the back with hanging loop.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING NON-WOVEN, INNER LINING: 100 % POLYESTER .

.....

FABRIC WEIGHT: approx. 515 g/m²



TEMPEX® CLASSIC

CHILLROOM

PPE for work in moderately cold conditions at temperatures between 0 °C and 10 °C.

INTENSITY OF MOVEMENT: normal

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|----------|------------|-------------|--|---|
| 1 ,3 | | 2040 | navy/red | EN 342 Y: 0,339 (B) m² K/W AP: Class 2 | Men: 46/48–58/60 Ladies: 36/38–44/46 |
| 2 | <u>:</u> | | | - | 46/48-58/60 |

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants, Cool chain logistics, Logistics centres, Pharmaceutical industry













BODY WARMER

Chillroom (0-10°C)

Part number: **09044 1K050 000 2040** Garment weight: approx. 560 g

Two-coloured • knitted smooth collar • left-side chest pocket with pencil pocket • 2 front pockets • front zipper • reflective stripes • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353 • waist width regulation by elastic waistband.

TROUSERS

Chillroom (0-10°C)

Part number: **09044 2K024 000 2040** Garment weight: approx. 1,290 g

LADIES TROUSERS

Chillroom (0-10°C)

Part number: **09044 2K001 002 2040** Garment weight: approx. 1,150 g

Two-coloured • adjustable suspenders • raised back • front zipper • full-length leg zippers covered inwards • side pockets • reinforced hem made of the outer fabric • circumferential reflective stripes on the legs • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353 • lighter non-woven insulation.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING

NON-WOVEN, INNER LINING: 100 % POLYESTER .

FABRIC WEIGHT: approx. 415 g/m²



TEMPEX® CLASSIC

COLD STORE

PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work.

INTENSITY OF MOVEMENT: intensive to normal

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|------------------|------------|-------------|---|---|
| 1 ,2 | | | | EN 342 Y: 0,448 (B) m² K/W Y: 0,344 (B) m² K/W (Acrylic fur) AP: Class 2 | Men: 46/48–58/60 Ladies: 36/38–44/46 |
| 3 | | 2040 | navy/red | EN 342 Y: 0,292 (R) m² K/W AP: Class 2 | 46/48–58/60 |
| 4 | · · · · | | | EN 342 Y: 0,411 (B) m² K/W AP: Class 2 | 40/40-30/00 |

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants,

Cool chain logistics, Logistics centres, Pharmaceutical industry





Full-length leg zippers covered inwards

Men



Cold Store (-49°C) Part number: **09045 1K000 000 2040** Garment weight: approx. 1,680 g

LADIES JACKET ORDER PICKER

Cold Store (-49°C)

Part number: 09045 1K001 000 2040 Garment weight: approx. 1,380 g

JACKET ORDER PICKER WITH ACRYLIC FUR LINING

Cold Store (-49°C)

Part number: 09028 1K009 000 2040 Garment weight: approx. 1,740 g Completely with acrylic fur lining.

Two-coloured • tight-fitting collar of faux fur with a hook&loop fastener • left side chest pockets with zipper • 2 front pockets • covered front zipper • knitted cuffs • elastic waistband in the back • circumferential reflective stripes • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.

TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: 09045 2K000 000 2040 Garment weight: approx. 1,520 g

LADIES TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: 09045 2K001 000 2040 Garment weight: approx. 1,355 g

TROUSERS ORDER PICKER WITH ACRYLIC FUR LINING

Cold Store (-49°C)

Part number: 09028 2K006 000 2040 Garment weight: approx. 1,600 g Completely with acrylic fur lining.

Two-coloured • adjustable suspenders • raised back • front zipper • full-length leg zippers covered inwards • side pockets • reinforced hem made of the outer fabric • circumferential reflective stripes on the legs • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.







Hood with faux fur lining



COAT VISITOR

Cold Store (-49°C)

Part number: **09045 4K000 000 2040** Garment weight: approx. 1,885 g

Two-coloured • hood with faux fur lining and tight-fitting knit collar • left-side chest pocket with zipper • 2 front pockets • covered 2-way front zipper • knitted cuffs • elastic waistband in the back • circumferential reflective stripes • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.

1 and 4 Tight-fitting collar of faux fur with a hook&loop fastener



COVERALL ORDER PICKER

Cold Store (-49°C)

Part number: **09045 3K000 000 2040**Garment weight: approx. 2,410 g

Two-coloured • tight-fitting collar of faux fur with a hook & loop fastener • 2 chest pockets • 2 front pockets • covered 2-way front zipper • knitted cuffs • elastic waistband in the back • adjustable hip size • leg zippers covered inwards • knee insulation made of acrylic fur lining • reinforced hem made of the outer fabric • circumferential reflective stripes on chest and legs • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING

<u>:</u>...

NON-WOVEN, INNER LINING: 100 % POLYESTER $\,\cdot\,$

FABRIC WEIGHT: approx. 520 g/m² · approx. 560 g/m² (with acrylic fur lining)





COLD STORE PLUS

PPE for low-movement work at temperatures up to -49 °C, like forklift driver.

INTENSITY OF MOVEMENT: intensive to normal // low

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|---------|--------|------------|-------------|--|---------------|
| 1 , 2 | | 2040 | navy/red | EN 342 Y: 0,404 (B) m² K/W Y: 0,398 (R) m² K/W (Plus) AP: Class 2 | 46/48-58/60 |

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants,

Cool chain logistics, Logistics centres, Pharmaceutical industry



2 Raised back Full-length leg zippers covered inwards Knee insulation made of acrylic fur lining

JACKET FORKLIFT DRIVER

Cold Store Plus (-49°C)

Part number: 09046 1K012 001 2040 Garment weight: approx. 1,840 g

JACKET FORKLIFT DRIVER PLUS

Cold Store Plus (-49°C)

Part number: 09046 1K012 000 2040 Garment weight: approx. 2,095 g Additional acrylic fur lining on the back.

Two-coloured • tight-fitting collar of faux fur with a hook&loop fastener • left side chest pockets with zipper • 2 front pockets • covered front zipper • knitted cuffs • elastic waistband in the back • circumferential reflective stripes • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353 • extra-strong non-woven insulation.

TROUSERS FORKLIFT DRIVER

Cold Store Plus (-49°C)

Part number: 09046 2K007 001 2040 Garment weight: approx. 1,650 g

TROUSERS FORKLIFT DRIVER PLUS

Cold Store Plus (-49°C)

Part number: 09046 2K007 000 2040 Garment weight: approx. 1,845 g

Knee pockets including additional knee insulation.

Two-coloured • adjustable suspenders • raised back • full-length leg zippers covered inwards • front zipper • side pockets • reinforced hem made of the outer fabric • circumferential reflective stripes on the legs • no Hi-Vis protective clothing acc. to EN ISO 20471 and EN 17353 \bullet extra-strong non woven insulation.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING

NON-WOVEN, INNER LINING: 100 % POLYESTER .

FABRIC WEIGHT: approx. 630 g/m²











CHILLROOM

PPE for work in moderately cold conditions at temperatures between 0 °C and 10 °C.

INTENSITY OF MOVEMENT: normal

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|--------|------------|-------------|--|---|
| 1 | | 2040 | navy/red | EN 342 Y: 0.391 (B) m² K/W AP: Class 2 | Men: 46/48–58/60 Ladies: 36/38–44/46 |

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants, Cool chain logistics, Logistics centres, Pharmaceutical industry



LADIES JACKET

Chillroom (0-10°C)

Part number: 01183 1K008 001 2040 Garment weight: approx. 1,365 g

Two-coloured • tight fitting collar of faux fur with hook&loop fastener • inside pocket for a pick-by-voice computer • lift-side chest pocket with pencil pocket and logo flap • 2 side pockets • left-side inside chest pocket with zipper • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest, arm and pocket areas • outer-layer hard-wearing • lighter non-woven insulation.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING NON-WOVEN, INNER LINING: 100 % POLYESTER ·

.....

FABRIC WEIGHT: approx. 445 g/m²



TEMPEX® COMFORT

CHILLROOM // COLD STORE

PPE for work in moderately cold conditions at temperatures between 0 °C and 10 °C. // PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work.

INTENSITY OF MOVEMENT: normal // intensive to normal

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|--------|------------|-------------|--|---------------------|
| 1 | | 2040 | navy/red | - | 46/48-58/60 |
| 2 | | 45 | navy | EN 342 Y: 0,391 (B) m² K/W AP: Class 2 | Men: 46/48–58/60 |
| 3 | | 2040 | navy/red | EN 342 | Ladies: 36/38-44/46 |
| 4 | | 45 | navy | Y: 0,435 (B) m² K/W AP: Class 2 | |

.....

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants,

Cool chain logistics, Logistics centres, Pharmaceutical industry



Front zipper with chin protection

Full-length 2-way leg

zippers covered inwards

Covered front zipper (only men's version)

Side pockets

BODY WARMER

Chillroom (0-10°C)

Part number: 01183 1K033 001 2040 Garment weight: approx. 640 g

Two-coloured • stand-up fleece collar • leftside chest pocket with pencil pocket • 2 front pockets • front zipper with chin protection • right-side reflective patch • reflective piping in the chest area • outer-layer hard-wearing • lighter non-woven insulation.

TROUSERS

Chillroom (0-10°C)

Part number: **01183 2K008 006 45** Garment weight: approx. 1,485 g

LADIES TROUSERS

Chillroom (0-10°C)

Part number: 01183 2K003 003 45 Garment weight: approx. 1,300 g

Single-coloured • adjustable suspenders • raised back waistband • covered front zipper (only for the men's model) • full-length 2-way leg zippers covered inwards • side pockets • knee pockets • reinforced hem made of the outer material • reflective patch on the straps • outer-layer hard-wearing • lighter non-woven insulation.

2











JACKET ORDER PICKER

Cold Store (-49°C)

Part number: **01183 1K005 000 2040** Garment weight: approx. 1,730 g

LADIES JACKET ORDER PICKER

Cold Store (-49°C)

Part number: **01183 1K006 000 2040** Garment weight: approx. 1,535 g

Two-coloured • tight-fitting collar of faux fur with hook&loop fastener • left-side chest pocket with pencil pocket and logo flap • 2 side pockets • left-side inside chest pocket with zipper • inside pocket for a pick-by-voice computer • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest, arm and pocket areas • outer-layer hard-wearing.

TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: **01183 2K002 000 45** Garment weight: approx. 1,665 g

LADIES TROUSERS ORDER PICKER

Cold Store (-49°C)

Part number: **01183 2K003 000 45** Garment weight: approx. 1,550 g

Single-coloured • adjustable suspenders • covered front zipper (only for the men's model) • full-length 2-way leg zippers covered inwards • side pockets • knee pockets including additional knee insulation made of acrylic fur lining • reinforced hem made of the outer fabric • reflective patches on the straps • outer-layer hard-wearing.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING

.....

NON-WOVEN, INNER LINING: 100 % POLYESTER .

FABRIC WEIGHT: CHILLROOM approx. $445\,\mathrm{g/m^2}$ · COLD STORE approx. $545\,\mathrm{g/m^2}$





COLD STORE // COLD STORE PLUS

PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work. // PPE for low-movement work at temperatures up to -49 °C, like forklift driver.

INTENSITY OF MOVEMENT: intensive to normal // low

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|------|--------|------------|-------------|---|--|
| 1 | | 2040 | navy/red | EN 342 Y: 0,274 (R) m² K/W | 46/48–58/60 Men: 46/48–58/60 Ladies: 36/38–44/46 |
| 2 | | | | EN 342 Y: 0,443 (B) m² K/W | |
| = 1 | | | | EN 342 Y: 0,508 (B) m² K/W | |
| 31 | | | | Y: 0,511 (B) m² K/W (Plus) AP: Class 2 | |
| 4 | | 45 | navy | EN 342 Y: 0,508 (B) m² K/W | 244,657,657,75 |

.....

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants,

Cool chain logistics, Logistics centres, Pharmaceutical industry





COAT VISITOR

Cold Store (-49°C)

Part number: 01183 4K001 000 2040 Garment weight: approx. 1,720 g

Two-coloured • tight-fitting collar of faux fur with hook&loop fastener • left-side chest pocket with pencil pocket and logo flap • left-side inside chest pocket with zipper • 2 side pockets • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest, arm and pocket areas • outer-layer hard-wearing.

ORDER PICKER COVERALL

Cold Store (-49°C)

Part number: 01183 3K001 000 2040 Garment weight: approx. 2,600 g

Two-coloured • tight-fitting collar of faux fur with hook&loop fastener • left-side chest pocket with pencil pocket and logo flap • left-side inside chest pocket with zipper • 2 side pockets • 2-way front zipper covered inwards • knitted cuffs • elastic leg zippers covered inwards • knee pockets including additional knee insulation made of acrylic fur lining • reinforced hem made of the outer fabric • right-side reflective patch • reflective piping in the chest, arm and pocket areas • outer-layer hard-wearing.









JACKET FORKLIFT DRIVER

Cold Store Plus (-49°C) Part number: **01183 1K013 000 2040**

Garment weight: approx. 1,840 g

JACKET FORKLIFT DRIVER PLUS

Cold Store Plus (-49°C)

Part number: 01183 1K018 000 2040 Garment weight: approx. 2,090 g Additional acrylic fur lining on the back.

Two-coloured ullet tight-fitting collar of faux fur with hook&loop fastener • left-side chest pocket with pencil pocket and logo flap • 2 side pockets • left-side inside chest pocket with zipper • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest, arm and pocket areas • outer-layer hard-wearing • extra-strong non woven insulation.

TROUSERS FORKLIFT DRIVER

Cold Store Plus (-49°C)

Part number: **01183 2K010 000 45** Garment weight: approx. 1,810 g

Single-coloured • adjustable suspenders • covered front zipper • full-length 2-way leg zippers covered inwards • side pockets • knee pockets including additional knee insulation made of acrylic fur lining • reinforced hem made of the outer fabric • reflective patches on the straps • outer-layer hard-wearing • extra-strong non woven insulation.

..... CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING NON-WOVEN, INNER LINING: 100 % POLYESTER .

·_____

 $\textbf{FABRIC WEIGHT:} \ \ \text{COLD STORE approx.} \ \ 545 \ \text{g/m}^2 \quad \cdot \quad \ \text{COLD STORE PLUS approx.} \ \ 645 \ \text{g/m}^2$



TEMPEX® THERMO

TEMPEX® thermal fleece clothing offers additional protection against the cold and can be used to supplement your personal protective equipment for work in chill rooms and cold environments. Useful features include the slit pockets with zip fastener, abrasion protection on the forearms and the slightly tailored cut of the ladies' jacket.

| I | TEM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES |
|-----|------|--------|------------|-------------|---|
| 11, | 2 ,4 | | 45 | navy | Men: 46/48–58/60 Ladies: 36/38–44/46 |
| | 3 | | | | 46/48–58/60 |



1 and 2 Waistband with draw-string

FLEECE JACKET

Intermediate clothing

Part number: 07024 1K003 000 45 Garment weight: approx. 535 g

LADIES FLEECE JACKET

Intermediate clothing

Part number: **07024 1K004 000 45** Garment weight: approx. 430 g

Single-coloured • high collar • front zipper with chin protector • 2 side pockets with zipper • waistband with draw-string • extra forearm abrasion protection • extra soft.

BODY WARMER

Intermediate clothing

Part number: 07024 1K029 000 45 Garment weight: approx. 360 g

LADIES FLEECE BODY WARMER

Intermediate clothing

Part number: **07024 1K030 000 45** Garment weight: approx. 375 g

Single-coloured • high collar • front zipper with chin protector • 2 side pockets with zipper • elastic arm holes • waistband with draw-string • extra soft.









3 and 4 This TEMPEX® fleecewear is referred to as reference clothing in the EN 342 standard, and it is used for the tests by certification institutes.





FLEECE SHIRT

Intermediate clothing

Part number: **07021 8K000 000 45** Garment weight: approx. 290 g

Single-coloured • turtleneck • front zipper with chin protection • extra soft.

FLEECE TROUSERS

Intermediate clothing

Part number: **07024 2K004 000 45** Garment weight: approx. 410 g

LADIES FLEECE TROUSERS

Intermediate clothing

.....

i.....i

Part number: **07024 2K005 000 45** Garment weight: approx. 365 g

Single-coloured • elastic stretch waistband • elastic hem • extra soft.

MATERIAL: FLEECE: 100 % POLYESTER . TRIM MATERIAL: 100 % POLYESTER .

FABRIC WEIGHT: 1 |, **2** |,**4** | approx. 265 g/m² · **3** | approx. 155 g/m²



Clothing that adapts to your movement: The ergonomic cut of the TEMPEX® THERMO ERGOPLUS provides excellent freedom of movement for the wearer. The jackets have pre-formed sleeves with optimised pivot spacing and an extended "drop-tail" back, the body warmers have a close-fitting cut and the trousers have pre-formed legs. Both product lines can be combined with our cold store and chill room clothing. The ladies' versions have a slightly fitted cut.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES |
|-------------|--------|------------|-------------|---|
| 1,2,3,4,5,6 | | 45 | navy | Men: 46/48–58/60 Ladies: 36/38–44/46 |

.....

JACKET ERGOPLUS

Intermediate clothing

Part number: **09020 1K021 001 45** Garment weight: approx. 435 g

LADIES JACKET ERGOPLUS

Intermediate clothing

Part number: 09020 1K022 000 45 Garment weight: approx. 445 g

Single-coloured • a maximum of movement freedom in any position by pre-formed sleeves with optimised length and drop-tail • high fleece collar • front zipper with chin protection • pencil pocket on the left side of the chest.

BODY WARMER ERGOPLUS

Intermediate clothing

Part number: **09020 1K034 001 45** Garment weight: approx. 305 g

LADIES BODY WARMER ERGOPLUS

Intermediate clothing

Part number: 09020 1K035 000 45 Garment weight: approx. 315 g

Single-coloured • a maximum of movement freedom in any position by ergonomically tailored fit • high fleece collar • front zipper with chin protection • pencil pocket on the left side of the chest.

TROUSERS ERGOPLUS

Intermediate clothing

Part number: **09020 2K015 000 45** Garment weight: approx. 370 g

LADIES TROUSERS ERGOPLUS

Intermediate clothing

Part number: **09020 2K016 000 45** Garment weight: approx. 400 g

Single-coloured • elastic waistband • front zipper • a maximum of movement freedom in any position by pre-formed legs • legs with fleece at the bottom.





Legs with fleece at the bottom









JACKET

Intermediate clothing

Part number: 09020 1K002 000 45 Garment weight: approx. 450 g

LADIES JACKET

Intermediate clothing

Part number: 09020 1K010 001 45 Garment weight: approx. 435 g

Single-coloured • high collar made of fleece • front zipper • left-side inside chest pocket with pencil pocket (ladies' jacket without) • knitted cuffs.

BODY WARMER

Intermediate clothing

Part number: 09020 1K023 001 45 Garment weight: approx. 285 g

LADIES BODY WARMER

Intermediate clothing

Part number: 09020 1K025 000 45 Garment weight: approx. 295 g

Single-coloured • high collar made of fleece • front zipper • left-side inside chest pocket with pencil pocket (ladies' body warmer without).

TROUSERS

Intermediate clothing

Part number: 09020 2K009 000 45 Garment weight: approx. 400 g

LADIES TROUSERS

Intermediate clothing

Part number: 09020 2K011 000 45 Garment weight: approx. 350 g

Single-coloured • elastic waistband • front zipper • leg end with knitted cuffs.







..... CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: DIAMOND NON-WOVEN INSULATION,

INNER LINING: 100 % POLYESTER . FABRIC WEIGHT: approx. 245 g/m²

TEMPEX® HYGIENE

CHILLROOM // COLD STORE

PPE for work in moderately cold conditions at temperatures between 0 °C and 10 °C. // PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work.

INTENSITY OF MOVEMENT: normal // intensive to normal

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | REGULAR SIZES |
|----------|---------------|------------------------|--|---|---------------|
| 1 | | 3116 | white/silver grey/ fluorescent yellow | EN 342 Y: 0,371 (B) m² K/W AP: Class 2 | |
| 3 | | 2237 | white/silver grey | - EN 342 Y: 0,371 (B) m² K/W AP: Class 2 | |
| 4 | | 3116 | white/silver grey/ | EN 342 Y: 0,417 (B) m² K/W AP: Class 2 | 46/48-58/60 |
| 5 | | 3110 | fluorescent yellow | EN 342 Y: 0,267 (R) m² K/W AP: Class 2 | |
| 6 | | 2237 | white/silver grey | EN 342 Y: 0,417 (B) m² K/W AP: Class 2 | |
| FIELDS O | F APPLICATION | DN: Food indust | rv | | |





1, 2 and 3 Reflective piping in the chest and sleeve area

> Reflective patch on the straps



JACKET

Chillroom (0-10°C)

Part number: 01174 1K007 001 3116 Garment weight: approx. 1,180 g

Three-coloured • tight-fitting collar made of fleece with hook&loop fastener • 2 inside chest pockets with zipper • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest and arm areas • lighter nonwoven insulation.

BODY WARMER

Chillroom (0-10°C)

Part number: 01174 1K024 000 3116 Garment weight: approx. 590 g

Three-coloured • tight-fitting collar made of fleece • 2 inside chest pockets with zipper • 2-way front zipper • right-side reflective patch • reflective piping in the chest area • lighter non-woven insulation.

TROUSERS

Chillroom (0-10°C)

Part number: 01174 2K008 005 2237 Garment weight: approx. 1,200 g

Three-coloured • adjustable suspenders • raised back • covered front zipper • full-length 2-way leg zippers covered inwards • reinforced hem made of the outer fabric • reflective patch on the straps • lighter non-woven insulation.







2-way front zipper

covered inwards

4 and 5 | Tight-fitting collar made of fleece with hook&loop fastener





JACKET ORDER PICKER

Cold Store (-49°C)

Part number: **01174 1K005 001 3116** Garment weight: approx. 1,205 g

Three-coloured • tight-fitting collar made of fleece with hook &loop fastener • 2 inside chest pockets with zipper • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the arm- and chest area.

COAT VISITOR

Cold Store (-49°C)

Part number: **01174 4K001 001 3116** Garment weight: approx. 1,565 g

Three-coloured • tight-fitting collar made of fleece with hook & loop fastener • 2 inside chest pockets with zipper • large inside pocket • 2-way front zipper covered inwards • knitted cuffs • elastic waistband in the back • right-side reflective patch • reflective piping in the chest and arm area.

TROUSERS

Cold Store (-49°C)

Part number: **01174 2K008 003 2237** Garment weight: approx. 1,365 g

Three-coloured • adjustable suspenders • raised back • covered front zipper • full-length 2-way leg zippers covered inwards • knee pockets • reinforced hem made of the outer fabric • reflective patch on the straps.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, PADDING: TEMPEX® HIGH-BULK, INSULATING

.....

NON-WOVEN, INNER LINING: 100 % POLYESTER .

FABRIC WEIGHT: CHILLROOM approx. 415 g/m 2 · COLD STORE approx. 515 g/m 2





TEMPEX® THERMO HYGIENE

Clothing that adapts to your movement: The ergonomic cut of the TEMPEX® THERMO ERGOPLUS provides excellent freedom of movement for the wearer. The jackets have pre-formed sleeves with optimised pivot spacing and an extended "drop-tail" back, the body warmers have a close-fitting cut and the trousers have pre-formed legs. Both product lines can be combined with our cold store and chill room clothing. The ladies' versions have a slightly fitted cut.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES |
|-------------|--------|------------|-------------|---|
| 1,2,3,4,5,6 | | 10 | white | Men: 46/48–58/60 Ladies: 36/38–44/46 |

JACKET ERGOPLUS

Intermediate clothing

Part number: **09020 1K021 000 10** Garment weight: approx. 435 g

LADIES JACKET ERGOPLUS

Intermediate clothing

Part number: 09020 1K042 000 10 Garment weight: approx. 445 g

Single-coloured • a maximum of movement freedom in any position by pre-formed sleeves with optimised length and drop-tail • high collar, with fleece inside • front zipper with chin protection • pencil pocket on the left side of the chest, with pen compartment on the left.



Intermediate clothing

Part number: **09020 1K034 000 10** Garment weight: approx. 305 g

LADIES BODY WARMER ERGOPLUS

Intermediate clothing

Part number: 09020 1K035 001 10 Garment weight: approx. 315 g

Single-coloured • a maximum of movement freedom in any position by ergonomically tailored fit • high collar, with fleece inside • front zipper with chin protection • pencil pocket on the left side of the chest, with pen compartment on the left.

TROUSERS ERGOPLUS

Intermediate clothing

Part number: **09020 2K015 000 10** Garment weight: approx. 370 g

LADIES TROUSERS ERGOPLUS

Intermediate clothing

Part number: **09020 2K016 000 10** Garment weight: approx. 400 g

Single-coloured • elastic waistband • front zipper • a maximum of movement freedom in any position by pre-formed legs • legs with fleece at the bottom.





Legs with fleece at the bottom









JACKET

Intermediate clothing

Part number: **09020 1K002 001 10** Garment weight: approx. 450 g

LADIES JACKET

Intermediate clothing

Part number: 09020 1K010 000 10 Garment weight: approx. 435 g

Single-coloured • high collar made of fleece • front zipper • left-side inside chest pocket with pencil pocket (ladies' jacket without) • knitted cuffs.



Intermediate clothing

Part number: **09020 1K023 000 10** Garment weight: approx. 285 g

LADIES BODY WARMER

Intermediate clothing

Part number: 09020 1K025 001 10 Garment weight: approx. 295 g

Single-coloured • high collar made of fleece • front zipper • left-side inside chest pocket with pencil pocket (ladies' body warmer without).

TROUSERS

Intermediate clothing

Part number: 09020 2K009 000 10 Garment weight: approx. 400 g

LADIES TROUSERS

Intermediate clothing

Part number: 09020 2K001 001 10 Garment weight: approx. 350 g

Single-coloured • elastic waistband • front zipper • leg end with knitted cuffs.





Leg end with knitted cuffs

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE, DIAMOND NON-WOVEN INSULATION, 100 % POLYESTER INNER LINING

FABRIC WEIGHT: approx. 245 g/m²

TEMPEX® COLD Pro

COLD STORE

PPE for movement-intensive work at temperatures up to -49 °C, like order-picker work.

INTENSITY OF MOVEMENT: intensive to normal

| | ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | ⊕€ | P. P | REGULAR SIZES |
|---|------|--------|------------|-------------|--|---------------------|--|---------------|
| | 1 ,3 | _ | 2128 | grey/black | EN 342 Y: 0,428 (B) m² K/W AP: Class 2 | EN 17353 Type B2 | Reduced temperature 60°C | S-2XL |
| : | 2 | | | | - | - | | |

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants, Cool chain logistics, Logistics centres, Pharmaceutical industry







JACKET

Cold Store (-49°C)

Part number: 01174 15001 000 2128 Garment weight: approx. 1,750 g

Two-coloured • modern, ergonomic cut • high stand-up collar, inside made of soft functional material • 2 breast pockets (left with pen compartment) with flap and covered snap fastener • 2 front pockets with flap and covered snap fastener • chin guard • full-length 2-way front zip to collar end, covered with snap fasteners • reflective applications • inside pocket for pick-by-voice computer • leasing collar • reflective stripes, suited for industrial laundry • standard pictograms as direct embroidery on the right arm.







Loop for buttoning in the outer jacket



Reflective stripes for higher visibility



For even higher protection against cold combinable with our TEMPEX®



Reflective applications

Full-length 2-way leg zips, covered inside



INNER JACKET

Cold Store (-49°C)

Part number: **09057 15002 000 2128** Garment weight: approx. 790 g

Two-coloured • maximum freedom of movement in all body positions thanks to pre-shaped sleeves with optimised lever length and extended back (droptail) • 2 side pockets with covered zip • high collar, soft functional material inside • front zip with chin guard • 2 inside breast pockets with pen compartment.

TROUSER

Cold Store (-49°C)

Part number: **01174 25001 000 2128** Garment weight: approx. 1,730 g

Two-coloured • length-adjustable elasticated braces • raised back waistband • covered front zip • full-length 2-way leg zips, covered inside • side insert pockets • reinforced hem made from outer fabric • reflective applications • leasing collar • reflective stripes, suited for industrial laundry • standard pictograms as direct embroidery on left leg.

CONSTRUCTION: UPPER MATERIAL: 100 % POLYAMIDE; PADDING: ISOLIERVLIES suitable for leasing,

<u>.....</u>

INNER LINING: 100 % POLYESTER .

FABRIC WEIGHT: 1 and 3 approx. 620 g/m² · 2 approx. 460 g/m²





TEMPEX® THERMO ACCESSORIES

In a multi-layered clothing system the underwear plays an important role. It protects the wearer from cooling down due to the close-to-skin fit providing insulating and moisture-regulating properties. Our underwear offers high wearing comfort and allows a climate regulation for high active working thanks to its material composition.

UNDERSHIRT LONG-SLEEVE

Accessories

Part number: 04036 7Z015 000 45 Garment weight: approx. 215 g

Single-coloured • double knitted • comfortable raglan sleeve • close-fitting cuff • extra-long back • non-bulky flat seams • fine functional fabric • breathable • suitable for movement-intensive activities.

Material: 55 % Polyester, 45 % Cotton

Sizes: 5-8 navy

UNDERSHIRT TROYER LONG-SLEEVE

Accessories

Part number: 04036 7Z015 002 45 Garment weight: approx. 230 g

Single-coloured • double knitted • collar with short front zipper • comfortable raglan sleeve • close-fitting cuff • extra-long back • non-bulky flat seams • fine functional fabric • breathable • suitable for movementintensive activities.

Material: 55 % Polyester, 45 % Cotton Sizes: 5-8



UNDERPANTS LONG

Accessories

Part number: 04036 7Z016 000 45 Garment weight: approx. 205 g

Single-coloured • double knitted • elastic waistband • leg end with cuff • non-bulky flat seams • fine functional fabric • breathable • suitable for movement-intensive activities

Material: 55 % Polyester, 45 % Cotton

Sizes: 5-8 navy

KIDNEY BELT

Accessories

Part number: 07024 7K003 000 45

Single-coloured • hook&loop fastener for adjusting waist circumference • extra soft.


Material: 100 % Polyester

Sizes: S-2XL navy



1, 2 and 3 Non-bulky flat seams

2





This TEMPEX® underwear is referred to as reference clothing in the EN 342 standard, and it is used for the tests by certification institutes.



PROTECTION



The face and head are more sensitive to differences in temperature than other parts of the body. We offer reliable accessories for the cold weather. Our range includes hoods, hats, caps, insulated helmets, neck warmers and fleece mouth protectors.

ALASKA HOOD

Accessories

Part number: 04046 7Z005 000 45

Single-coloured • faux fur lining • made of 65% Polyester and 35% Cotton • forehead protection • neck protection • ear protection • hook&loop strap for securing the ear protection in place.

Sizes: 1/56-5/64 Sale unit: 1 piece navy

This TEMPEX® hood is referred to as reference clothing in the EN 342 standard, and it is used for the tests by certification institutes.



Matching the TEMPEX® collections

HOOD CLASSIC

Accessories

Part number: 01174 7K001 001 45

Single-coloured • tight-fitting knitted • chin area with adjustable snap fastener • field of vision adjustable via drawstring and stopper • faux fur lining • made of 100% Polyamide • 2 button holes for possible attachment • matching the TEMPEX® CLASSIC collection.

One size Sale unit: 1 piece navy



Matching the TEMPEX® CLASSIC collection

HOOD COMFORT

Accessories

Part number: 01183 7K001 000 45

Single-coloured • tight-fitting knitted • chin area with adjustable hook&loop fastener • field of vision adjustable via drawstring and stopper • faux fur lining • made of 100% Polyamide • 2 button holes for possible attachment • outer-layer hard-wearing •

One size Sale unit: 1 piece navy



Matching the TEMPEX® COMFORT collection

HOOD HYGIENE

Accessories

Part number: 01174 7K001 002 10

Single-coloured • tight-fitting knitted • chin area with adjustable hook&loop fastener • field of vision adjustable via drawstring and stopper • faux fur lining • made of 100% Polyamide • 2 button holes for possible attachment • matching the TEMPEX® HYGIENE collection.

One size Sale unit: 1 piece ☐ white



Matching the TEMPEX® HYGIENE collection



TEMPEX® THERMO ACCESSORIES

The face and head are more sensitive to differences in temperature than other parts of the body. We offer reliable accessories for the cold weather. Our range includes hoods, hats, caps, insulated helmets, and neck warmers.

KNITTED CAP

Accessories

Part number: **04045 7Z009 000 + COLOUR NO.**

Single-coloured • double knitted • scotchgard treatment • thinsulate lining • made of 100% Polyacrylic.

One size

Sale unit: 1 piece

46 black

 \square **10** white



BALACLAVA, DOUBLE-LAYERED

Accessories

Part number: 04044 7Z014 000 46

Single-coloured • 2-ply • face opening with elastic strap for flexible and secure fit • made of 100% Polyacrylic.

One size Sale unit: 1 piece

black



BALACLAVA

Accessories

Part number: **04036 7Z014 001 45**

Single-coloured • fine functional fabric • face opening with elastic strap for flexible and secure fit • made of 55% Polyester and 45% Cotton.

One size

Sale unit: 1 piece

navy





PROTECTIVE HELMET POLY

Accessories

Part number: 90022 7Z006 012 25

Single-coloured • storage pocket for hearing protection • removable, washable insulated inside part • insulation insert made of 100 % Polyester • with button holes to fix with helmet \bullet tested down to -30 °C \bullet fits with insulation insert.

One size (51-64 cm) Sale unit: 1 piece

red

Standards:





EN 50365

INSULATING INSERT

Accessories

Part number: 01158 7K000 000 48

Single-coloured • storage pocket for hearing protection • removable, washable insulated inside part • insulation insert made of 100 % Polyester \bullet with button holes to fix with helmet • tested down to -20 °C • fits with POLY helmet.

One size

Sale unit: 1 piece dark blue

PROTECTIVE HELMET POLY WITH INSULATING INSERT

Accessories

Part number: 90022 75001 000 25

Description see protective helmet and insulation insert.

One size (51-64 cm) Sale unit: 1 piece

red and ark blue



EN 50365



FLEECE NECK WARMER

Accessories

Part number: 07034 75000 000 46

Single-coloured • soft fleece material • made of 100% recycled Polyethylene Terephthalate • suited for industrial laundry.

One size


Sale unit: 1 piece black





Removable, washable insulated insert







have been collected




TEMPEX® THERMO ACCESSORIES

With us, you will find the right cold protection gloves for your work in the deep-freeze or cold room area – suitable for a wide range of applications in trade as well as in industry, logistics and research. Besides our new cold protection gloves with certified protection against cold and mechanical risks, which are particularly suitable for order pickers, we also offer fleece and underlay gloves.

Protective gloves against cold EN 511:2006

This standard specifies the test methods and performance requirements of protective gloves against cold. The insulating capacity of the material on contact, the resistance to progressively penetrating cold and the thermal resistance to direct contact with a cold object are measured. The three-digit code next to the standard pictogram indicates the performance levels, with 0 corresponding to the weakest and 4 to the highest performance. Water resistance is defined with two performance levels: 0 = Water penetration after 30 min, 1 = No water penetration after 30 min.




Performance levels for protective gloves against cold according to EN 511

| Test | Performance Level | | | | | | |
|--|-------------------------------|-------------------------------|-------------------------------|------------------------|--|--|--|
| | 1 | 2 | 3 | 4 | | | |
| Convective Cold Thermal Insulation/ _{TR} (in m² K/W) (Insulation value) | 0,10 ≤ / _{TR} < 0,15 | 0,15 ≤ / _{TR} < 0,22 | 0,22 ≤ / _{TR} < 0,30 | 0,30 ≤ / _{TR} | | | |
| Contact Cold Thermische Isolation/ _{TR} (in m² K/W) (Widerstandswerte) | 0,025 ≤ R < 0,050 | 0,050 ≤ R < 0,100 | 0,100 ≤ R < 0,150 | 0,150 ≤ R | | | |
| Waterproofness | No water penetration | | | | | | |

4 means the highest and 1 means the lowest performance level. X means "not tested". 0 means "below the minimum requirements".

Protective gloves against mechanical risks EN 388:2016

This standard specifies the test methods and performance requirements of protective gloves against mechanical risks. The specific protective performance depends on which test is carried out during certification and which performance level is achieved, 1 being the lowest and 5 the highest performance level. "X" means not tested.



| Test | | · · · · · · · · · · · · · · · · · · · | Performance Leve | = | |
|--|-----|---------------------------------------|------------------|------|----|
| | 1 | 2 | 3 | 4 | 5 |
| Abrasion resistance (Number of cycles) | 100 | 500 | 2000 | 8000 | |
| Cutting resistance (Factor) | 1,2 | 2,5 | 5,0 | 10,0 | 20 |
| Tear strength (in newton) | 10 | 25 | 50 | 75 | |
| Cutting strength (in newton) | 20 | 60 | 100 | 150 | |

5 means the highest and 1 means the lowest performance level. X means "not tested". 0 means "below the minimum requirements".

FIELDS OF APPLICATION: Retail and Wholesale, Research, Catering and Restaurants, Cool chain logistics, Food Industry, Logistics centres, Pharmaceutical industry







| | [**] | | MAT | | | |
|------|--------|---------------------|--------------|---|-------------------------|-------|
| ITEM | | | BACK OF HAND | LINING | PALM OF HAND | SIZES |
| 1 | EN 511 | EN 388 2 X 2 2 C | Polyester | HPPE, polyester and steel fiber thread | Synthetic leather | 6–12 |
| 2 | 111 | EN 388 2 1 1 1 X | Spandex | Thinsulate™ 40 g | Full grain goat leather | 7–12 |

1 2





GLOVES TOUCH & CUT 4

Accessories

Part number: **04103 76027 004 2128**

Two-coloured • forefinger reinforcement • reinforced fingertips • waterproof • cut protection A4 • velcro fastener • chromium-free • suitable for cool environments • suitable for order pickers • suitable for Touchscreens.

grey/black

GLOVES TOUCH & HI-VIS

Accessories

Part number: **14016 76027 005 2171**

Two-coloured • forefinger reinforcement • reinforced fingertips • waterproof • cut protection A4 • velcro fastener • chromium-free • suitable for cool environments • suitable for order pickers • suitable for Touchscreens.

fluorescent yellow/black



TEMPEX® THERMO ACCESSORIES

Our cold protection gloves for order picking work offer certified protection that you can rely on for your work in the deep-freeze area down to -49 °C, as well as in the fresh and cold storage area between 0°C and 10°C. All models are made of high-quality materials and are elaborately finished.

| [} *] [| | | МА | | | |
|---------------------|-----------------|---------------------|--------------|---------------------------|--------------------------------|-------|
| ITEM | | | BACK OF HAND | LINING | PALM OF HAND | SIZES |
| 1 | EN 511 1 2 X | EN 388 2 1 4 1 X | Neoprene | Fleece | MACROTHAN® (Nylon and PU) | 7–11 |
| 2 | EN 511 2 2 1 | EN 388 2121X | Polyester | Thinsulate™ 100 g, Fleece | MICROTHAN® + (Nylon and PU) | 7–13 |
| 3 | EN 511 2 2 0 | EN 388 2 2 3 2 X | Leather | Knitted pile | Leather | 8–10 |

1 2 3





GLOVES TK PRO

Accessories

Part number: **04039 7Z000 010 2049**

Two-coloured • ergonomically designed fingers and thumb • finger and thumb reinforcement reinforced fingertips • moisture-resistant and windproof back of the hand • robust inside hand protection • 360° cuff • with reflective elements • chromium-free • suitable for cold environments • suitable for order pickers.

black/middle grey

GLOVES AQUA PRO

Accessories

Part number: **04102 76027 001 3395**

Three-coloured • ergonomically designed fingers and thumb • reinforced fingertips • waterproof, windproof and moistureresistant • especially robust • 360° cuff • with reflective elements • chromium-free • suitable for cold environments • suitable for order pickers.

middle grey/black/yellow

GLOVES 2 2 0 PLUS, KNIT

Accessories

Part number: **14004 7Z000 006 2099**

Two-coloured • backs of hand made of split leather • palms made of full grain leather • knitted cuffs • foam insulation up to the start of the cuff • hardwearing • suitable for order pickers.

middle grey/black





| | | | MAT | | | |
|----------|-----------------|---------------------|--------------------------------------|-------------------|----------------------------|-------|
| ITEM | | | BACK OF HAND | LINING | PALM OF HAND | SIZES |
| 1 | EN 511 2 2 1 | EN 388 2 2 2 2 X | Neoprene, full grain goat leather | Thinsulate™ 120 g | Full grain goat leather | |
| 2 3 | EN 511 2 3 1 | EN 388 2122X | Neoprene, Polyester | Thinsulate™ 150 g | Full grain cowhide leather | 7–12 |







GLOVES LEATHER PRO

Accessories

Part number: **14013 76027 000 46**

Single-coloured • ergonomically designed fingers • forefinger and thumb reinforcement • reinforced fingertips • waterproof • moisture-resistant • especially robust • velcro fastener • with reflective elements • suitable for very cold environments • suitable for order pickers.

black

GLOVES ALLROUND

Accessories

Part number: **14014 76027 002 2415**

Two-coloured • ergonomically designed fingers • finger and thumb reinforcement • waterproof • moisture-resistant and windproof back of the hand • robust inside hand protection • 360° cuff • long model • suitable for very cold environments • suitable for order pickers.

VERY COLD ENVIRONMENT

black/white

GLOVES ALLROUND HI-VIS

Accessories

Part number: **14015 76027 003 3396**

Three-coloured • signal colour • ergonomically designed fingers • finger and thumb reinforcement • waterproof • moistureresistant and windproof back of the hand • robust inside hand protection • 360° cuff • long model • suitable for very cold environments • suitable for order pickers.

fluorescent green/white/black



TEMPEX® THERMO ACCESSORIES

In addition to our certified range of cold protection gloves, we also offer fleece, knitted and underlay gloves in various designs.

| ITEM | LINING | MATERIAL | SIZES |
|------|-------------------|-----------|-------|
| 1 | | | 8, 10 |
| 2 | Thinsulate™ 100 g | Polyester | 0, 10 |
| 3 | | | 8–11 |



These gloves are referred to as reference clothing in the EN 342 standard, and it is used for the tests by certification institutes.





FLEECE GLOVES, GRIP

Accessories

Part number: **07029 7Z000 002 46**

Single-coloured • palms and 4 fingers covered with leather for grip safety • elastic band at the wrist • extra soft.

black

FLEECE GLOVES, KNIT & GRIP

Accessories

Part number: **07029 7Z000 003 46**

Single-coloured • palms and 4 fingers covered with leather for grip safety • knitted cuffs • extra soft.

black

FLEECE GLOVES, RUBBER GRIP

Accessories

3

Part number: **07029 7Z000 000 46**

Single-coloured • palms covered with tough rubber nubs for grip safety • elastic band at the wrist • extra soft.

black





| ITEM | | | MATERIAL | SIZES |
|------|---|---------------------|-------------------|----------|
| 1 | - | EN 388 2 1 4 X X | Cotton, Polyamide | 8–10 |
| 2 | - | - | Polypropylene | One size |

1



Additional insulation underneath cold protection gloves

2



KNITTED GLOVES, GRIP

Accessories

Part number: **04037 7Z000 005 45**

Single-coloured • palms covered with rubber nubs or grip safety • knitted cuffs.

navy

UNDERGLOVES

Accessories

Part number: **04038 7Z000 004 45**

Single-coloured • wearable as additional insulation underneath cold protection gloves • elastic material • processed without a seam • can be combined with all TEMPEX® cold protection gloves.

navy



> TEMPEX® THERMO ACCESSORIES

Our thermal safety boots are made of grained, water-resistant cow leather and have a non-slip, cold-resistant and insulated sole. Insulated steel, fibre glass or plastic toecaps ensure additional safety. Easy to put on and featuring a genuine lambswool or Loden/Primaloft lining, a high level of comfort is guaranteed.

Easy-to-put-on-zipper

S2 INSULATED SAFETY BOOTS

Accessories

Part number: 14003 7Z011 000 + COLOUR NO.

Two-coloured • made of grained, water-resistant cow leather • nonslip, cold-resistant and cold-insulated outsole • completely lined with real lambskin • aluminized insole • easy to put on thanks to slanted zipper • insulated steel toecap.

Insulated steel toecap

Sizes: 37-50

2001 white/yellow 2046 black/red

Standards:



FN 20345



S2 LACED SAFETY BOOTS

Accessories

Part number: 14003 7Z011 001 46

Single-coloured • made of grained, water-resistant cow leather • nonslip, cold-resistant and cold-insulated outsole • completely lined with real lambskin • aluminized insole • insulated steel toecap • good fit by lacing.

Sizes: 36-50 **black** Standards:





Real lambskin

S3 SAFETY BOOTS

Accessories

Part number: 14003 76033 001 46

Single-coloured • made of grained, water-resistant cow leather • nonslip, cold-resistant and cold-insulated outsole • completely lined with real lambskin • aluminized, preshaped insole • plastic zipper • insulated plastic toecap • non-metallic penetration protection.

Sizes: 36-48 black Standards:





Nonslip, coldresistant and coldinsulated outsole



S3 INSULATED SAFETY BOOTS

Accessories

Part number: 14017 76033 000 66

Single-coloured • nubuk leather, waxed • nonslip, cold-resistant and cold insulated outsole • Loden lining combined with Primaloft • aluminium layer in the sole • toe cap out of fibreglass • quick lacing system for easy and fast slip on an off.

Sizes: 39-47 brown Standards:



EN 20345



UNIVERSAL SOCKS

Accessories

Part number: 04041 7Z013 001 528

Single-coloured • made of a virgin wool blend •

felted wool sole.

One size

Sale unit: 1 piece dark grey

ALASKA SOCKS

Accessories

Part number: **04042 7Z013 000 52**

Single-coloured • made of a virgin wool blend • extremely effective insulation for long-term exposure.

Sizes: 37-38 to 47-48 Sale unit: 1 pair middle grey

LINER SOCKS

Accessories

Part number: 03018 7Z003 000 52

Single-coloured • made of tricot • flannel lining.

Sizes: 38-47 Sale unit: 1 piece middle grey







In addition to high-quality day shift wear for fire brigades, we also offer modern protective clothing for technical assistance and area fire fighting.

They meet the highest functional demands and also impress with a great look, useful features and outstanding wearing comfort. So much in fact, that you'll be happy to keep them on even after you've gone off duty.







Like all Flammgard® products, this station wear is made of a hard-wearing and high-quality fabric. Firefighters wear it when they are not on fire duty – e.g. for equipment maintenance, training courses or fire safety watches. It is comfortable like leisure wear, looks presentable and also protects in case of fire.

COLOUR COLOUR NO. COLOUR NAME **REGULAR SIZES** Men: 46-58, 23-29, 94-110 dark blue 1,2 Ladies: 36–46, 18–23, 72–92 FIELDS OF APPLICATION: Station wear for firemen





Elasticated hem

BLOUSON

Station wear FR

Part number: 01041 10160 000 48 Garment weight: approx. 1,100 g

LADIES BLOUSON

Station wear FR

Part number: 01041 10168 005 48 Garment weight: approx. 1,040 g

Single-coloured • shoulder tunnel for rank badge • collar with flap and hook&loop fastening • closure strip with zip and covered snap fasteners on both sides • 2 breast pockets with flaps with zip • right-hand flap with hook&loop tape for name badge • left-hand pocket with loop and metal half ring • 2 side pockets as piped pockets with zips • 2 inside pockets • adjustable cuff width thanks to concealed zip • hem band elasticated on the side • back with side folds for freedom of movement.



Female cut









JACKET

Station wear FR

Part number: **01041 10162 000 48** Garment weight: approx. 1,150 g

LADIES JACKET

Station wear FR


Part number: **01041 10174 000 48** Garment weight: approx. 1,100 g

Single-coloured • shoulder tunnel for rank badge • collar with flap and hook&loop fastening • front zipper with snap fasteners covered on both sides • breast pockets with flaps and hook&loop fastening • right-hand flap with hook&loop tape for name badge • left-hand pocket with loop and metal half ring • 2 inside pockets • wristbands adjustable via hook&loop • reinforced elbows • hem with drawstring and safety catch • back with yoke partition.



MATERIAL: 49 % ARAMIDE, 50 % VISCOSE FR, 1% CARBON

FABRIC WEIGHT: approx. 300 g/m²





As a basic collection, Flammgard® Klassik also includes women's models, different trouser variants, optionally with elastic waistband or yellow-silver-yellow reflective stripes, as well as a fleece jacket and a softshell jacket in addition. All Flammgard® models convince with many details such as elbow reinforcement or a hook&look tape for name tags.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | REGULAR SIZES |
|------|--------|------------|--|-----------------------------|------------------------|--|
| 3 | | 48 2051 | dark blue dark blue/fluore- scent yellow | EN ISO 11612 A1+A2/B1/C1 | EN ISO 13688 Hupf 2 | Men: 46–58, 23–29, 94–110 Ladies: 36–46, 18–23, 72–92 |
| 4 | | 46 | black | - | - | 46-58, 23-29, 94-110 |
| 5 | | 45 | navy | - | - | S–2XL |

LADIES TROUSERS

Station wear FR

Part number: 01041 20117 000 48 Garment weight: approx. 700 g

TROUSERS, ELASTIC WAISTBAND

Station wear FR

Part number: 01041 20109 000 48 Garment weight: approx. 730 g

TROUSERS WITH REFLECTIVE TAPE

Station wear FR

Part number: **01041 20086 008 48** Garment weight: approx. 770 g

Reflective stripes parallel to the seam • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

FIELDS OF APPLICATION: Station wear for firemen

LADIES TROUSERS WITH REFLECTIVE TAPE

Station wear FR

Part number: 01041 20117 003 2051

Garment weight: approx. 740 g

Reflective stripes parallel to the seam • no high-visibility protective clothing acc. to EN ISO 20471 and $\stackrel{\circ}{\text{EN}}$ 17353.

Single-coloured • waistband with hook&loop fastening • 2 pleats at the front, 4 darts at the back • covered zip fastener • 2 slant pockets • 1 back pocket with flap and zip • 2 bellow pockets on the side seam with flaps and zips • adjustable hem with elastic • front of trousers and crotch with flame-retardant cotton lining • seat seam designed to be easy to modify.



ACCESSORIES

Accessories

Adapter for rank badge Part number: 01041 70044 000 48 Flap with hook&loop fastening.

Name badges

Black-stitched border • first and last name individually embroidered in red, silver or gold.







Shoulder tunnel for





SOFTSHELLJACKET

Station wear

Part number: 11001 10161 014 46 Garment weight: approx. 1,070 g

Single-coloured • shoulder tunnel for rank badge • collar with flap and hook&loop fastening • front zipper with covered snap fastener • 2 breast pockets with flap and snap fastener • right-hand pocket with pen compartment and hook&loop tape for name badge on the flap • loop with metal half ring in the pocket • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 1 closable inside mobile phone pocket • wristbands adjustable via covered snap fastener • with black mesh lining.

rank badge

Hook&loop tape for name badge

FLEECE JACKET

Station wear

Part number: **07001 10151 000 45** Garment weight: approx. 700 g

Single-coloured ullet stand-up collar with zip fastening ulletfront zipper • breast pocket with flap and hook&loop fastening • flap with pen opening • side pockets as welt pockets • sleeves with inner knit cuffs and underarm reinforcement • hem with ribbed structure.

Flap with pen opening



MATERIAL: 3 49% ARAMIDE, 50% VISCOSE FR, 1% CARBON 4 94% POLYESTER, 6% ELASTANE . 5 100% POLYESTER .

FABRIC WEIGHT: 3 ,4 and 5 approx. 300 g/m²





Flammgard® KLASSIK Green Turtle

As a useful addition to the equipment of firefighters on day duty, we now also offer matching shirts, blouses and polo shirts. Thanks to the exceptionally light and highly functional materials such as Coolmax® Piqué and organic cotton, as well as a modern and comfortable cut, they are very comfortable to wear. An outfit that is a pleasure to wear even after work.

| ΙΤ | EM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES | | | | |
|-----|---|--------|------------|----------------------|-----------------------------------|--|--|--|--|
| , | 1 | | 488 | black blue | Men: S-2XL Ladies: XS-L | | | | |
| 2 | 2 ,3 | | 10 471 | white pastel blue | Men: 39/40-47/48 Ladies: 36-46 | | | | |
| FIE | FIELDS OF APPLICATION: Station wear for firemen | | | | | | | | |





POLOSHIRT

Station wear

Part number: 90027 86045 000 488 Garment weight: approx. 220 g

LADIES POLOSHIRT

Station wear

Part number: 90027 86046 000 488 Garment weight: approx. 190 g

Single-coloured • polo placket with buttoning • chest pocket on the left incl. pen compartement and button \bullet sleeve hem with cuffs • stylish shirt length, with short slits • sligthly extended back • incl. Coolmax® and ecofresh (fast drying and breathable) • UPF40 • with silver ions to reduce bacterial activity by 99%. Ladies' shirt with feminine cut.









Adapter for rank badge Flap with hook&loop fastening. 03028 70044 001 + COLOUR NO.

BLOUSE SHORT-SLEEVE

Station wear

Part number: 03028 60031 001 + COLOUR NO.

Garment weight: approx. 190 g

BLOUSE LONG-SLEEVE

Station wear

Part number: 03028 60031 000 + COLOUR NO.

Garment weight: approx. 240 g

Sleeve ends with cuff, slit and button closure.

Single-coloured • turn-down collar • front closure with buttons • shoulder with tunnel for badge • darts at chest height and at the back • chest

pocket with flap.





SHIRT SHORT-SLEEVE

Station wear

Part number: 03028 60030 001 + COLOUR NO.

Garment weight: approx. 210 g

SHIRT LONG-SLEEVE

Station wear

Part number: 03028 60030 000 + COLOUR NO.

Garment weight: approx. 260 g

Sleeve ends with cuff, slit and button closure.

Single-coloured • turn-down collar • front closure with buttons • shoulder with tunnel for badge • chest pocket with flap.







FABRIC WEIGHT: 1 approx. 160 g/m² · 2 and 3 approx. 120 g/m²





Flammgard® NORDRHEIN-WESTFALEN

Our Flammgard® collection Nordrhein-Westfalen is made of a high-quality aramid-viscose blend and is used by the fire brigade in North Rhine-Westphalia. In addition to the blouson, various trouser models with and without leg pockets are available in ladies' and men's versions.

| | ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4 | | REGULAR SIZES |
|---|---|--------|------------|-------------|-----------------------------|-----------|---|--|
| | 1 2 | • | 488 | black blue | EN ISO 11612 A1+A2/B1/C1 | EN 1149-5 | EN ISO 13688 HuPF 2* *only signed men's trousers | Men: 46–58, 23–29, 94–110 Ladies: 36–46, 18–23, 72–92 |
| : | FIELDS OF APPLICATION: Station wear for firemen Nordrhein-Westfalen | | | | | | | |





Covered hook&loop fastener to regulate the sleeve hem width

BLOUSON

Station wear FR Part number: **01056 10149 018 488** Garment weight: approx. 1,125 g

LADIES BLOUSON

Station wear FR

Part number: 01056 10168 006 488 Garment weight: approx. 1,060 g

Single-coloured • shoulder tunnel for rank badge • collar with flap and hook&loop fastening • closure strip with zip and covered snap fasteners on both sides • 2 breast pockets with flaps and zips • righthand flap with hook&loop tape for name badge • left-hand pocket with loop and metal half ring • flap with "Feuerwehr" embroidery • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 2 inside pockets • adjustable cuff width with covered zip; right sleeve pocket with zip and 2 pen pockets • waistband elasticated on the side • back with side folds for freedom of movement • flame-retardant cotton lining.









Seat seam easy to modify

TROUSERS (HuPF PART 2)

Station wear FR

Part number: **01056 20106 007 488** Garment weight: approx. 770 g

LADIES TROUSERS

Station wear FR

Part number: 01056 20117 004 488 Garment weight: approx. 740 g

TROUSERS WITHOUT CARGO POCKET

Station wear FR

Part number: 01056 20106 008 488 Garment weight: approx. 740 g

LADIES TROUSERS WITHOUT CARGO POCKET

Station wear FR

Part number: 01056 20117 005 488 Garment weight: approx. 710 g

Single-coloured • waistband with hook fastening and side elastic band • 2 pleats at the front, 4 darts at the back • covered zip fastener • 2 wing pockets • 1 back pocket with flap and zip • 2 bellow pockets on the side seam with flaps and zips • adjustable elasticated hem • seat seam designed to be easy to modify.





ACCESSORIES

Accessories

Also available for North Rhine-Westfalia blouson:

Adapter for rank badge

Part number: **01056 70048 000 488** Flap with hook&loop fastening.

Name badges

Black-stitched border • first and last name individually embroidered in red, silver or gold.





MATERIAL: 59 % ARAMIDE, 40 % VISCOSE FR, 1 % CARBON .

FABRIC WEIGHT: approx. 260 g/m²





Flammgard® BADEN-WÜRTTEMBERG

Flammgard® Baden-Württemberg is used by the fire brigade in Baden-Württemberg and impresses with many details such as the opening in the upper left pocket flap of the jacket for the antenna of the radio; above it is a loop for an antenna microphone. The embroidery with the Staufer lion is also a must in this collection.

1,2

2240

COLOUR COLOUR NO. COLOUR NAME black blue/red

REGULAR SIZES

Men: 46-58, 23-29, 94-110 Ladies: 36-46, 18-23, 72-92

FIELDS OF APPLICATION: Station wear for firemen Baden-Württemberg





BLOUSON

Station wear FR

Part number: **01056 10150 028 2240** Garment weight: approx. 1,040 g

LADIES BLOUSON

Station wear FR

Part number: 01056 10163 024 2240 Garment weight: approx. 1,000 g

Two-coloured • decorative red piping on front and back • shoulder tunnel for rank badge • loop for aerial microphone • collar with flap and button • front zipper with covered snap fasteners • 2 breast pockets with flaps and snap fastening • right-hand pocket with pen compartment and flap with hook&loop tape for name badge • left-hand flap with opening for radio antenna and "Staufer Löwe + Feuerwehr" embroidery • loop with metal half ring in the pocket • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 5 inside pockets in various designs • cuffs with gusset, adjustable cuff width thanks to covered snap fastener • hem band elasticated on the side • back with "FEUERWEHR" patch • flame-retardant cotton lining.













JACKET

Station wear FR

Part number: **01056 10159 012 2240** Garment weight: approx. 1,060 g

LADIES JACKET

Station wear FR

Part number: 01056 10169 008 2240 Garment weight: approx. 1,020 g

Two-coloured • decorative red piping on front and back • shoulder tunnel for rank badge • loop for aerial microphone • collar with flap and button • front zipper with snap fasteners covered on both sides • 2 breast pockets with flaps and snap fastening • right-hand pocket with pen compartment and hook& loop tape for name badge on the flap • left-hand flap with opening for radio antenna and "Staufer Löwe + Feuerwehr" embroidery • loop with metal half ring in the pocket • 2 side pockets as welt pockets with zip • 1 Napoleon pocket • 5 inside pockets in various designs • cuffs with gusset, adjustable via covered snap fastener • hem with drawstring • back with "FEUERWEHR" patch • flame-retardant lining.



MATERIAL: 59 % ARAMIDE, 40 % VISCOSE FR, 1 % CARBON .

İ......

FABRIC WEIGHT: approx. 260 g/m²





Flammgard® BADEN-WÜRTTEMBERG

For Baden-Württemberg, in addition to the men's and women's trousers, there is also a softshell jacket with black and, on request, red mesh lining as well as a fleece jacket for colder days. Both jackets are also intended

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4 | | REGULAR SIZES |
|------|--------|------------|----------------|-----------------------------|-----------|------------------------|--|
| 3 | | 2240 | black blue/red | EN ISO 11612 A1+A2/B1/C1 | EN 1149-5 | EN ISO 13688 Hupf 2 | Men: 46-58, 23-29, 94-110 Ladies: 36-46, 18-23, 72-92 |
| 4 | | 2046 | black/red | | | | 46-58, 23-29, 94-110 |
| 5 | | 2040 | navy/red | - | - | - | S–2XL |

FIELDS OF APPLICATION: Station wear for firemen Baden-Württemberg

TROUSERS

Station wear FR

Part number: 01056 20103 018 2240 Garment weight: approx. 690 g

LADIES TROUSERS

Station wear FR

Part number: 01056 20111 005 2240 Garment weight: approx. 670 g

Two-coloured • waistband with hook&loop fastening and elasticated on the sides • 2 pleats on the front of the trousers • covered zip fastener • 2 wing pockets • 2 back pockets and 2 bellow pockets on the side seam each with flaps and snap fasteners, red piping and "Staufer Löwe + Feuerwehr" embroidery • right-hand flap with opening for pen • crotch with flame-retardant cotton lining • seat seam designed to be easy to modify.





ACCESSORIES

Accessories

Also available for Baden-Württemberg blouson, jacket, softshell and fleece:

Adapter for rank badge

Part number: **01056 70048 000 488** Flap with hook&loop fastening.

Name badges

Black-stitched border • first and last name individually embroidered in red, silver or gold.







FIRE & **RESCUE SERVICES**



SOFTSHELLJACKET

Station wear

Part number: 11001 10161 010 2046 Garment weight: approx. 1,070 g

Two-coloured • decorative piping on front and back • shoulder tunnel for rank badge • collar with flap and hook & loop fastener • front zipper with covered snap fasteners • 2 breast pockets with flaps and snap fasteners • right-hand pocket with pen compartment and flap with hook&loop tape for name badge - left-hand flap with "Staufer Löwe + Feuerwehr" embroidery • loop with metal half ring in the pocket • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 1 closable inside mobile phone pocket • adjustable cuff width thanks to covered snap fastener • back with "FEUERWEHR" patch.

> Hook&loop fastener for name badge



Jacket also available with red mesh lining (Part number: 11001 10161 012 2046)



FLEECE JACKET

Station wear

Part number: **07001 10152 000 2040** Garment weight: approx. 700 g

Two-coloured • decorative red piping on front and back • shoulder tunnel for rank badge • stand-up collar • fastener strip with zip and covered snap fasteners on both sides • 2 breast pockets with flaps and zips \bullet right-hand flap with hook &loop tape for name badge • left-hand flap with "Staufer Löwe + Feuerwehr" embroidery • 2 side pockets as welt pockets • sleeves with inner knit cuffs and underarm reinforcement • hem with ribbed structure.



MATERIAL: 3 59 % ARAMIDE, 40 % VISCOSE FR, 1% CARBON · 4 94 % POLYESTER, 6 % ELASTANE

5 100 % POLYESTER .

FABRIC WEIGHT: 3 | approx. 260 g/m² · **4** | approx. 300 g/m² · **5** | approx. 260 g/m²





All certified Flammgard® Saarland products are made of the proven aramid viscose fabric weighing only 260 g/m² and are equipped with practical hook&loop fasteners. The collection is characterised by product diversity: In addition to women's models, a fleece and a softshell jacket are also available.

1,2

COLOUR : COLOUR NO. :

2240

COLOUR NO.

black blue/red

REGULAR SIZES

Men: 46-58, 23-29, 94-110 Ladies: 36-46, 18-23, 72-92

FIELDS OF APPLICATION: Station wear for firemen Saarland





Men

BLOUSON

Station wear FR

Part number: 01056 10150 026 2240 Garment weight: approx. 1,040 g

LADIES BLOUSON

Station wear FR

Part number: 01056 10163 022 2240 Garment weight: approx. 1,000 g

Two-coloured • piping on front and back • shoulder tunnel for rank badge • loop for aerial microphone • collar with flap and hook&loop fastening • front zipper with snap fasteners covered on both sides • 2 breast pockets with flaps with hook&loop fastening • right-hand pocket with pen compartment and hook&loop tape for name badge on the flap • left-hand flap with opening for radio antenna and underlined "Feuerwehr" embroidery • loop with metal half ring in the pocket • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 5 inside pockets in various designs • cuffs with gusset, adjustable via covered snap fastener • hem elasticated on the side • back with "Feuerwehr" patch • flame-retardant lining.













JACKET

Station wear FR

Part number: 01056 10198 002 2240 Garment weight: approx. 1,060 g

LADIES JACKET

Station wear FR

Part number: 01056 10169 006 2240 Garment weight: approx. 1,020 g

Two-coloured • piping on front and back • shoulder tunnel for rank badge • loop for aerial microphone • collar with flap and hook&loop fastening • front zipper with snap fasteners covered on both sides • 2 breast pockets with flaps with hook&loop fastening • right-hand pocket with pen compartment and hook&loop tape for name badge on the flap • left-hand flap with opening for radio antenna and underlined "Feuerwehr" embroidery, loop with metal half ring in the pocket • 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 5 inside pockets in various designs • cuffs with gusset, adjustable via covered snap fastener • hem with drawstring • back with "Feuerwehr" patch • flame-retardant lining.



MATERIAL: 59 % ARAMIDE, 40 % VISCOSE FR, 1 % CARBON .

İ......

FABRIC WEIGHT: approx. 260 g/m²





The Flammgard® Saarland collection is characterised by a high product diversity and also includes, among other things, men's trousers according to VWV as well as women's models, fleece and softshell jackets. The trousers are made with high-quality fabrics and yarns from NOMEX® and Lenzing.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | 4 | | REGULAR SIZES |
|----------|-----------|------------------------|--------------------|-----------------------------|-----------|--|--|
| 3 | | 2240 | black blue/red | EN ISO 11612 A1+A2/B1/C1 | EN 1149-5 | EN ISO 13688 HuPF 2* * only signed men's trousers | Men: 46–58, 23–29, 94–110 Ladies: 36–46, 18–23, 72–92 |
| 4 | | 2046 | black/red | | | • | 46-58, 23-29, 94-110 |
| 5 | | 2040 | navy/red | - | - | - : | S-2XL |
| FIELDS C | F APPLICA | TION: Station w | ear for firemen Sc | aarland | | | |

TROUSERS

Station wear FR

Part number: **01056 20103 016 2240** Garment weight: approx. 690 g

LADIES TROUSERS

Station wear FR

Part number: 01056 20137 001 2240 Garment weight: approx. 670 g

TROUSERS ACC. TO VWV (HuPF PART 2)

Station wear FR

Part number: 01056 20110 002 2240 Garment weight: approx. 710 g

Two-coloured • waistband with hook fastening and elasticated on both sides • 2 pleats at the front of the trousers • covered zip • 2 side pockets • 2 recessed back pockets with flap and hook&loop fastening • 2 bellow pockets on the side seam with flaps and hook&loop fastening, flaps with red trim and underlined "FEUERWEHR" embroidery • right-hand flap with opening for pen • lined crotch • seat seam designed to be easy to modify.



Also available with two side welt pockets with covered zips acc. to VWV





ACCESSORIES

Accessories

Also available for Saarland blouson, jacket, softshell and fleece:

Adapter for rank badge

Part number: **01056 70048 000 488** Flap with hook&loop fastening.

Name badges

Black-stitched border • first and last name individually embroidered in red, silver or gold.







FIRE & **RESCUE SERVICES**



Jacket also available with red mesh lining (Part number: 11001 10161 013 2046)



SOFTSHELLJACKET

Station wear

Part number: 11001 10161 011 2046 Garment weight: approx. 1,070 g

Two-coloured • decorative red piping on front and back • shoulder tunnel for rank badge • collar with flap and hook&loop fastening • front zipper with covered snap fastener • 2 breast pockets with flap and snap fastener • right-hand pocket with pen compartment and hook&loop tape for name badge on the flap • left-hand flap with "FEUERWEHR" underlined embroidery \bullet loop with metal half ring in the pocket ullet 2 side pockets as welt pockets with zips • 1 Napoleon pocket • 1 closable inside mobile phone pocket • sleeves with adjustable wristbands via covered snap fastener • back with "FEUERWEHR" patch.



FLEECE JACKET

Station wear

Part number: **07001 10152 001 2040** Garment weight: approx. 700 g

Two-coloured • decorative red piping on front and back • shoulder tunnel for rank badge • stand-up collar with zip fastening • front zipper with snap fastener covered on both sides • 2 breast pockets with flaps and hook&loop fastening • right-hand flap with hook&loop tape for name badge • left-hand flap with underlined "FEUERWEHR" embroidery • 2 side pockets as welt pockets • sleeves with inner knit cuffs and underarm reinforcement • hem with ribbed structure



Hem with ribbed structure

MATERIAL: 3 59 % ARAMIDE, 40 % VISCOSE FR, 1% CARBON 4 94 % POLYESTER, 6% ELASTANE .

.....

5 100 % POLYESTER .

FABRIC WEIGHT: 3 | approx. 260 g/m² · **4** | approx. 300 g/m² · **5** | approx. 260 g/m²





Day shift duty made easy: The material of our Flammgard® Bayern collection is particularly light and soft and can be worn very comfortably even over longer periods of use. Movement-friendly parts such as elastic knit inserts and shaped knees provide physical relief. Red details add visual accents and make the Bayern collection a real eye-catcher.

| | ITEM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES |
|---|------|--------|------------|---------------|-----------------------------|
| : | 1 | | 2120 | dark navy/red | Men: 46–58, 23–29, 94–110 |
| | 2 | | 458 | dark navy | Ladies: 36-46, 18-23, 72-92 |

FIELDS OF APPLICATION: Station wear for firemen Bayern



BLOUSON

Station wear

Part number: **04104 10218 000 2120** Garment weight: approx. 790 g

LADIES BLOUSON

Station wear

Part number: **04104 10217 000 2120** Garment weight: approx. 770 g

Two-coloured • shoulder tunnel for rank badge • loop fastener for name badges on the right front • undercollar and inner collar band in contrasting colour red • front closure with zipper • 2 breast pockets with flaps and hook&loop fastening • left pocket with pen compartment • ladies model with darts at chest height • 2 side pockets as welt pockets with zip • 2 inner pockets with zip and red pipe • mobile phone pocket inside on the right • cuffs with elastic knit insert • hem cuff with elastic knit • completely lined • label inside on the back for barcode or name patches.

ACCESSORIES

Accessories

Adapter for rank badge Part number: 04104 70044 002 458

Flap with hook&loop fastening.

Name badges

Black-stitched border • first and last name individually embroidered in red, silver or gold.





Hook&loop fastener for name badge





Elastic waistband





TROUSERS

Station wear

Part number: **04104 20155 000 458** Garment weight: approx. 620 g

LADIES TROUSERS

Station wear

Part number: **04104 20154 000 458** Garment weight: approx. 610 g

Two-colored ullet waistband with patent button closure and elastic band on both sides • covered zip-fly • saddle made of elastic fabric • 2 wing pockets • 2 back pockets • 2 integrated leg pockets, each with a piped pocket and zipper • ergonomic knee section.



2 integrated leg pockets, each with a piped pocket and zipper

MATERIAL: 63 % POLYESTER, 33 % COTTON, 4 % ELASTOLEFIN .

FABRIC WEIGHT: approx. 245 g/m²





HB-TECHNICAL RESCUE

The all-rounder for technical assistance: The light and robust fabric protects against heat and flames and fulfils the high-visibility vest exemption according to DGUV. The parka additionally is virus- and bacteria-proof, protects against rain and keeps you warm on colder days with the zip-in fleece jacket. All pockets have practical hook & loop fastenings and the elbows and knees have additional reinforcements.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | (Ť) | REGULAR SIZES |
|------|--------|------------|--|-----------------------------|--|---------------|
| 1 | | 3271 | dark blue/ fluorescent yellow/ black | EN ISO 11612 A1+A2/B1/C1 | EN 343 4 4 X (excl. Fleecejacket) EN 343 4 3 X (incl. Fleecejacket) | |
| 2 | | 2395 | black blue/black | | | |
| 3 | | 2047 | black/navy | - | - | |



Virus and bacteria-proof due to laminate according to ISO 16603 and ISO 16604

Torch holder with deflection flap for stable hold

Ergonomically formed sleeves with elbow reinforcement



Technical assistance FR

Part number: 01280 19005 001 3271 Garment weight: approx. 1,300 g

Single-coloured • segmented reflective stripes • stand-up collar with flap and hook&loop fastening • covered front zipper with covered hook&loop fastening • hook&loop tape on the front and on the back to attach the additional collar • 2 added breast pockets for radio devices with covered hook \& loop fastening \bullet opening for the antenna on the right with two radio attachment hooks • 1 inside pocket on the right • 2 sidepockets with flap and covered hook&loop fastening • 2 movement pleats on the back • ergonomically formed sleeves with elbow reinforcement • sleeve hem with strap for adjustment with hook&loop fastening • sleeve hem with cuff and thumb loop • jacket and trouser in combination fullfills DGUV 205-20 Information • virus and bacteria-proof due to laminate according to ISO 16603 and ISO 16604 • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353 • zippers to zip in a fleece jacket.



TROUSERS

Technical assistance FR

Part number: 01056 20147 000 2395 Garment weight: approx. 810 g

Single-coloured • segmented reflective stripes • detachable braces • waistband with hook fastening • covered zip fly • elasticated waist in the side • 2 slant pockets, 1 hip pockets, 2 beloow pockets on side seam - each with flap and hook&loop fastening • 2 inside knee pockets • reinforcementmaterial on knee and hem • hem with elastic • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

2 Elasticated waist in the side

Reinforcement material on knee and hem

FLEECE JACKET

Technical assistance FR

Part number: 07015 19006 000 2047 Garment weight: approx. 700 g

Two-coloured • high stand-up collar • inner collar made of Nomex® • zip for closing as well as for zipping into our HB-Technical Rescue Parka • loops at the sleeve hem for fixing in the jacket • sleeve cuffs with elastic band • material certified according to EN ISO 11612 A1/B1/C2/F1.



MATERIAL: 1 98% ARAMIDE, 2% CARBON · 2 59% ARAMIDE, 40% VISCOSE FR, 1% CARBON ·

.....

3 48 % MODACRYLIC, 32 % COTTON, 18 % POLYESTER, 2 % CARBON ·

FABRIC WEIGHT: 1 approx. 195 g/m² · **2** approx. 260 g/m² · **3** approx. 260 g/m²



HB-TECHNICAL RESCUE LITE

A real classic in the field of technical assistance: our suit made of hard-wearing and flame-retardant fabric with DGUV-compliant reflective striping in combination of jacket and trousers. Back labels can be attached to wide fleece strips on the upper back.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | REGULAR SIZES | | |
|----------|---|------------|-------------|-----------------------------|-----------------------------|----------------------|--|--|
| 1 2 | | 48 | dark blue | EN ISO 11612 A1+A2/B1/C1 | - EN ISO 13688 Hupf 2 | 46-58, 23-29, 94-110 | | |
| FIELDS C | FIELDS OF APPLICATION: Technical assistance | | | | | | | |

Back with hook&loop tape for badge



Yoke partition on front and back

Pocket flap with loop for name badge

DGUV-compliant reflective stripes



JACKET

Technical assistance FR Part number: 01041 10162 001 48 Garment weight: approx. 1,100 g

Single-coloured • with reflective stripes • yoke partition on front and back • collar with flap and hook&loop fastening • front zipper with snap fastener covered on both sides • 2 breast pockets with flaps and hook&loop fastening • right-hand pocket flap with hook&loop tape for name badge • left-hand flap with additional pocket opening under the flap • loop with metal half ring in the pocket • 2 side patch pockets with flaps • 2 inside pockets in various designs • cuffs with gusset, adjustable via covered hook&loop fastening • hem with drawstring • back with hook & loop tape for badge • sleeves with reinforced elbows • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353 • flame-retardant lining.







.....

i.....i

Seat seam designed to be easy to modify

Bellow pockets with flaps and hook&loop fastening

TROUSERS

Technical assistance FR

Part number: **01041 20086 006 48** Garment weight: approx. 740 g

Single-coloured • with reflective stripes • waistband with hook&loop fastening • 2 pleats on the front of the trousers, 4 darts on the back • with front and crotch lining • zip covered on one side • 2 side pockets • 1 back pocket with flap and hook&loop fastening • 2 bellow pockets on the side seam with flaps and hook&loop fastening • adjustable elasticated hem • seat seam designed to be easy to modify • no high-visibility protective clothing acc. to EN ISO 20471 and EN 17353.

MATERIAL: 49 % ARAMIDE, 50 % VISCOSE FR, 1% CARBON .

FABRIC WEIGHT: approx. 300 g/m²



HB-WILDFIRE® 2.0 has been specially developed to meet the increasing demands placed on emergency services. A safe and comfortable outfit that protects against flames and relieves physical strain, e.g. thanks to the inner lining with hydrophilic finish and lightweight, hard-wearing outer material that can withstand many washes.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | ** | REGULAR SIZES | | |
|-----------|---|------------|-------------------------------|------------------------------------|----------|----------------------|--|--|
| | | 3390 | red/dark blue/black | : | | | | |
| 1 | | 3393 | dark blue/dark blue/ black | EN ISO 11612 A1+A2/B1/ C1/F1 | EN 15384 | 46-58, 23-29, 94-110 | | |
| | | 3394 | gold/gold/black | : | | | | |
| FIEL DC O | FIFTO OF ADULGATION. For Cabries is wide as as Tarbairal Assistance | | | | | | | |

FIELDS OF APPLICATION: Fire fighting in wide areas, Technical Assistance





Stand-up collar with flap

Inserted walkie-talkie pockets

and snap fastener



Hook&loop strips for back collar covered with outer material

Opening for antenna/ hook straps for radio attachment

Inner lining with hydrophilic features: absorbs moisture. releases it in the form of evaporative cooling -> the wearer does not sweat as quickly

JACKET

Wildland firefighting

Part number: 01284 10196 003 + COLOUR NO.

Garment weight: approx. 1,200 g

Three-coloured • with segmented yellow/silver/yellow reflective stripes • no high-visibility clothing according to EN ISO 20471 and EN 17353 • stand-up collar with flap and snap fastener • fastening strip with zip and covered snap fastener • covered hook&loop strips on front and back for fastening the overcoat back coller • front part lined • elbow reinforcement with silicone-coated trim • 2 set-in radio pockets on the chest with flaps and covered hook&loop fastener; right with opening for the antenna and 2 hook straps for attaching the radio • 1 inside pocket on the right; 1 Napoleon pocket on the left ullet 2 set-in side pockets with flap and covered hook&loop fastener • back section with 2 movement pleats • ergonomically shaped sleeves with adjustable hem width.

MATERIAL: 49.5 % VISCOSE FR, 49.5 % ARAMID, 1% CARBON ·


FABRIC WEIGHT: approx. 230 g/m²





| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | THREE REGULAR SIZES |
|------|--------|------------|-------------|---|
| | | 10 | white | 40-48: for jackets sz. 40-48; 86-98; 20-24 |
| 2 | | 17 25 | red | 50–58: for jackets sz. 50–58; 102–118; 25–29 |
| | | 41 | royal | 60-70: for jackets sz. 60-70; 122-142; 30-35 |

FIELDS OF APPLICATION: Fire fighting in wide areas, Technical Assistance



IDENTIFICATION COLLAR

Wildland firefighting

Part number: 01266 70049 001 + COLOUR NO.

Optional label collar complementing the jacket in order to indicate the function • available in several colours for different functions • attached via hook&loop tape on the front and on the back of the jacket.





i.....i





MATERIAL: 54 % MODACRYLIC, 45 % LYOCELL, 1% CARBON ·

FABRIC WEIGHT: approx. 320 g/m²

HB-WILDFIRE® 2.0

The elaborate manufacture of HB-Wildfire® 2.0 with special moulded seams and segmented reflective strips ensures freedom of movement. Particularly exposed areas are reinforced with a silicone-carbon trim and all pockets have hook & loop fasteners. Button-on braces provide additional comfort. Jackets and trousers are also available in long and short sizes.

| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | | | REGULAR SIZES | | |
|------|--|------------|------------------|-----------------------------|----------|----------------------|--|--|
| : | | 2197 | red/black | : | • | | | |
| 3 | | 2395 | black blue/black | EN ISO 11612 A1+A2/B1/C1 | EN 15384 | 46-58, 23-29, 94-110 | | |
| | | 2414 | gold/black | : | • | | | |
| FIFE | FIFTOGOS ADDITION ST. C. L. C. L. C. L. C. L. C. L. C. L. C. | | | | | | | |

FIELDS OF APPLICATION: Fire fighting in wide areas, Technical Assistance



Waist adjustment with elastic band

Hem with adjustable elastic



The perceptibility acc. to EN 15384 is given when jacket and trousers are worn together. The values prescribed in the standard correspond to the requirements of DGUV 205-020.

Silicone-coated hem protector



TROUSERS

Wildland firefighting

Part number: 01284 20152 000 + COLOUR NO.

Garment weight: approx. 870 g

Two-coloured • with segmented yellow/silver/yellow reflective stripes • no high-visibility clothing according to EN ISO 20471 and EN 17353 • buttons in the waistband for attaching braces • waist adjustment by elastic band on the sides • covered zip • 2 wing pockets • silicone coated knee reinforcement and hem protection • inner leg reinforcement • 1 hip pocket • 2 bellow pockets on side seam each with flap and hook&loop • 2 outside knee pockets • hem with adjustable snap fastener flap.

MATERIAL: 49.5 % MODACRYLIC, 49.5 % COTTON, 1 % CARBON

FABRIC WEIGHT: approx. 230 g/m²





| ITEM | COLOUR | COLOUR NO. | COLOUR NAME | REGULAR SIZES |
|------|-----------------------------------|------------|-------------|---|
| | | 25 | red | |
| 4 | | 488 | black blue | One size |
| | | 68 | gold | |
| : | • · · · · · · · · · · · · · · · · | ••••• | | • |

FIELDS OF APPLICATION: Fire fighting in wide areas, Technical Assistance



With the braces the trousers can be turned into bib and brace trousers in no time at all



BRACES

Wildland firefighting

Part number: 01284 70064 001 + COLOUR NO.

Single-coloured • adjustable buckles to adjust length • elasticated back • buttonholes to attach to trousers.







Adjustable buckles

MATERIAL: 49.5 % MODACRYLIC, 49.5 % COTTON, 1% CARBON ·

FABRIC WEIGHT: approx. 230 g/m²





NO MATTER WHAT ELECTRIFIES YOU: YOUR OUTFIT REMAINS UNAFFECTED

Not everyone has

the ability to let environmental voltages roll off them.

Our high-quality ESD clothing does: it offers reliable conductivity and prevents sensitive product parts in electronics production from being damaged by electrostatic discharge. Very reassuring: each of our products

has to pass extensive tests

to become part of our unrivalled ESD range.





CONDUCTEX® Green Turtle

Bestseller for environmental protection: our successful CONDUCTEX® coats without side seams are now also available in recycled and organically grown material. The tried and tested fabric blend now also scores with sustainability – and remains as light, comfortable and high-functional as usual. All closing seams are double-bound. Fabric with "breathability" quality label from the Hohenstein testing institute.

REGULAR SIZES ITEM Men: S-2XL 10^6 bis $10^7~\Omega$ acc. to EN 61340-5-1 (IEC 61340-5-1) 1 , 2 Ladies: XS-L

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing





LADIES COAT, LONG SLEEVE

FSD

Part number: **08100 48019 000 10** Garment weight: approx. 320 g

COAT, LONG SLEEVE

ESD

Part number: 08100 48011 000 10 Garment weight: approx. 330 g

Single-coloured • cut without side seams • lapel collar • front with one-sided covered snap fasteners • 1 attached front pocket on the left • 2 attached side pockets with slanted openings • 2 front tucks on ladies' coat • sleeve hem adjustable via snap fasteners • embroidered EPA emblem on right upper arm.

☐ white



and is GRS certified. The production of the rPET yarn requires 60% less energy and avoids 2.4kg of waste per kg of yarn.

GRS is an international, voluntary and full product standard and defines


















LADIES COAT, SHORT SLEEVE

ESD

Part number: **08100 48019 005 10** Garment weight: approx. 275 g

COAT, SHORT SLEEVE

ESD

Part number: **08100 48011 011 10** Garment weight: approx. 285 g

Single-coloured • cut without side seams • lapel collar • front with one-sided covered snap fasteners • 1 attached front pocket on the left • 2 attached side pockets with slanted openings ullet 2 front tucks on ladies $\dot{}$ coat ullet hemmed short-sleeve • embroidered EPA emblem on right upper arm.

☐ white

MATERIAL: 75 % POLYESTER, 23 % COTTON, 2 % CARBON; rec. PES/ Bio CO ·

FABRIC WEIGHT: approx. 130 g/m²





CONDUCTEX® Cotton Knit Green Turtle

We are also adding sustainable products to our successful CONDUCTEX® Cotton Knit collection: the T-shirts and polo shirts for men and women in the trend colour black are made from organically grown cotton. The environmentally friendly material is very light and comfortable and impresses with its consistently high quality and dissipative properties.

REGULAR SIZES Men: S-2XL Ladies: XS-L

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing



T-SHIRT, SHORT SLEEVE

Part number: 08023 86002 016 46 Garment weight: approx. 200 g

Single-coloured • comfortable neck width • modern shirt length, suitable for wearing over the shirt • EPA emblem on right upper arm.

black

LADIES T-SHIRT, SHORT SLEEVE

FSD

Part number: 08023 86002 016 46 Garment weight: approx. 160 g

Single-coloured • tailored cut • mnodern shirt length, suitable for wearing on top • EPA emblem on right upper arm.

black









POLOSHIRT, SHORT SLEEVE

ESD

Part number: 08023 86004 037 46 Garment weight: approx. 240 g

Single-coloured • conductive polo collar • polo placket with button fastening • left chest pocket with button fastening • modern shirt length, suitable for wearing on top • EPA emblem on right upper arm.

black

LADIES POLOSHIRT, SHORT SLEEVE

ESD

Part number: 08023 86044 003 46 Garment weight: approx. 200 g

Single-coloured • tailored cut • conductive polo collar • polo placket with button fastening • left chest pocket with button fastening • doubled sleeve cuffs • modern shirt length, suitable for wearing on top • EPA emblem on right upper arm.

black

MATERIAL: 95 % COTTON (ORGANIC), 5 % CARBON .

FABRIC WEIGHT: approx. $160 \, g/m^2$

[CONDUCTEX*]



CONDUCTEX® is one of the lightest and most comfortable materials for protection of products against electrostatic discharge. Furthermore, the blended fabric offers a good functionality and high wearing comfort. The closure seams are additionally edged. Fabric with the quality label "breathability" of the Hohenstein certification institute.

ITEM

Men: S-2XL Ladies: XS-L

REGULAR SIZES

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing

LADIES COAT, SHORT SLEEVE

ESD

Part number: 08005 48027 000 10 Garment weight: approx. 335 g

Single-coloured • female cut • lapel collar • front with one-sided covered snap fasteners • 2 side pockets with slanted openings • embroidered EPA emblem on right upper arm.

☐ white

LADIES COAT, LONG SLEEVE

FSD

Part number: 08005 48028 000 10 Garment weight: approx. 360 g

Single-coloured • female cut • lapel collar • front with one-sided covered snap fasteners • 2 side pockets with slanted openings • sleeve hem adjustable via snap fasteners • embroidered EPA emblem on right upper arm.

___ white

COAT, WITH KNITTED CUFFS

ESD

Part number: 08005 48011 040 10 Garment weight: approx. 350 g

Single-coloured • cut without side seams • lapel collar • fastener strip with covered snap fasteners • 1 breast pocket attached on left • 2 side pockets with slanted openings • sleeves with stretchable knitted cuffs • embroidered EPA emblem on right upper arm.

__ white









DISCHARGE



LADIES COAT, SHORT SLEEVE

ESD

Part number: 08005 48019 005 10 Garment weight: approx. 275 g

COAT, SHORT SLEEVE

ESD

Part number: **08005 48011 011 10** Garment weight: approx. 285 g

Single-coloured • cut without side seams • lapel collar • front with one-sided covered snap fasteners • 1 attached front pocket on the left • 2 attached side pockets with slanted openings • 2 front tucks on ladies' coat • hemmed short-sleeve • embroidered EPA emblem on right upper arm.

☐ white



LADIES COAT, LONG SLEEVE

ESD

Part number: 08005 48019 000 + COLOUR NO.

Garment weight: approx. 320 g

COAT, LONG SLEEVE

Part number: **08005 48011 000 + COLOUR NO.**

Garment weight: approx. 330 g

Single-coloured ullet cut without side seams ullet lapel collar ullet front with one-sided covered snap fasteners • 1 attached front pocket on the left • 2 attached side pockets with slanted openings • 2 front tucks on ladies' coat • sleeve hem adjustable via snap fasteners • embroidered EPA emblem on right upper arm.

__ 10 white 41 royal 45 navy 46 black

50 silver grey 471 pastel blue 58 anthracite

i.....i.



MATERIAL: 75 % POLYESTER, 23 % COTTON, 2 % CARBON .

FABRIC WEIGHT: approx. 130 g/m²

CONDUCTEX*

CONDUCTEX®

CONDUCTEX® is one of the lightest and most comfortable materials for protection of products against electrostatic discharge. Furthermore, the blended fabric offers a good functionality and high wearing comfort. The closure seams are additionally edged. Fabric with the quality label "breathability" of the Hohenstein certification institute.

ITEM REGULAR SIZES 46-58 & 94-110 1 , 2

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, warehouse work within electronics manufacturing



BLOUSON

ESD

Part number: 08005 18006 000 + COLOUR NO. Garment weight: approx. 380 g

Single-coloured • stand-up collar with slanted corner and covered snap fastener • front with covered snap fastening • 1 straight cut pocket on the left front • 2 side pockets with zipper • ergonomic sleeves • sleeve hem adjustable via snap fastener • leasing label on the inside in the back • embroidered EPA emblem.













.....

TROUSERS

ESD

Part number: **08005 28007 000 + COLOUR NO.**

Garment weight: approx. 290 g

Single-coloured • attached waistband with covered button fastening • slit detail with plastic fastening ${}^{\bullet}$ adjustable elastic band in the back with button ${}^{\bullet}$ 2 wing pockets • 2 back pockets without flap and fastening • 1 thigh pocket on the right with flap and covered snap fastening \bullet embroidered EPA emblem.



MATERIAL: 75 % POLYESTER, 23 % COTTON, 2 % CARBON .

FABRIC WEIGHT: approx. 130 g/m²





CONDUCTEX® Cotton Knit

High Functionality - High Comfort: T-Shirts and Polo shirts made of CONDUCTEX® Cotton Knit offer high wearing comfort as they are knitted, not woven. This design allows for very high mobility. Furthermore, the materials are characterised by very good functionality thanks to its carbon file. Available in numerous colours and womens' shirts with female cut.

| ITEM | EPA EPA | REGULAR SIZES |
|---------|---|---------------|
| 1 - 3 | 10 ⁶ bis 10 ⁷ Ω acc. to EN 61340-5-1 (IEC 61340-5-1) | S-2XL |

.....

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing



T-SHIRT, SHORT SLEEVE

ESD

Part number:

08010 86002 000 + COLOUR NO.

Garment weight: approx. 180 g

Single-coloured • comfortable neck width • stylish shirt length, suitable for wearing on top • embroidered EPA emblem on right upper arm.

41 royal **45** navy 46 black **50** silver grey

POLO SHIRT, SHORT-SLEEVE

ESD

Part number:

08011 86004 002 + COLOUR NO.

Garment weight: approx. 210 g

Single-coloured • conductive polo collar • polo placket with buttoning • front pocket on the left with button • double-stitched sleeve opening • stylish shirt length, suitable for wearing on top • embroidered EPA emblem on right upper arm.

____ 10 white **50** silver grey **45** navy 46 black

More colours available on request.



POLO SHIRT, SHORT-SLEEVE

ESD

Part number:

08011 86004 000 + COLOUR NO.

Garment weight: approx. 220 g

Two-coloured • conductive polo collar • polo placket with buttoning • front pocket on the left with button • double-stitched sleeve opening • stylish shirt length, suitable for wearing on top • embroidered EPA emblem on right upper arm.

2031 royal/silver grey 2042 navy/silver grey 2186 black/silver grey 2061 silver grey/red **2064** silver grey/navy

More colours available on request.



.....

i.....i



1, 2 and 3 EPA emblem on right upper arm

MATERIAL: 95 % COTTON, 5 % CARBON ·

FABRIC WEIGHT: approx. 160 g/m²

(CONDUCTEX*)



CONDUCTEX® Cotton Knit

High Functionality - High Comfort: Polo shirts made of CONDUCTEX® Cotton Knit offer high wearing comfort as they are knitted, not woven. This design allows for very high mobility. Furthermore, the materials are characterised by very good functionality thanks to its carbon file. Available in numerous colours and womens' shirts with female cut.

ITEM REGULAR SIZES Men: S-2XL $10^{4}\ bis\ 10^{7}\ \Omega$ acc. to EN 61340-5-1 (IEC 61340-5-1) 1 - 3 Ladies: XS-L

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing



LADIES POLO SHIRT, SHORT-SLEEVE

FSD

Part number: 08011 86013 000 + COLOUR NO. Garment weight: approx. 180 g

Two-coloured • female cut • conductive polo collar • polo

placket with buttoning • front pocket on the left with button • double-stitched sleeve opening • stylish shirt length, suitable for wearing on top • embroidered EPA emblem on right upper arm.

2031 royal/silver grey
2186 black/silver grey More colours available on request.

LADIES POLO SHIRT, SHORT-SLEEVE

Part number: 08011 86013 001 + COLOUR NO. Garment weight: approx. 175 g

Single-coloured • female cut • conductive polo collar • polo placket with buttoning ${}^{\bullet}$ front pocket on the left with button • double-stitched sleeve opening • stylish shirt length, suitable for wearing on top • embroidered EPA emblem on right upper arm.

10 white 50 silver grey **45** navy 46 black

More colours available on request.









POLO SHIRT, LONG-SLEEVE

ESD

Part number: 08011 86008 000 + COLOUR NO.

Garment weight: approx. 255 g

Two-coloured • conductive polo collar in contrast colour • polo placket with buttoning • front pocket on the left with button • sleeve opening in contrast colour • stylish shirt length, suitable for wearing on top • embroidered EPA emblem

on right upper arm.

2031 royal/silver grey 2042 navy/silver grey 2064 silver grey/navy 2 and 3 Collar and sleeve opening manufactured in contrast colour



MATERIAL: 95 % COTTON, 5 % CARBON ·

FABRIC WEIGHT: approx. 160 g/m²





CONDUCTEX® Cotton Knit

Sweatshirt and sweat jacket offer excellent wearing comfort, high-end manufacture and very good ESD functionality. The material is soft and smooth. As it is knitted, not woven, it fits very well and leaves you much freedom of movement.

ITEM REGULAR SIZES Unisex S-2XL 1 , 2 EN 61340-5-1 (IEC 61340-5-1)

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing

SWEATSHIRT

ESD

Part number: 08014 86019 000 + COLOUR NO.

Garment weight: approx. 440 g

Single-coloured • comfortable round neck with conductive collar • comfortable sleeve hems • embroidered EPA emblem on right upper arm.

silver grey 50 10 white 46 black



SWEAT JACKET

FSD

Part number: 08014 86012 001 + COLOUR NO.

Garment weight: approx. 520 g

50 silver grey 46 black

Part number: 08014 86012 000 2064 Garment weight: approx. 520 g

silver grey/navy

More colours available on request.

Collar, sleeve hems and waistband in contrast colour.

Single-coloured or two-coloured • very smooth and comfortable conductive sweat collar • front with zip fastener • 2 laterally attached pockets • stylish length • comfortable sleeve hems • embroidered EPA emblem on right upper arm.



MATERIAL: 95 % COTTON, 5 % CARRBON

FABRIC WEIGHT: approx. 300 g/m²

(CONDUCTEX*)



CONDUCTEX® Pro Knit



This cotton blend fabric is exceptionally soft with a maximum of wearing comfort. The knit (not woven) material provides optimum fit. It offers a high level of functionality and excellent conductivity levels. Thanks to the polyester amount it is very colorfast.

ITEM 1 , 2 EN 61340-5-1 (IEC 61340-5-1)

REGULAR SIZES

S-2XL

FIELDS OF APPLICATION: Semiconductor and telecommunications indus-

try, aerospace industry, automotive industry, electronics manufacturing

POLO SHIRT, SHORT-SLEEVE

Part number: **08012 86004 002 + COLOUR NO.** Garment weight: approx. 235 g

Single-coloured • conductive polo collar • polo placket with buttoning • front pocket on the left with buttoning • stylish shirt length, suitable for wearing on top • EPA emblem on right upper arm.

45 navy 46 black 50 silver grey

More colours available on request.



POLO SHIRT, SHORT-SLEEVE

ESD

Part number: 08012 86004 000 + COLOUR NO. Garment weight: approx. 235 g

Two-coloured • conductive polo collar in contrast colour • polo placket with buttoning • front pocket on the left with button • double-stitched sleeve opening in contrast colour • stylish shirt length, suitable for wearing on top • EPA emblem on right upper arm.

2031 royal/silver grey 2064 silver grey/navy

More colours available on request.



MATERIAL: 48 % COTTON, 48 % POLYESTER, 4 % CARBON .

FABRIC WEIGHT: approx. 170 g/m²

CONDUCTEX*



CONDUCTEX® Pro Knit

This cotton blend fabric is exceptionally soft with a maximum of wearing comfort. The knit (not woven) material provides optimum fit. It offers a high level of functionality and excellent conductivity levels. Thanks to the polyester amount it is very colorfast. Complete your outfit with our new gloves.

| ITEM | EPA . | REGULAR SIZES |
|------|---|---------------|
| 1 | 10 ⁶ bis 10 ⁷ Ω acc. to EN 61340-5-1 (IEC 61340-5-1) | Unisex S-2XL |

FIELDS OF APPLICATION: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing

For best possible protection while manufacturing electronic parts, CONDUCTEX® thread is enwinded of two high quality carbon fibres.



EPA emblem on right upper arm

.....





SWEAT JACKET

Part number: 08016 86012 005 + COLOUR NO. Garment weight: approx. 550 g

Single-coloured • very smooth and comfortable conductive sweat collar • front with zip fastener • 2 laterally attached pockets • stylish length • comfortable sleeve hems • EPA emblem on right upper arm.

46 black **45** navy

MATERIAL: 60 % POLYESTER, 33 % COTTON, 7 % CARBON ·

FABRIC WEIGHT: approx. 305 g/m²





ESD ELECTRO-STATIC DISCHARGE



Naptex® 4.0 offers reliable protection for electronic components when high surface resistance is required. The material developed by HB is suitable for industrial washing and certified with the Pro Label, withstands many washes and has a very long service life. With Hohenstein breathability label.

| ITEM | EPA EPA | | PRO I | REGULAR SIZES |
|------|---|---------------|-----------|----------------|
| 1 | 10 ⁵ bis 10 ⁶ Ω acc. to | D4b-bilia. | 100 15707 | 46-58 & 94-110 |
| 2 | EN 61340-5-1 (IEC 61340-5-1) | Breathability | ISO 15797 | 46–58 |

EINSATZGEBIETE: Semiconductor and telecommunications industry, aerospace industry, automotive industry, warehouse work within electronics manufacturing* of particularly sensitive components

BLOUSON

ESD

Part number: **08022 18006 001 41** Garment weight: approx. 425 g

1-coloured • stand-up collar with bevelled collar corner and covered snap fastening • front with covered snap fastening placket • 1 modern spade pocket on left side of chest • 2 side pockets with zip • ergonomically shaped sleeves with dividing seam • sleeves at hem with adjustable covered snap fastening • leasing label at back of collar • EPA badge on the hem.

royal



Side pockets with zip fastener

TROUSERS

ESD

Part number: **08022 28010 000 41** Garment weight: approx. 325 g

1-coloured • cut waistband with button closure • slit with zip • perforated elastic with button adjustable in the back • 2 wing pockets • 1 back pocket on the right with flap and covered snap fastener • 1 leg pocket on the right with flap and covered snap fastener, with cell phone pocket inside • embroidered EPA emblem.

royal



MATERIAL: 65 % POLYESTER, 33 % COTTON, 2 % METAL ·

FABRIC WEIGHT: approx. 165 g/m²



Naptex® 4.0 offers reliable protection for electronic components when high surface resistance is required. The clothing is suitable for industrial washing and certified with the Pro Label. It withstands many washes and has a very long service life. The material has been developed by HB and is especially breathable and certified with the Hohenstein breathability label.

ITEM 10^5 bis $10^6~\Omega$ acc. to EN 61340-5-1 (IEC 61340-5-1)

REGULAR SIZES Men: S-2XL Ladies: XS-L

EINSATZGEBIETE: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing* of particularly sensitive components

LADIES COAT, LONG-SLEEVE

ESD

Part number: 08022 48005 018 + COLOUR NO. Garment weight: approx. 370 g

COAT, LONG-SLEEVE

Part number: 08022 48000 026 + COLOUR NO. Garment weight: approx. 380 g

Single-coloured • cut without side seams • lapel collar • snap fastener closure covered on one side • 1 modern spade pocket on left chest • 2 attached side pockets with slanted openings • hemmed long sleeves • 2 darts on the women's coat • leasing label on the back of the collar • embroidered EPA emblem on the right upper arm.

10 white 41 royal



LADIES COAT, SHORT-SLEEVE

FSD

Part number: 08022 48005 019 + COLOUR NO.

Garment weight: approx. 335 g

COAT, SHORT-SLEEVE

Part number: 08022 48000 027 + COLOUR NO.

Garment weight: approx. 340 g

Single-coloured • cut without side seams • lapel collar • snap fastener closure covered on one side • 1 modern spade pocket on left chest • 2 attached side pockets with slanted openings • hemmed long sleeves • 2 darts on the women's coat • leasing label on the back of the collar • embroidered EPA emblem on the right upper arm.

□ 10 white 41 royal







DISCHARGE



LADIES COAT, LONG-SLEEVE WITH CUFFS

ESD

Part number: 08022 48005 020 10 Garment weight: approx. 400 g

COAT, LONG-SLEEVE WITH CUFFS

ESD

Part number: 08022 48000 029 10 Garment weight: approx. 410 g

Single-coloured • cut without side seams • lapel collar • snap fastener closure covered on one side • 1 modern spade pocket on the left breast side • 2 attached side pockets with slanted openings • cuffs with slit and hidden snap fasteners for adjustment • 2 darts on the women's coat • leasing label on the back in the collar • embroidered EPA emblem on the right upper arm.

☐ white



COAT, WITH KNITTED CUFFS

ESD

Part number: **08022 48000 028** 10 Garment weight: approx. 400 g

Single-coloured • cut without side seams • lapel collar • snap fastener closure covered on one side • 1 modern spade pocket on left chest • 2 attached side pockets with slanting openings \bullet cuffs with knitted cuffs \bullet leasing label in the back of the collar • embroidered EPA emblem on the right upper arm.

☐ white



MATERIAL: 65 % POLYESTER, 33 % COTTON, 2 % METAL .

FABRIC WEIGHT: approx. 165 g/m²

.....



HABETEX® ESD Comfort is the perfect solution for prevention of both electric charging and high particle release. The fabric combines ESD and cleanroom features. So this is multifunctional clothing for working areas needing both ESD and cleanroom protective properties. Fabric with quality label "breathability" from Hohenstein certification institute.

REGULAR SIZES ITEM Men/Unisex: S-2XL 1,2 Ladies: XS-L

EINSATZGEBIETE: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing in cleanrooms, cleanroom requirements





COVERALL, WITH KNITTED CUFFS

ESD/Cleanroom

Part number: **08020 38002 001 10** Garment weight: approx. 385 g

Single-coloured • stand-up collar with slanted collar corner and covered snap fastener • front with covered 2-way zip fastener • ergonomic sleeves with stretchy knitted cuffs • ventilation on the back • leasing label on the inside in the back • embroidered EPA emblem on right upper arm.

☐ white













LADIES COAT, WITH KNITTED CUFFS

ESD/Cleanroom

Part number: 08020 48043 000 10 Garment weight: approx. 290 g

Single-coloured • stand-up collar with slanted collar corner and covered snap fastener • front with covered snap fastening and darts • 1 straight cutted pocket on the front • 2 slant pockets on the sides with slanted corner • ergonomic sleeves with stretchy knitted cuffs • leasing label on the inside in the back • embroidered EPA emblem on right upper arm.

white

and exceptionally high discharge values which are in a low 10° field even after 60 washings.

MATERIAL: 98 % POLYESTER, 2 % CARBON .

FABRIC WEIGHT: approx. $125\,\text{g/m}^2$ · **CHARACTERISTICS:** low weight, breathable

.....






HABETEX® ESD Comfort & ACCESSORIES ESD

HABETEX® ESD Comfort is the perfect solution for prevention of both electric charging and high particle release. The fabric combines ESD and cleanroom features. So this is multifunctional clothing for working areas needing both ESD and cleanroom protective properties. Fabric with quality label "breathability" from Hohenstein certification institute.

REGULAR SIZES ITEM Men/Unisex: S-2XL 1 , 2 Head Cover: 1/56 bis 5/64

EINSATZGEBIETE: Semiconductor and telecommunications industry, aerospace industry, automotive industry, electronics manufacturing in cleanrooms, cleanroom requirements







COAT, WITH KNITTED CUFFS

ESD/Cleanroom

Part number: 08020 48042 000 10 Garment weight: approx. 295 g

Single-coloured • stand-up collar with slanted collar corner and covered snap fastener • front with covered snap fastening and darts • 1 straight cutted pocket on the front ullet 2 slant pockets on the sides with slanted corner • ergonomic sleeves with stretchy knitted cuffs • leasing label on the inside in the back • embroidered EPA emblem on right upper arm.

☐ white









HEAD COVER

Accessories

Part number: **08020 77004 002 10** Garment weight: approx. 20 g

Single-coloured • round head part • face field with elastic • shoulder part in front closable with zip.

☐ white


MATERIAL: 98 % POLYESTER, 2 % CARBON .

FABRIC WEIGHT: approx. 125 g/m² · **CHARACTERISTICS:** low weight, breathable

.....

Very good cleanroom values and exceptionally high discharge values which are in a low 10° field even after 60 washings.





OUR PURITY LAW DOES NOT APPLY TO YOUR BEER. BUT IT DOES FOR YOUR COVERALL.

Not a grain of dust, not a lint - this is the ideal of a cleanroom.

What is not intended in nature

is indispensable in paint shops, for example. In the cleanroom, it is the hour of fabrics that secrete as little as possible and also function as filters for particles emitted by the body.







This tried and tested cleanroom fabric offers the perfect combination of particularly high wearing comfort, optimised stability and a very low weight. The manufacture of our fabric HABETEX® climatic Pro is specially adapted to suit the specific requirements of cleanrooms.





COAT

Cleanroom

Part number: **06015 47010 000 + COLOUR NO.**

Garment weight: approx. 290 g

Single-coloured • band collar • front edge with covered 2-way PVC zip fastener • 1 attached front pocket on the left • 1 inner front pocket on the right • 2 attached side pockets • visually appealing raglan sleeve with PVC snap fasteners for adjustment.

Regular sizes: 46/48-58/60

47 light blue 48 dark blue **53** grey

Cleanroom

COVERALL

Part number: 06015 37008 000 + COLOUR NO.

Garment weight: approx. 430 g

47 light blue **53** grey

Part number: 06015 37007 000 48 Garment weight: approx. 430 g

dark blue

Single-coloured • band collar • front with covered 2-way PVC zip fastener • 1 front pocket with flaps and PVC snap fastener (only dark blue: 2 breast pockets, one with name badge) • 1 hip pocket on the right with flap, no fastener • 1 trowel pocket on the right • waist adjustment via integrated elastic band with drawstring and stoppers • ventilation via cape collar on back • wristband made of bi-elastic material • elastic leg opening.

Regular sizes: 46/48-58/60

MATERIAL: 72 % VISCOSE, 28 % POLYESTER · FABRIC WEIGHT: approx. 105 g/m² ·

CHARACTERISTICS: particularly high wearing comfort, very low garment weight ·

FIELDS OF APPLICATION: Automotive industry, paint shop





CLEANROOM & DUST



A high particle retention and very comfortable material for being a polyester fabric characterise HABETEX® Micronplus, as well as good breathability. Also the manufacture of the coveralls has been specially adapted to suit very high cleanroom requirements.



COVERALL

Cleanroom

Part number: 06008 37001 000 + COLOUR NO.

Garment weight: approx. 640 g

Two-coloured • band collar • covered 2-way PVC zip fastener • 1 inner front pocket on the left • 2 attached front pockets, 1 hip pocket on the right and 1 leg pocket on the left as bellows on side seam with flap and covered hook&loop fastener • 2 side seam pockets • 1 ruler pocket on the right • outer pockets reinforced • waist adjustment via integrated elastic band with drawstring and stoppers • ventilation via cape collar on back and mesh inserts in armpit area • wristbands with vent and hook&loop fastener • leg opening adjustable via PVC snap fasteners.

Regular sizes: 46/48-58/60

2033 royal/bugatti blue 2083 anthracite/silver grey

COVERALL

Cleanroom

Part number: 06008 37012 001 + COLOUR NO.

Garment weight: approx. 640 g

Single-coloured • turn-down collar • covered 2-way PVC zip fastener • 2 attached front pockets and 1 hip pocket, each with flaps and covered hook&loop fastener • 1 inner front pocket on the left • 1 ruler pocket on the right • 2 attached thigh pockets with bellows • 1 leg pocket on the left as bellows on side seam with flap and covered hook&loop fastener • waist adjustment via integrated elastic band with drawstring and stoppers • ventilation via mesh inserts in armpit area • wristbands with vent and hook&loop fastener • leg opening with vent and adjustable via hook&loop fastener.

Regular sizes: 46/48-58/60

10 white **53** grey

<u>.....</u>

MATERIAL: 98 % POLYESTER, 2 % CARBON · FABRIC WEIGHT: approx. 150 g/m² · **CHARACTERISTICS:** fuzz resistant, suited for cleanroom areas with high requirements ·

HIGH PARTICLE RETENTION: nearly 100 % for particles > 5 µm ·

FIELDS OF APPLICATION: Automotive industry, paint shop

(HABETEX®)



HABETEX® Micronselect

Despite its very high density, this cleanroom fabric has a low fabric weight. Thus, HABETEX® Micronselect is very comfortable and offers high water vapour permeability. The manufacture of our fabric HABETEX® Micronselect is specially adapted to suit the specific requirements of cleanrooms.



Hood adjustable in chin area, field of vision and neck



COVERALL WITH HOOD

Cleanroom

Part number: 06006 37024 001 41 Garment weight: approx. 455 g

Single-coloured • attached hood, adjustable in chin area via hook&loop fastener • field of vision and neck with adjustment via elastic band • covered 2-way PVC zip fastener • 2 attached front pockets with flaps and covered hook&loop fastener • 1 hip pocket on the right with hook&loop fastener • waist adjustment with integrated elastic lateral waistband • ventilation via cape collar on back • wristband with let-in piece and hook&loop fastener • leg opening with vent and covered hook&loop fastener.

Regular sizes: 46/48-58/60

royal









COVERALL WITH HEAD COVER

Cleanroom

Part number: **06006 37032 000 + COLOUR NO.**

Garment weight: approx. 480 g

Single-coloured • integrated cap, adjustable chin area and head width via PVC snap fasteners • field of vision adjustable via elastic band • closure band with covered 2-way PVC zip fastener • 2 inner front pockets with PVC zip fastener • back ventilation via cape collar • raglan sleeves with thumb loop • leg hem with overshoe cap.

Regular sizes: 46/48-58/60

58 anthracite **10** white

41 royal

COAT

Cleanroom

Part number: **06006 47010 000 10** Garment weight: approx. 335 g

Single-coloured • standing board • closure band with covered 2-way PVC zip fastener • 1 front pocket on the left • 1 inner front pocket on the right • 2 side pockets • raglan sleeves with PVC snap fasteners for adjustment.

Regular sizes: 46/48-58/60

☐ white

.....

<u>......</u>

MATERIAL: 98 % POLYESTER, 2 % CARBON · FABRIC WEIGHT: approx. 115 g/m² ·

CHARACTERISTICS: very low fabric weight ·

FIELDS OF APPLICATION: Automotive industry, paint shop

HABETEX*



ACCESSORIES CLEANROOM

To complete your cleanroom outfit, we offer functional head protection and gloves. Both are central elements when working in areas that need to be free of dust and fluff.

HEAD COVER, ELASTIC BAND

Accessories

Part number: 06015 77000 000 47 Garment weight: approx. 40 g

Single-coloured • round upper head part • field of vision with elastic band all round • shoulder part lockable via hook&loop fastener at front.

Material: 72 % Viscose, 28 % Polyester

Grammage: approx. 105 g/m²

Sizes: 1/56-5/64 light blue



VISOR CAP

Accessories

Part number: 06008 77002 000 53 Garment weight: approx. 35 g

Single-coloured • visor made of reinforced PVC material • 2 lateral separation seams • elastic band centrally on the back • hem reinforced by PES rep ribbon.

Material: 98 % Polyester, 2 % Carbon Grammage: approx. 150 g/m² Sizes: 1/54-56 to 3/60-63

grey



VISOR CAP

Accessories

Part number: 06015 77002 000 53 Garment weight: approx. 30 g

Single-coloured • visor made of reinforced PVC material • 2 lateral separation seams • elastic band centrally on the back • hem reinforced by PES rep ribbon.

Material: 72 % Viscose, 28 % Polyester Grammage: approx. 105 g/m² Sizes: 1/54-56 to 3/60-63

grey



Elastic band centrally on the back

CLEANROOM & DUST



GLOVES

Accessories

Part number: **08009 76004 000 10** Garment weight: approx. 20 g

Uncoated, with knitted cuffs • Packaging unit: 10 pairs.

Material: Nylon for gloves 100 % Polyamide

Sizes: S-XL ☐ white



GLOVES

Accessories

Part number: **08009 76007 000 10** Garment weight: approx. 25 g

Jersey gloves • Packaging unit: 12 pairs/bag.

Material: 100 % Cotton

Sizes: 8-11 ___ white



OVERVIEW PRODUCT LINES

| | Product Line | Fabric Composition Upper material | Fabric weight (approx. | Retro Reflective | patche | lems & | ○ | |
|--------------|---|--|------------------------------|---------------------|----------|----------|-----------------|---|
| | | | g/m²) | | | | _ | |
| ≿ | HB-SecureAllround® | 75 % CO, 24 % PES, 1% Carbon | 350 | ✓ | ✓ | | Dryer | |
| <u> </u> | HB-ArcSelect® Pro | 87 % CO, 12 % PA, 1 % Carbon | 340 + 280 | | ✓ | / | | |
| Z | | • | 280 | | | / | see pages 26–31 | |
| ARC & ENERGY | | | 340 + 265 | | / | / | _ | |
| 2 | HB-4arc® | 89 % CO, 10 % PA, 1 % Carbon | 390 + 250 | : | ✓ | • | Dryer | |
| ⋖ | HB-MODarc® | 55 % MAC, 43 % CO, 2 % Carbon | 275 + 175 | | / | • | Dryer* | |
| | HB-MODarc® Reflective Stripes | 55% MAC, 43% CO, 2% Carbon | 275 + 175 | ✓ | / | • | Dryer* | : |
| | HB-MODarc®knit | 54% MAC, 44% CO, 2% Carbon | 215 | : | / | / | 5 | |
| | HB-MODarc® Sweatshirt | 54% MAC, 44% CO, 2% Carbon | 405 | : | / | • | Dryer* | : |
| | HB-PROtection® | 55% MAC, 43% CO, 2% Carbon | 275 + 175 | / | / | • | Dryer* | : |
| | HB-PROtection® Green Turtle | 54% MAC, 44% CO, 2% Carbon | 195 | : | / | | Dryer | : |
| | HB-MODarc & vis® | 55% MAC, 43% CO, 2% Carbon | 275 + 175 245 | / | / | | Dryer* | : |
| | HB-MODarc&vis® Polo-Shirt 2397 | : 49 % PES, 30 % MAC, 20 % CO, 1% Carbon | 245 | 1 | / | ✓ ✓ | | • |
| | HB-MODarc&vis® Polo-Shirt 2112 | 54% MAC, 44% CO, 2% Carbon | 275 | / | | | D* | : |
| | HB-MODarc&vis® Vest FR | : 55% MAC, 43% CO, 2% Carbon | | • | ✓ | • | Dryer* | : |
| | HB-MODarc&vis® Fleece jacket | : 48% MAC, 32% CO, 18% PES, 2% Carbon | 360 | · / | , | / | D + | : |
| | HB-MODarc&vis® Sweatshirt | 54% MAC, 44% CO, 2% Carbon | | | ✓ | <i>\</i> | Dryer* | : |
| | HB-MODarc&vis® Fleece jacket | : 48 % MAC, 32 % CO, 18 % PES, 2 % Carbon | 360 | : | , | | | : |
| | HB-MODarc&vis® Parka with liner HB-MODarc&vis® Parka | 55 % MAC, 43 % CO, 2 % Carbon, FC-Equipment | 275 300 | 1 | / | / | | : |
| | HB-MODarc&vis® Bib trousers | 55 % MAC, 43 % CO, 2 % Carbon, PU-Membrane 55 % MAC, 43 % CO, 2 % Carbon, PU-Membrane | 300 | / | <i>J</i> | <i>\</i> | | • |
| | | • 33 % MAC, 43 % CO, 2 % Carbon, FO-Membrane • 44 % MAC, 30 % CO, 20 % PA, 5 % AR, 1 % Carbon | 260 + 180 | / | / | • | Dryer* | : |
| | HB-4Energy® | : 31% PES, 28% MAC, 20% AR, 20% CV, 1% Carbon | 200 + 100 | : ' | • | ✓ | Dryer | • |
| | HB-MultiPro FR® Parka | • with liner | 320 | . / | ✓ | ✓ | | : |
| | HB-MultiPro FR® Fleece jacket | : 48 % MAC, 32 % CO, 18 % PES, 2 % Carbon | : 360 + 195 | : | | / | | : |
| | HB-MultiPro FR® Brace trousers | : 31% PES, 28% MAC, 20% AR, 20% CV, 1% Carbon | 320 | . / | / | / | | |
| | NOMEX® Viscose | 50 % CV, 49 % AR, 1% Carbon | 260 | | | / | | |
| | NOMEX® Comfort | 98 % AR, 2 % Carbon | 260 | : | 1 | / | | : |
| | INOTEC® Arc & Energy | 98 % AR, 2 % Carbon | 260 + 180 | | / | / | Dryer | : |
| | • | | | | | | | |
| _O | PROBAN® | 100 % CO | 470 | | | ✓ | Dryer | |
| ž | HB-WeldersFORCE | 79 % CO, 10 % PES, 1 % Carbon | 350 | | | | Dryer | |
| 2 | | | 450 | | | | Dryer | |
| WELDING | HB-4welders® 2.0 | 89 % CO, 10 % PA, 1% Carbon | 390 | | ✓ | ✓ | Dryer | |
| ર્ચ | HB-ComFlex® | 94 % CO, 4 % PES, 2 % Elasthane | 425 | | | | Dryer | |
| ES | | 40 % AR, 30 % MAC, 20 % CLY, 9 % PA, 1 % Carbon | 430 | | | | Dryer | |
| SPLASHES | SECAN® Securo 420 | 98 % CO, 2 % Carbon | 420 | : | 1 | ✓ | Dryer | |
| 4 | HB-Iron Pro | 98 % CO, 2 % Carbon | 420 | . / | ✓ | ✓ | Dryer | : |
| SP | HB-Iron Pro Shirt | : | 250 | : | | | Dryer | |
| j, | MARLAN | 50 % CV FR, 30 % WO, 20 % PA | 365 | : | ✓ | ✓ | Dryer+Finisher | : |
| HEAT, | HB-HeavyMetal Pro® Jacket+Trouser | 50 % CO, 39 % MAC, 10 % CV, 1 % Carbon | 340 | / | / | ✓ | Dryer+Finisher | |
| | HB-HeavyMetal Pro® Jacket+Trouser | 52 % CO, 37 % MAC, 10 % CV, 1 % Carbon | 430 | / | ✓ | • | Dryer+Finisher | : |
| | HB-HeavyMetal Pro® Shirt | 50 % CO, 39 % MAC, 10 % CV, 1 % Carbon | 250 | : | ✓ | ✓ | Dryer+Finisher | : |
| | VINEX® | 85 % Vinylal, 15 % Modal | 390 | : | ✓ | ✓ | | : |
| | | • | 285 | | ✓ | | | |
| | TEMPEX®-TREME HEAT | • | : | : | | | | : |
| | CK-12/Z | : 70 % Preox, 30 % AR | 360 | : | | | | |
| | AW-1/Y | : 100 % AR | 420 | : | | | | |
| | KF-3/Z | : 100 % AR | 475 | | | | | • |
| | CK-4/Z | 70 % Preox, 30 % AR | 690 | | | | | |
| | LID CLIENA | • • • • • • • • • • • • • • • • • • • | . 070 | : | | | | |
| LS | HB-CHEMstandard | 100 % PAC, FC-Equipment | 270 | : | 1 | / | D | : |
| CHEMICALS | HB-CHEM Protect | 99% RECYCLED PES, 1% Carbon, FC-Equipment | 240 | : | / | • | Dryer+Finisher | : |
| Σ | | : | : | : | : | : | | : |
| ± | | : | : | : | : | : | | : |
| 0 | | • | • | : | | | | |
| | | <u>:</u> | : | : | | | | |

1) A=A1+A2 🗸=Flame retardent 2) Blouson and trousers or bib and brace trousers worn together. *Reduced washing temperature 60°C.



| 14 | | 1) | | | M | \bigcirc | - E | | [y] | [ψ] | | - - | MULTI | 21to 21wear |
|-------------|--------------|--------------------|-----------|--------------|------------------------------|--------------------------|-----------|------------|--------------|--------------|--------------|------------------|---------------|----------------------|
| 13 | F | | 4 | | | \bigoplus \mathbb{C} | T | 40+ | | | EPA | 桑磺 | MULTI RISK | . 232 WEAR : : |
| IEC 61482-2 | EN ISO 11611 | EN ISO 11612 | EN 1149-5 | EN 13034 | EN ISO 20471 | EN 17353 | EN 343 | EN 13758-2 | EN 14058 | EN 342 | EN 61340-5-1 | EN 15384 | MULTI-RISK | 21 TO WEAR® |
| APC 1 | Class 1 | A/B1/C1/E2/F1 | 1 | Туре 6 | : | | | : | | | | | ✓ | / |
| APC 1/2 | Class 1 | A/B1/C1/F1 | 1 | : | : | B2 | | : | | | | | ✓ | / |
| APC 1 | Class 1 | A/B1/C1/E1/F1 | ✓ | : | : | : | : | : | : | : | : | : | ✓ | · / |
| APC 2 | Class 1 | A/B1/C1/F1 | / | : | : | | : | : | : | | : | | / | · / |
| APC 2 | Class 2 | A/B1/C1/E3/F1 | ✓ | : | : | | : | : | : | | : | | ✓ | · / |
| | Class 1 | A/B1/C1/F1 | / | Туре 6 | : | | : | : | : | | : | | ✓ | / |
| APC 1/2 | Class 1 | A/B1/C1/F1 | ✓ | Туре 6 | : | B3 | : | : | : | | : | | / | / |
| APC 1 | | A/B1/C1/F1 | ✓ | : | : | | : | · / | : | | : | | ✓ | : |
| APC 2 | | A/B1/C1 | ✓ | : | : | | : | · / | : | | : | | ✓ | : |
| APC 1/2 | Class 1 | A/B1/C1/F1 | ✓ | Туре 6 | : | | | | | | | | ✓ | / |
| APC 1 | | A/B1/C1/F1 | ✓ | | : | | | | | | | | | / |
| APC 1/2 | Class 1 | A/B1/C1/F1 | 1 | Туре 6 | Class 3 ²⁾ | | | | | | | | ✓ | / |
| : APC 1 | | : A1/B1/C1/F1 | 1 | : | Class 2 | | : | / | : | | • | | / | : |
| APC 1 | | A/B1/C1/F1 | 1 | : | Class 2 | | : | · / | : | | | | / | : |
| : | | A/B1/C1/F1 | 1 | : | : | | : | : | : | | : | | · / | / |
| APC 1 | | A1/B1/C2/F1 | 1 | : | Class 2 | | : | : | Class 1 | | : | | / | / |
| APC 2 | | A1/B1/C1 | 1 | : | Class 2 | | : | · / | : | | • | | / | : |
| : | | : | | : | : | | : | : | Class 1 | | : | | / | |
| APC 2 | Class 1 | A/B1/C1/E1/F1 | 1 | :Type PB [6] | Class 2 | | CI. 3/3 | : | : | | : | | / | : |
| APC 2 | Class 1 A1 | A1/B1/C1/F1 | / | • | Class 2 | | CI. 3/4 | : | : | | : | | / | |
| APC 1 | Class 1 A1 | A1/B1/C1/F1 | 1 | • | Class 1 | | Cl. 3/4 | : | : | | : | | / | . / |
| APC 1/2 | Class 1 A1 | A1/B1/C1/F1 | / | • | Class 3 ²⁾ | | : | : | : | | : | | / | : |
| : APC 2 | | A1/B1/C1/E1/F1 | / | • | : : Class 3 ²⁾ | | Cl. 3/4 | : | | | : | | / | : |
| APC 1/2 | : | : A1/B1/C2/F1 | / | : | : | : | : | : | Class 1 | : | : | | / | |
| | | : A1/B1/C1/E1/F1 : | 1 | Tuna 6 | : Class 1 | | CI. 3/4 | : | · Class I | | : | | <i>'</i> | : |
| :APC 1 | • | : A1/B1/C1/F1 : | <i>'</i> | Type 6 | · Cluss I | : | · Cl. 3/4 | : | : | : | • | | <i>'</i> | |
| :APC1 | • | : A1/B1/C1/F1 | <i>y</i> | : | <u>:</u> | : | : | <u>:</u> | : | : | : | | • • | : ' |
| APC 1/2 | | • | | T | : | : | : | : | : | : | : | | / | : |
| AFC 1/2 | | A1/B1/C1/F1 | ✓ | Туре 6 | | | | : | | | • | | . , | : |
| • | Class 2 A1 | A1/B1/C1/E3/F1 | | | | | | | | | | | | |
| : | Class 1 | A/B1/C1/E2/F1 | / | : | : | | : | : | : | | • | | : | : |
| | Class 2 | A/B1/C1/E2/F1 | / | : | : | | : | : | : | | • | | | : |
| | • | A/B1/C1/E3/F1 | / | • | • | | • | : | • | | | | / | ./ |
| : | • | A/B1/C1/E2 | · | : | : | | : | : | : | | | | | : |
| • | • | A/B1/C1/E2 | | • | : | | • | • | • | | • | | • | : |
| | • | A/B1/C1/E3/F1 | 1 | | • | | | | | | | | | : |
| | | A/B1/C1/E3/F1 | / | | : | / | | | | | | | / | / |
| | • | A/B1/C1/E1/F1 | / | | | , | | | | | | | , | , |
| | | A1/B1/C1/D3/E3/F1 | • | : | • | | • | • | • | | | | | |
| : | Class 1 | A/B1/C1/D2/E2/F1 | / | : | : | / | : | : | : | | | | / | : |
| : | | A/B1/C1/D3/E3/F1 | 1 | : | : | / | : | : | : | | | | / | : |
| | | A/B1/C1/D1/E2/F1 | / | : | : | | : | : | : | | : | | | : |
| | | A/B1/C1/D3/E2/F1 | · | : | : | | | • | | | | | | : |
| | | A/B1/C1/D1/E1/F1 | • | : | : | | | : | | | | | • | : |
| : | | | | : | : | | : | : | : | | | | | : |
| : | | A1/B1/C3/D3/E3/F1 | | : | : | : | : | : | : | : | : | | : | : |
| : | | A1/B1/C4/D3/E3/F2 | | : | : | : | : | : | : | : | : | : | : | : |
| : | | A1/B1/C3/D3/E3/F1 | | : | : | : | : | : | : | : | : | : | : | : |
| : | | A1/B1/C3/D3/E3/F2 | | : | : | : | : | : | : | : | : | | : | : |
| : | | : | | : | : | : | : | : | : | : | : | | : | : |
| | | | | Туре 6 | : | | | : | | | | _ | | : |
| | | : | / | Туре 6 | : | | | : | | | | | | / |
| | | | | : | : | | | : | : | | | | : | : |
| | | | | : | : | : | : | : | : | : | : | | : | : |
| | | : | | : | : | | : | : | : | : | : | | : | : |
| : | | : : | | : | : | | : | : | : | | : | | : | : |

> OVERVIEW PRODUCT LINES

| | : | : | : | | | | : | : |
|-------------------------------------|--------------------------------------|--|-------------------|---------------------|------------------|----------|-----------------------|--------------|
| | Product Line | Fabric Composition Upper material | Fabric weight | Retro Reflective | Attach of emb | lems & | | |
| | | | (approx. g/m²) | | Patch | Stitch | ISO 15797 | : |
| ~ | HI-VISION® Basic Reflective Shirts | 55 % CO, 45 % PES | 185 | / | 1 | . / | : : Dryer+Finisher | : |
| EATHER | HI-VISION® Basic Parka | 99 % PES, 1% Carbon, Fluorcarbon finish | 150 | / | | . / | : | : |
| A T | HB-StormBase® Parka+Brace trousers | 99 % PES, 1% Carbon, Fluorcarbon finish | 150 | 1 | | : | | : |
| HIVIS & WE | | | | | | | | |
| | TEMPEX® CLASSIC 2.0 | : : 100 % PA | 515 | √ 3) | | / | : | : |
| Z | TEMPEX® CLASSIC | : 100 % PA | 415 | ✓ 3) | | : * | • | : |
| ECTION | TEMILEX CEASSIC | . 100 /01 /4 | 520 | √ 3) | | : | : | : |
| <u> </u> | | | 560 | ✓ ³⁾ | | : | : | : |
| PROT | | | 630 | √ 3) | | : | • | : |
| <u> </u> | | | 645 | · · | | : | • | : |
| 2 | TEMPEX® COMFORT | : : 100 % PA | :445/545/645 | √ 3) | | / | | • |
| COLD | TEMPEX® HYGIENE | 100 % PA | 415/515 | | | / | | |
| | TEMPEX® THERMO | 100 % PA | 265/155/245 | | | | | : |
| | TEMPEX® THERMO HYGIENE | 100 % PA | 245 | | | : | | : |
| | TEMPEX® COLD Pro | 100 % PA | 620 | / | | : | Dryer | : |
| | | | | | | : | | : |
| S | Flammgard® Klassik | 49 % AR, 50 % CV FR, 1% Carbon | 300 | | 1 | / | • | : |
| ä | Flammgard® Green Turtle Poloshirt | 100 % RECYCLED PES | 160 | | 1 | / | | |
| ≅ | Flammgard® Green Turtle Shirt/Blouse | 100 % CO (ORGANIC) | 120 | | ✓ | ✓ | | : |
| SERVICES | Flammgard® Nordrhein-Westfalen | 59 % AR, 40 % CV FR, 1% Carbon | 260 | | ✓ | ✓ | | : |
| 144 | Flammgard® Baden-Württemberg | 59 % AR, 40 % CV FR, 1% Carbon | 260 | | 1 | ✓ | : | : |
| RESCU | Flammgard® Saarland | 59 % AR, 40 % CV FR, 1% Carbon | 260 | | / | / | : | : |
| ES | Flammgard® Bayern | 63 % PES, 33 % CO, 4 % Elasthane | 245 | | ✓ | ✓ | : | : |
| - 2 | Softshell | 94% PES, 6% Elasthane | 300 | | / | · / | : | : |
| FIRE | Fleece | : 100 % PES | : 300/260 | | | · / | : | : |
| E | HB-Technical Rescue Parka | 98% AR, 2% Carbon | 195 | ✓ | ✓ | ✓ | : | : |
| | HB-Technical Rescue Trouser | 59 % AR, 40 % CV FR, 1% Carbon | 260 | ✓ | ✓ | ✓ | | : |
| | HB-Technical Rescue Fleece | 48 % MAC, 32 % CO, 18 % PES, 2 % Carbon | 360 | | ✓ | ✓ | : | : |
| | HB-Technical Rescue lite | 49 % AR, 50 % CV FR, 1% Carbon | 300 | ✓ | ✓ | √ | | |
| | HB-Wildfire® 2.0 | 49.5 % CV FR, 49.5 % AR, 2 % Carbon | 230 | ✓ | ✓ | / | • • | : |
| | CONDUCTEX® Green Turtle | : 75 % RECYCLED PES, 23 % CO (ORGANIC), 2 % Carbon | 130 | | / | . / | | : |
| ESD | CONDUCTEX® Cotton Knit Green Turtle | • | 160 | | / | . , | | |
| <u> </u> | CONDUCTEX® | 75 % PES, 23 % CO, 2 % Carbon | 130 | | / | | | : |
| | CONDUCTEX® Cotton Knit | 95% CO, 5% Carbon | 160 | | 1 | . , | • | : |
| | CONDUCTER COLLON KINC | 73 % 66, 3 % 6415611 | 300 | | , | / | | : |
| | CONDUCTEX® Pro Knit | : 48 % CO, 48 % PES, 4 % Carbon | 170 | | / | / | | : |
| | | 60 % PES, 33 % CO, 7 % Carbon | 305 | | / | . / | : | : |
| | Naptex® 4.0 | 65 % PES, 33 % CO, 2 % Metall | 165 | | / | . / | Dryer+Finisher | : |
| | HABETEX® ESD Comfort | 98% PES, 2% Carbon | 125 | | 1 | 1 | | |
| | | | | | | | | |
| 2 | HABETEX® climatic Pro | 72 % CV, 28 % PES | 105 | | 1 | | | |
| ó | HABETEX® Micronplus | 98% PES, 2% Carbon | 150 | | / | | | : |
| 5 | HABETEX® Micronselect | 98% PES, 2% Carbon | 115 | | 1 | : | : | : |
| CLEANROOM | | | : | | | : | • | : |
| = = = = = = = = = = = = = = = = = = | | | : | | | : | • • | : |
| | | | : | | | : | • | : |

^{✓ =} Flame retardent 3) Reflective application, no Hi-Vis protection. 4) Does not apply to blouson and trousers. 5) Applies to jacket and trousers. *Reduced washing temperature 60 °C.



| 15 IEC 61482-1 | 2 EN ISO 11611 | 1) EN ISO 11612 | <u>4</u> EN 1149-5 | EN 13034 | | △ℂ EN 17353 | | EN 13758-2 | EN 14058 | EN 342 | EN 61340-5-1 | EN 15384 | MULTI-RISK | ZITO ZIWEAR 21 TO WEAR® |
|-----------------------|----------------|--------------------|-----------------------|-------------|---------|------------------------|--------------------|------------|----------|-------------|--------------|-----------------|------------|---|
| | • | | | | Class 2 | | | / | | | | | | |
| | : | : | <i>'</i> | | Class 2 | | CI. 3/3 CI. 3/3 | | | | | | | |
| | : | : | | | : | | | | | | | | | |
| | | : | | • | : | | | • | | | • | | | |
| | | : | | | : | | | | | | | | | |
| | | : | | | | | | | | | | | | |
| | | : | | | • | | | • | | ✓ ✓ | | | | |
| | | : | | | : | | | : | | / | | | | |
| | | : | | | : | | | • • | | / | • | | | |
| | : | : | | | : | | | | | ✓ ✓ | | | | |
| | : | : | | | • | | | • | | 1 | | | | |
| | | : | | | : | | | | | | | | | |
| | | | | | | √ ⁵⁾ | | | | √ 5) | | | | |
| | | : A/B1/C1 | | | : | | | : | | | | | | |
| | | | | | : | | | | | | | | | |
| : | : | : : A/B1/C1 | / | | : | | | • | | | | | | |
| | | A/B1/C1 | / | | : | | | | | | | | | |
| | | A/B1/C1 | / | | : | | | • | | | | | | |
| | | : | | | : | | | | | | | | | |
| : | | A/B1/C1 | | | • | | CI. 3/3 | | | | | | | |
| : | : | A/B1/C1 | : | | : | | | • | | | | | | |
| | | A/B1/C1 | | | : | | | : | | | | | | |
| | | A/B1/C1/F1 | | • | | | | • | | | | ✓ | | |
| | | | | | | | | | | | 1 | | | ✓ |
| | | | | | : | | | : | | | <i>/</i> | | | √ 4) |
| | | : | : | | : | | | | | | 1 | | | , |
| | <u>:</u> | <u>:</u> | | | : : | | | | | | <i>/</i> | | | |
| | | | | | : | | | : | | | / | | | |
| | | | | | | | | | | | 1 | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | • | : | | | : | | | • | | | | | | |
| | : | : | | • • • | : : | <u>.</u> | | <u>.</u> | | | • | | | • |
| : | : | : | : | | : | | | : | | | : | | | |

> EMBLEMS AND PATCHES







HOW YOUR PPE BECOMES YOUR CORPORATE IDENTITY

Your employees' protective clothing is now just as much a part of your company's image as your website or vehicles – it is your company's business card as it conveys expertise and is immediately perceived by your customers. Equipped with company emblems and name badges, it also supports employees' identification with the company and is an important distinguishing feature.

However, to ensure that safety doesn't get left behind and conformity with standards doesn't suffer, a few important points must be noted.

The PPE Regulation, which has been in force since 2018, clearly stipulates that any subsequent changes to PPE that are not in accordance with the respective Type examination certificate will result in the certification becoming null and void. This means that anyone who makes a change of this kind becomes the manufacturer of a new item of PPE. which must undergo recertification.

At HB Protective Wear, we have certified our product lines in such a way that they can be equipped with different emblem variants. Embroidered emblems, direct embroidery, patched or woven emblems are available in different sizes depending on the product.

We only use materials that have successfully undergone certification so that the certified protective properties of the garments are still guaranteed after finishing. To see which emblem variants are available for your collection, please refer to the overview starting on page 212.

If you would like to attach emblems to your HB Protective Wear garments or those of your customers yourself, please contact us. We will be happy to provide information on what to consider concerning material, size and attachment position when customising your HB collection. This is because only materials and emblem sizes that have been tested in the course of certification may be used, so as not to put the certification and safety of your protective clothing at risk.







IMPORTANT INFORMATION FOR ATTACHING EMBLEMS AND BADGES:

The implementation of certification-relevant changes to protective clothing - such as the subsequent affixing of emblems - by third parties, which are not carried out in conformity with the manufacturer's specifications, means that the products concerned are no longer covered by the respective Type examination certificate and the certification becomes null and void. Subsequent attachment of any emblems to our protective garments is only possible if they have been certified as part of a Type examination. Therefore we would advise that the finishing of our protective clothing products is carried out by HB as the manufacturer.



| | (<u>4</u>) | | | A (1) | | | ** |
|------------------------|--|--|--|------------------------------------|--|--|---|
| STANDARDS | EN 1149-5 Antistatic protection | EN 11611 Welding protection | EN 11612 Heat and flame protection | EN 61482-2 Arc Flash protection | EN 20471 High visibility reflective properties | EN 13034 Type 6 Chemical protection | EN 342 Cold protection |
| EMBROIDERED EMBLEMS | Emblems (made from antistatic fabric), accessories and other features with no conductive properties, have to be firmly attached without being able to become detached; it is not allowed to fix them via hook &loop fastening or via snap fasteners. | certified FR version If a background me tested by the man emblem must be t | aterial and/or embro ufacturer is used, the | oidery yarn not e embroidery | In order to comply with the determined high-visibility protection classes, the manufacturer's instructions regarding the maximum available space for the emblem application must be considered when selecting the emblem sizes.* At least 5 cm distance to reflective stripes are to be kept. | Free-standing embroidery badges are to be tested on the garment. In addition, same fabric or a comparable material with the same or higher performance class is to be used as background material. Small embroidery | Embroidered emblems can be applied without affecting the thermal insula- tion specified by the manufac- turer.* |
| | If a background material and/or embroidery yarn not tested by the manufacturer is used, the embroidered emblem must be explicitly tested on the desired materials if the size exceeds 100 cm²! | | Manufacture: For the EN standard code E and D 1-3, manufacture in the roof tile effect is always necessary to do. | | | badges that can be attached touching the edges are allowed. | |
| DIRECT EMBROIDERIES | | with a FR material The embroidery ya FR version. If anoth | Manufacture: The direct embroidery absolutely must be underlaid with a FR material towards the body. The embroidery yarn is only to be used in certified FR version. If another embroidery thread is used, the direct embroidery must be tested individually. | | | The direct embroidery must be underlaid with outer fabric towards the body. Direct embroideries larger than 20 qcm must be explicitly tested on the garment. Large direct embroideries are generally not recommended. | Direct embroideries are only allowed to be attached for the following product lines: Comfort, Hygiene and Fleece; they need to be tested depending on the embroidery's size.* |
| PATCHED EMBLEMS | If a patch emblem not tested by the manufacturer is used, the patch emblem must be explicitly tested on the desired materials if the size exceeds 100 cm²! | pages 214–217), an individually in the EN 15025, ISO 1749 | Manufacture: Material qualities not shown in our catalogue (see pages 214–217), and marked as certified, must be tested individually in the largest possible size in accordance with EN 15025, ISO 17493 and EN 1149-5 and, if necessary, in accordance with the standard specification code D+E. | | | Patch badges up to a size of 320 x120 mm are tested and approved by the manufacturer. | Not allowed. |
| WOVEN EMBLEMS | Web emblems that are not conductive must be firmly attached without being able to be- come detached. | For woven emblems larger than 10 cm² has to be available a recent test report according to EN 15025. | | | In order to comply with the determined high-visibility protection classes, the manufacturer's instructions regarding the maximum available space for the emblem application must be considered when selecting the emblem sizes.* At least 5cm distance to reflective stripes are to be kept. | Woven badges larger than 20 qcm must be explicitly checked. | Woven emblems can be applied without affecting the thermal insulation specified by the manufacturer.* |

^{*} The details of the maximum available space for the emblem application are shown on our product data sheets for each sales item. Please contact our sales representatives fore more information (see page 231).

OUR PARTNERS

WE SUCCESSFULLY COOPERATE WITH THE FOLLOWING COMPANIES IN THE FIELD OF ACCESSORIES:







JOINTLY STRONG

Fair and cooperative collaboration with all our partners has always been very important

In order to be able to offer our customers the best possible quality, we also rely on long-term cooperation with renowned manufacturers for our accessories, so that we can continue to meet the highest standards for both.











> 21 TO WEAR®

The following versions will be supplied within our high-speed delivery service 21 TO WEAR®. First order starting with 1 piece and delivery time approx. 21 days. No stock-keeping for these products. Requirements of more than 30 pieces will normally be produced separately, the production time then will be approx. 6-8 weeks from receipt of order.

21 TO WEAR® FOR LADIES

| Item number | Designation | Material | Colour | Weight | Standards | |
|----------------------|---|---|----------------------------|---------------------------------------|---|--|
| HB-PROtectio | n® Ight | | | | | |
| 01072 10206 006 2177 | Ladies jacket 1-ply 4kA | | navy/dark grey | approx. 275 g/m² | IEC 61482-2 APC 1 EN ISO 11612 A1+A2/B1/C1/F1 EN ISO 11611 Class 1 A1+A2 | |
| 01072 20144 010 2175 | Ladies trousers 1-ply 4kA | | dark grey/navy | арргох. 273 g/т | EN 1149-5 EN 13034 Type 6 | |
| 01072 10206 008 2177 | Ladies jacket 2-ply 7kA/4kA | 55 % Modacrylic, 45 % Cotton, 2 % Carbon | navy/dark grey | approx. 275 g/m² +approx. 175 g/m² | IEC 61482-2 APC 2 (front parts and sleeves) EN ISO 11612 A1+A2/B1/C1/F1 EN ISO 11611 Class 1 A1+A2 EN 1149-5 EN 13034 Type 6 IEC 61482-2 APC 2 EN ISO 11612 A1+A2/B1/C1/F1 | |
| 01072 10206 007 2177 | Ladies jacket 2-ply 7kA | | | | EN ISO 11611 Class 1 A1+A2 EN 1149-5 EN 13034 Type 6 | |
| HB-PROtectio | n® Green Turtle 🏻 🐺 | (1) | | | | |
| 01251 60029 000 52 | Ladies shirt 1-ply 4kA | 54% Modacrylic, 44% Cotton (organic), 2% Carbon | middle grey | approx. 195 g/m² | IEC 61482-2 APC 1 EN ISO 11612 A1+A2/B1/C1/F1 EN 1149-5 EN 13758-2 | |
| HB-MODarc® | light 💆 🕕 | | | | | |
| 1072 10206 002 2251 | Ladies blouson 1-ply 4kA | | grey/black | | | |
| 1072 20144 006 2188 | Ladies trousers | | black/grey | | | |
| 1072 20144 006 2251 | 1-ply 4kA | | grey/black | | IEC 61482-2 APC 1 EN ISO 11612 A1+A2/B1/C1/F1 | |
| 1072 10206 013 2041 | Ladies blouson Reflective | | navy/royal | approx. 275 g/m² | EN ISO 11611 Class 1 A1+A2 EN 1149-5 | |
| 1072 10206 013 2251 | Stripes 1-ply 4kA | 55 % Cotton, | grey/black | | EN 13034 Type 6 | |
| 1072 20144 020 2188 | Ladies trousers Reflective | 43% Modacrylic, 2% Carbon | black/grey | | | |
| 1072 20144 022 45 | Stripes 1-ply 4kA | | navy | | | |
| 1072 10206 014 2041 | Ladies blouson Reflective Stripes 2-ply 7kA/4kA | | navy/royal | | IEC 61482-2 APC 2 (front parts and sleeves/front | |
| 1072 10206 014 2251 | Suipes 2 ply 7/6/04/67 | | grey/black black/grey | approx. 275 g/m² | of trouser legs) EN ISO 11612 A1+A2/B1/C1/F1 | |
| | Ladies trousers Reflective Stripes 2-ply 7kA/4kA | | | +approx. 175 g/m² | EN ISO 11611 Class 1 A1+A2 EN 1149-5 | |
| 01072 20144 023 45 | , , , , , | | navy | | EN 13034 Type 6 | |
| HB-MODarc&\ | ∕is [®] ∰ | , | | | | |
| 01072 10206 004 2112 | Ladies blouson 1-ply 4kA | | | approx. 275 g/m² | EN ISO 20471 Class 1+2* IEC 61482-2 APC 1 EN ISO 11612 A1+A2/B1/C1/F1 | |
| 01072 20144 008 2112 | Ladies trousers 1-ply 4kA | EFO/ Madagardia | | -FF: -::: 210 91 111 | EN ISO 11611 Class 1 A1+A2 EN 1149-5 EN 13034 Type 6 | |
| 01072 10206 005 2112 | Z-pliy /kA/4kA Z% Carbon | | fluorescentyellow/ navy | approx. 275 g/m² +approx. 175 g/m² | EN ISO 20471 Class 1+2* IEC 61482-2 APC 2 (front parts and sleeves/fron of trouser legs) EN ISO 11612 A1+A2/B1/C1/F1 EN ISO 11611 Class 1 A1+A2 EN 1149-5 | |





- For all those who require PPE urgently
- Rapid response to immediate requirements
- Get your employees started straight away
- 100 % HB quality
- Reduces your stock

Please find more information at

www.21towear.de

| Item number | Designation | Material Colour | | Weight | Standards | | |
|--|-----------------|-----------------------------|---|---------------------|--|--|--|
| HB-4welders® | | | | | | | |
| 01237 20144 011 458 | Ladies trousers | 89 % Cotton, | navy | 700 (2 | EN ISO 11611 Class 2 A1+A2 EN ISO 11612 A1+A2/B1/C1/E3/F1 | | |
| 01237 20144 011 52 | 2-ply 7kA | 10% Polyamide, 1% Carbon | medium grey | ·· approx. 390 g/m² | EN 1149-5 IEC 61482-2 APC 1 | | |
| HB-CHEMprotect | | | | | | | |
| 02018 40073 000 2030 02018 40073 000 2382 | ·· Ladies coat | 99% Polyester, 1% Carbon | royal/dark blue anthracite/dark blue | 0.40 / 1 | EN 13034 Type 6 EN 1149-5 | | |

21 TO WEAR® FOR MEN

| Item number | Designation | Material | Colour | Weight | Standards |
|--|---|-----------------------------|---|---------------------------------------|--|
| HB-MODarc® | MULTI Sight | | | | |
| 1072 10107 034 2188 | Blouson 1-ply 4kA | | | approx. 275 g/m² | IEC 61482-2 APC 1 |
| 1072 10107 035 2188 | Blouson 2-ply 7kA/4kA | 55 % Cotton, | blask/aray | approx. 275 g/m² +approx. 175 g/m² | (2-ply: IEC 61482-2 Class 2 (front parts and sleeves)) EN ISO 11612 A1+A2/B1/C1/F1 |
| 1072 10107 050 2188 | Blousop Reflective Stripes | | bideki grey | approx. 275 g/m² | EN ISO 11611 Class 1 A1+A2 |
| 1072 10107 051 2188 | Blouson Reflective Stripes 2-ply 7kA/4kA | | | approx. 275 g/m² +approx. 175 g/m² | EN 13034 Type 6 |
| HB-Iron Pro | MULTI TES | | | | |
| | Trousers with knee pocket | | | • | EN ISO 11612 A1+A2/B1/C1/E3/F1 EN ISO 11611 Class 2 A1+A2 |
| 1248 50100 006 3011 | Bib and brace trousers with knee pocket | 98% Cotton, 2% Carbon | middle grey/orange/ fluorescent yellow | approx. 420 g/m² | EN 1149-5 IEC 61482-2 Class 1 EN 17353 Type B2 |
| HB-CHEMprot | ect | | | | |
| 02018 20000 014 2030 02018 20000 014 2082 | · Trousers with knee pocket | 99% Polyester, 1% Carbon | royal/dark blue anthracite/dark blue | · approx. 240 g/m² | EN 13034 Type 6 EN 1149-5 |

> TEMPEX®-TREME HEAT

PRODUCT VARIANTS OF OUR MODULAR HEAT PROTECTION SYSTEM

Here you will find all relevant tables and information concerning our TEMPEX®-TREME HEAT modular system. Choose between many different features and product variants. This modular clothing system enables you to put together your own personal heat protection equipment according to your individual requirements at the work place.

The following products will be, in case they are not available on stock, supplied within our high-speed delivery service 21 TO WEAR®. First order starting with 1 piece and delivery time approx. 21 days*. Requirements of more than 30 pieces will normally be produced separately, the production time then will be approx. 6-8 weeks from receipt of order.

MATERIAL VARIANTS OF THE MODULAR HEAT PROTECTION SYSTEM

The following table shows the different materials and indicates the material name, the material composition, the material weight and the certified fabric's standards.

| Part number | Material name | Material | Material weight | Standards |
|---------------|---------------|------------------------|-----------------|-----------------------------------|
| 120xx = 12014 | CK-12/Z | 70% Preox, 30% Aramide | approx. 360 g | EN ISO 11612 A1/B1/C3/D3/E3/F1 |
| 120xx = 12008 | AW-1/Y | 100 % Aramide | | EN ISO 11612 A1/B1/C4/D3/E3/F2 |
| 12003 | KF-3/Z | 100% para-aramide | approx. 475 g | EN ISO 11612 A1/B1/C3/D3/E3/F1 |

FOUNDRY COAT (see pages 98, 102 and 104)

| Product line | Part number | Closure | Ergonomic sleeves | Ventilation | Walking comfort | On stock |
|-------------------|--------------------|----------------|----------------------|----------------|--------------------|-------------|
| 1 CLASSIC | 12003 41030 000 15 | Hook&loop | - | - | - | 1 |
| KF-3/Z | 12003 41040 000 15 | Hook&loop | _ | - | - | 21 TO WEAR® |
| | 12003 41030 200 15 | Quick release | _ | - | - | 21 TO WEAR® |
| | 12003 41040 200 15 | Quick release | - | - | - | 21 TO WEAR® |
| 2 COMFORT | 12014 41130 001 15 | Hook&loop | ✓ | - | Slit | 1 |
| CK-12/Z AW-1/Y | 12008 41130 001 15 | Hook&loop | 1 | - | Slit | 1 |
| AVV-1/ 1 | 120xx 41yyy 001 15 | Hook&loop | 1 | - | Slit | 21 TO WEAR® |
| | 120xx 41yyy 101 15 | Snap fastening | 1 | - | Slit | 21 TO WEAR® |
| 3 COMFORT Plus | 120xx 41yyy 011 15 | Hook&loop | ✓ | Sleeves | Slit | 21 TO WEAR® |
| CK-12/Z AW-1/Y | 120xx 41yyy 012 15 | Hook&loop | 1 | Sleeves | Pleat | 21 TO WEAR® |
| AVV-1/ 1 | 120xx 41yyy 111 15 | Snap fastening | 1 | Sleeves | Slit | 21 TO WEAR® |
| | 120xx 41yyy 112 15 | Snap fastening | ✓ | Sleeves | Pleat | 21 TO WEAR® |
| | 12014 41130 021 15 | Hook&loop | ✓ | Sleeves + Back | Slit | ✓ |
| | 12008 41130 021 15 | Hook&loop | 1 | Sleeves + Back | Slit | 1 |
| | 120xx 41yyy 021 15 | Hook&loop | 1 | Sleeves + Back | Slit | 21 TO WEAR® |
| | 120xx 41yyy 022 15 | Hook&loop | ✓ | Sleeves + Back | Pleat | 21 TO WEAR® |
| | 120xx 41yyy 121 15 | Snap fastening | ✓ | Sleeves + Back | Slit | 21 TO WEAR® |
| | 120xx 41yyy 122 15 | Snap fastening | 1 | Sleeves + Back | Pleat | 21 TO WEAR® |

Length variants

| Part number | Length of the back |
|-------------|--------------------|
| 41030 | 130 cm |
| 41040 | 140 cm |

Length variants 2 COMFORT + 3 COMFORT Plus

| Part number | Length of the back |
|-------------------------------|--------------------|
| 41 yyy = 41 110 | 110 cm |
| 41 yyy = 41 120 | 120 cm |
| 41 yyy = 41 130 | 130 cm |
| 41 yyy = 41 140 | 140 cm |

If you like to order the COMFORT Plus foundry coat 70 % Preox, 30 % Aramide, length 130 cm, covered snap fastening, arm and back ventilation and walking pleat, the result will be the following part number:

12014 41130 122 15







MODULAR SYSTEM

JACKET (see pages 99, 103 and 105)

| Product line | Part number | Closure | Ergonomic sleeves | Ventilation | On stock |
|-------------------|--------------------|----------------|----------------------|----------------|-------------|
| 1 CLASSIC | 12003 11080 000 15 | Hook&loop | - | - | 1 |
| KF-3/Z | 12003 110yy 000 15 | Hook&loop | - | - | 21 TO WEAR® |
| | 12003 110yy 200 15 | Quick release | - | - | 21 TO WEAR® |
| 2 COMFORT | 12008 11180 000 15 | Hook&loop | 1 | - | 1 |
| CK-12/Z AW-1/Y | 120xx 111yy 000 15 | Hook&loop | ✓ | - | 21 TO WEAR® |
| AVV-1/ 1 | 120xx 111yy 100 15 | Snap fastening | ✓ | - | 21 TO WEAR® |
| 3 COMFORT Plus | 120xx 111yy 010 15 | Hook&loop | 1 | Sleeves | 21 TO WEAR® |
| CK-12/Z AW-1/Y | 120xx 111yy 110 15 | Snap fastening | ✓ | Sleeves | 21 TO WEAR® |
| AVV 1/ 1 | 12014 11180 020 15 | Hook&loop | ✓ | Sleeves + Back | ✓ |
| | 120xx 111yy 020 15 | Hook&loop | ✓ | Sleeves + Back | 21 TO WEAR® |
| | 120xx 111yy 120 15 | Snap fastening | ✓ | Sleeves + Back | 21 TO WEAR® |

Length variants 1 CLASSIC

| Part number | Length of the back |
|---------------|--------------------|
| 110yy = 11080 | 80 cm |
| 110yy = 11090 | 90 cm |
| 110yy = 11000 | 100 cm |

Length variants 2 | COMFORT + 3 | COMFORT Plus

| Part number | Length of the back |
|---------------|--------------------|
| 111yy = 11180 | 80 cm |
| 111yy = 11190 | 90 cm |
| 111yy = 11100 | 100 cm |

If you like to order the COMFORT Plus heat protection jacket 100 % Aramide, 90 cm length, with hook&loop fastener and ventilations under the arms and on the back, the result will be the following part number: 12008 11190 020 15

APRON WITH SLEEVES (see pages 98 and 101)

| Product line | Part number | Length | Closure | On stock |
|------------------|--------------------|--------|-----------|-------------|
| 1 CLASSIC KF-3/Z | 12003 71130 000 15 | 130 cm | Hook&loop | ✓ |
| 2 COMFORT | 12008 71110 000 15 | 110 cm | Hook&loop | 21 TO WEAR® |
| CK-12/Z | 12008 71130 000 15 | 130 cm | Hook&loop | ✓ |
| AW-1/Y | 12014 71110 000 15 | 110 cm | Hook&loop | 21 TO WEAR® |
| | 12014 71130 000 15 | 130 cm | Hook&loop | 21 TO WEAR® |

BIB APRON (see pages 100 and 101)

| | | | • | |
|------------------|--------------------|--------|-----------|-------------|
| Product line | Part number | Length | Closure | On stock |
| 1 CLASSIC KF-3/Z | 12003 71131 000 15 | 130 cm | Tie trap | √ |
| 2 COMFORT | 12008 71111 000 15 | 110 cm | Hook&loop | 21 TO WEAR® |
| CK-12/Z | 12008 71131 000 15 | 130 cm | Hook&loop | ✓ |
| AW-1/Y | 12014 71111 000 15 | 110 cm | Hook&loop | 21 TO WEAR® |
| | 12014 71131 000 15 | 130 cm | Hook&loop | 21 TO WEAR® |

HALF APRON (see page 100)

| Product line | Part number | Length | Closure | On stock |
|------------------|--------------------|--------|-----------|-------------|
| Troduct lifte | 1 di Cildilibei | Length | Ciosuie | OHISTOCK |
| 1 CLASSIC KF-3/Z | 12003 71100 000 15 | 100 cm | Tie trap | 1 |
| 2 COMFORT | 12008 71080 000 15 | 80 cm | Hook&loop | 21 TO WEAR® |
| CK-12/Z | 12008 71100 000 15 | 100 cm | Hook&loop | 21 TO WEAR® |
| AW-1/Y | 12014 71080 000 15 | 80 cm | Hook&loop | 21 TO WEAR® |
| | 12014 71100 000 15 | 100 cm | Hook&loop | 21 TO WEAR® |

HEAD PROTECTION (see pages 106 and 107)

| Product line | Part number | Designation | Ventilation | On stock |
|----------------|--------------------|--|-------------|-------------|
| 1 CLASSIC | 12003 7H007 000 15 | Protective hood with shoulder and chest protection | _ | 1 |
| KF-3/Z | 12003 7H007 001 15 | Protective hood | _ | 1 |
| | 12003 7H009 000 15 | Helmet cover | _ | 1 |
| 2 COMFORT | 12008 71001 000 15 | Protective hood with shoulder and chest protection | - | 21 TO WEAR® |
| CK-12/Z | 12014 71001 000 15 | Protective hood with shoulder and chest protection | - | 21 TO WEAR® |
| AW-1/Y | 12008 71001 001 15 | Protective hood | _ | 21 TO WEAR® |
| | 12014 71001 001 15 | Protective hood | _ | 21 TO WEAR® |
| | 12008 71002 000 15 | Helmet cover | _ | 21 TO WEAR® |
| | 12014 71002 000 15 | Helmet cover | _ | 21 TO WEAR® |
| 3 COMFORT Plus | 12008 71001 002 15 | Protective hood with shoulder and chest protection | / | 1 |
| CK-12/Z | 12014 71001 002 15 | Protective hood with shoulder and chest protection | 1 | 21 TO WEAR® |
| AW-1/Y | ••••• | · · · · · · · · · · · · · · · · · · · | | • |





CONFIGURE YOUR PPE YOURSELF ONLINE

WITH HB READY TO WEAR. ONE SYSTEM, MORE THAN 1,000 POSSIBILITIES.

4 articles, 216 colour combinations, 12 equipment variants, 28 sizes. Whether jacket or overall, red or black, with reflective or without, leg pocket or knee pocket: with our online configurator you can easily create your own personalised outfit.

MAXIMUM FLEXIBILITY AND FAST DELIVERY

You can also enjoy a delivery time of just 21 days and an order quantity from just 15 parts per item*. WITH HB READY TO WEAR.

| | | THREE | OPTION | IS | | PART | | | | | | | |
|-------------------|----------------------------|-----------------|-------------------------|----|-------------------|---------------------|-------|-------------|-----------|------------|-----|--------|-----|
| | REFLEC- TIVE STRIPES | KNEE POCKETS | 2ND COMBAT POCKET | | 1 RULER POCKET | | BLACK | MEDIUM GREY | DARK BLUE | ROYAL NAVY | RED | YELLOW | |
| | | | | | | YOKE | | | | | | | dh |
| JACKET | | | | | | TORSO/ARMS | | | | | | | |
| | | | | | | PIPES | | | | | | | |
| | | | | | | LEGS | | | | | | | |
| TROUSERS | | | | OR | | POCKET PLEAT | | | | | | | |
| | | | | | | PIPES | | | | | | | |
| BIB AND | | | | | | LEGS | | | | | | | M |
| BRACE TROUSERS | | | | OR | | POCKET PLEAT | | | | | | | - M |
| IKOUSEKS | | | | | | PIPES | | | | | | | |
| | | | | | | TORSO/ARMS/LEGS | | | | | | | |
| COVERALL | | | | OR | | YOKE + POCKET PLEAT | | | | | | | |
| | | | | | | PIPES | | | | | | | |

^{*} Outside Germany, delivery will take a few days longer. Up to a max. of 60 units. Delivery times for larger quantities are available on request.



Optional: Reflective stripes



Optional: Second combat pocket or ruler pocket

USE OUR READY TO WEAR CONFIGURATOR TO DESIGN YOUR OWN PROTECTIVE CLOTHING!

Come and try online for yourself at: www.hb-ready-to-wear.com





> INSULATION VALUES

INSULATION VALUES COLD PROTECTION

This table shows the performance levels of our TEMPEX $^{\scriptsize \circledcirc}$ cold protective wear. It shows the duration of use for the relevant clothing in relation to temperature and physical strain. The performance levels are light duty (more static works) and medium duty (works where you move more). The specified values are achieved only if jacket and trousers of the same material construction are worn.



| | | | | | | Stan acti 75 W | vity | | I | Activit ow mo 115 V | | | re | gular n | ty with noveme W/m² | |
|----------------|------------------------------------|---|--------|------------|-------------|----------------------|-------|--------|--------|---------------------------|-------|--------|-------------------|--------------------|---------------------------|--------|
| | | | | tion value | | Air sp | eeds | | | Air s | peeds | | | Air s | peeds | |
| | | | / m² • | (/W | 0,4 | m/s | 3 r | n/s | 0,4 | m/s | 3 r | m/s | 0,4 | m/s | 3 1 | m/s |
| | Part Number | Part | R-val | ue | 8 h | 1 h | 8 h | 1 h | 8 h | 1 h | 8 h | 1 h | 8 h | 1 h | 8 h | 1 h |
| U | 01174 1K014 000 | Jacket order picker | 0,428 | (B) AP 2 x | ₹° C | -16°C | 10 °C | -6°C | −13 °C | 33 °C | _3°C | _20°C | -34°C | _10°C | _20°C | _38°C |
| SSI | 01174 2K012 000 | Trousers order picker | 0,420 | (D) Al 2 X | 3 C | -10 C | 10 C | -0 C | -13 C | 33 C | -5 C | -20 C | -3 4 C | - 4 7 C | -20 C | -30 C |
| CLASSIC 2.0 | 01174 1K037 000 | Ladies' jacket order picker | 0,428 | (B) AP 2 x | 3°C | -16°C | 10 °C | -6°C | -13 °C | 33°C | -3°C | -20°C | -34°C | -49°C | -20°C | -38°C |
| 0 2 | | Ladies' trousers order picker | -, | (-/ | | | | | | | | | | | | |
| | 09044 1K048 000 | Jacket | 0,339 | (B) AP 2 x | 8°C | −10 °C | 16°C | 1°C | -5°C | -22°C | 4°C | −11°C | -22 °C | -41°C | -10° | -26 °C |
| | 09044 2K024 000 | Trousers | | . , | | | | | | | | | | | | |
| | 09044 1K049 000 | Ladies' jacket | 0,339 | (B) AP 2 x | 8°C | −10 °C | 16°C | 1°C | -5°C | -22°C | 4°C | −11°C | -22 °C | -41°C | -10° | -26 °C |
| | 09044 2K001 002 | Ladies' trousers Jacket order picker | | | | | | | | | | | | | | |
| | 09028 1K009 000 | with acrylic fur lining Trousers order picker | 0,344 | (B) AP 2 x | 8°C | -7°C | 15°C | 1°C | -5°C | -22°C | 3°C | -11°C | -23 °C | -42°C | −11 °C | -27°C |
| () | 09028 2K006 000 | with acrylic fur lining | | | | | | | | | | | | | | |
| CLASSIC | 09045 1K000 000 | Jacket order picker | 0,448 | (B) AP 2 x | 1°C | -18°C | 9°C | -7°C | -15 °C | -35°C | -4°C | -22°C | -37°C | -49°C | -22°C | -40°C |
| Ϋ́ | 09045 2K000 000 | Trousers order picker | 0,110 | (5) / 2 / | . 0 | .0 0 | , 0 | , 0 | .0 0 | 00 0 | , 0 | | 0, 0 | ., 0 | 22 0 | .0 0 |
| O | 09045 1K001 000 | Ladies' jacket order picker | 0,448 | (B) AP 2 x | 1°C | −18°C | 9°C | -7°C | -15 °C | -35°C | -4°C | -22°C | -37°C | -49°C | -22°C | -40°C |
| | 09045 2K001 000 | Ladies' trousers order picker | · | | | | | | | | | | | | | |
| | 09045 3K000 000 | Coverall order picker | 0,411 | (B) AP 2 x | 4°C | | 11 °C | -5°C | | -31°C | | | -32 °C | | | |
| | 09045 4K000 000 | Coat visitor | 0,292 | (R) AP 2 x | 11 °C | −2°C | 18 °C | 5°C | 0°C | −16°C | 7°C | -6°C | -16°C | -33 °C | -5 °C | -20°C |
| | 09046 1K012 001 09046 2K007 001 | Jacket forklift driver | 0,404 | (B) AP 2 x | 5°C | −12 °C | 13 °C | -3°C | -9°C | -28 °C | 0°C | -16°C | -29°C | -49°C | −16 °C | -33°C |
| | 09046 2K007 001 | Trousers forklift driver Jacket forklift driver Plus | | | | | | | | | | | | | | |
| | 09046 1K012 000 | Trousers forklift driver Plus | 0,398 | (B) AP 2 x | 5°C | −12 °C | 13 °C | -3°C | -9°C | -28°C | 0°C | -16°C | -29°C | -49°C | -16 °C | -33°C |
| | 01183 1K007 002 | Jacket | | | | | | | | | | | | | | |
| | 01183 2K008 006 | Trousers | 0,391 | (B) AP 2 x | 5°C | −12 °C | 13 °C | −3°C | -9°C | -28 °C | 0°C | -16°C | -29°C | -49°C | −16 °C | -33°C |
| | 01183 1K008 001 | Ladies' jacket | | | | | | | | | | | | | | |
| | 01183 2K003 003 | Ladies' trousers | 0,391 | (B) AP 2 x | 5°C | −12 °C | 13 °C | −3°C | -9°C | −28 °C | 0°C | −16°C | −29°C | -49°C | −16 °C | -33°C |
| | 01183 1K005 000 | Jacket order picker | | | | | | | | | | | | | | |
| J.K. | 01183 2K002 000 | Trousers order picker | 0,435 | (B) AP 2 x | 2°C | -16°C | 10 °C | -6°C | −14 °C | -34°C | -3°C | -21°C | -35 °C | -49°C | −21°C | −39°C |
| COMFORT | 01183 1K006 000 | Ladies' jacket order picker | | | | | | | | | | | | | | |
| 8 | 01183 2K003 000 | Ladies' trousers order picker | 0,435 | (B) AP 2 x | 2°C | −16°C | 10 °C | -6°C | −14 °C | -34°C | -3°C | -21°C | -35 °C | -49°C | -21°C | -39°C |
| _ | 01183 3K001 000 | Coverall order picker | 0,443 | (B) AP 2 x | 2°C | −17°C | 9°C | -7°C | -14 °C | -35°C | -4°C | -21°C | -36°C | -49°C | −21 °C | -40°C |
| | 01183 4K001 000 | Coat visitor | 0,274 | (B) AP 2 x | 12 °C | −1°C | 19°C | 6°C | 2°C | −13°C | 8°C | -4°C | -13 °C | -30°C | -3°C | -17°C |
| | 01183 1K013 000 | Jacket forklift driver | 0,508 | (B) AP 2 x | -3°C | -23°C | 5°C | −12 °C | -21°C | -42°C | -9°C | -27°C | -45°C | -49°C | -28°C | -48°C |
| | 01183 2K010 000 | Trousers forklift driver | · | ` , | | | | | | | | | | | | |
| | 01183 1K018 000 | Jacket forklift driver Plus | 0,511 | (B) AP 2 x | -3 °C | -23°C | 5°C | −12 °C | −21 °C | -42°C | -9°C | -28°C | -45°C | -49°C | -29°C | -48°C |
| ш | 01174 1K007 001 | Jacket | 0,371 | (B) AP 2 x | 6°C | -10°C | 14°C | -2°C | -7°C | -26°C | 1°C | -14°C | -26°C | -46°C | -14°C | -30°C |
| HYGIENE | 01174 2K008 005 | Trousers | | . , | | | | | | | | | | | | |
| ₹ Z | 01174 1K005 001 | Jacket order picker | 0,417 | (B) AP 2 x | 3°C | -15°C | 11 °C | -5°C | −12 °C | -31°C | -2°C | −19°C | -33°C | -49°C | −19 °C | -36°C |
| I | 01174 2K008 003 | Trousers order picker | 0.047 | (D) A D C | 17.00 | 0.00 | 10.00 | 700 | 7.00 | 10.00 | 0.00 | 7.00 | 10.00 | 20.00 | 0.00 | 1/ 00 |
| | 01174 4K001 001 | Coat visitor | 0,267 | (R) AP 2 x | 13 °C | 0°C | 19°C | 7°C | 3°C | −12 °C | 9°C | -3°C | −12 °C | -28 °C | -2°C | -16 °C |
| COLD | 01174 15001 000 01174 25002 000 | Jacket Trousers | 0,420 | (R) AP 2 x | 3°C | -14°C | 11 °C | -5°C | −12 °C | -31°C | -2°C | -18 °C | -33°C | -49°C | -19°C | -36°C |
| | | | | | | | | | | | | | | | | |

If a cold protection suit is selected from this table for a specific workplace, it must be ensured that the hand and foot coverings also has sufficiently high heat insulation for the ambient temperature that is present and that the face and head are properly protected. The specified values are achieved only if a jacket and trousers of the same construction are worn. The heat insulation may be converted into clo: 1clo = 0,155 m²K/W.

IMPORTANT! TEMPEX® Cold Store garments are classified acc. to DIN EN 342 Category II. Therefor it is not allowed to wear them at temperatures below -49 °C.

STANDARDS



IEC 61482-2:2009 (preceding standards: EN 61482-1-2 and ENV 50354)

Protective clothing against the thermal hazards of an electric arc

This Type of protective clothing is intended to protect the wearer against thermal effects of a defined electric fault arc according to the tested protection level e.g. protection class.

The Standard defines general requirements and requires an electric arc flash test. The material and garments tests are carried out either according to IEC 61482-1-1 (determination of the ATPV and the Elim value) or IEC 6148-1-2 (Determination of the arc protection class APC 1/APC 2). The tested protective clothing does not replace electrically insulating protective clothing such as clothing in accordance with EN 50286:1999, "Electrically insulating protective clothing for work on lowvoltage installations". Complete personal protection also requires suitable protective equipment such as safety helmet/visor, protective gloves etc.



EN ISO 11611

(preceding standard: EN 470-1) Protective clothing for use in welding and related processes

This Type of protective clothing is intended to protect the wearer against weld spatter (small splashes of molten metal), shortterm contact with fl ames as well as radiant heat from the electric arc. Under normal welding conditions, it offers limited electrical insulation against electric conductors of up to 100 V DC. This standard sets out two classes with specific performance requirements (class 1 is for lower requirements, class 2 for higher requirements).



EN ISO 11612

(preceding standard: EN 531) Clothing to protect against heat and flame

This international standard specifies

the minimum requirements for clothing protecting against heat and/or flames. In a wide variety of fields of application, the wearer can also be exposed to convective, radiant or contact heat, as well as splashes of molten metal. Within the standard, letters A–F define the performance levels relating to the protective properties listed above.



EN 1149-5

(preceding standard: EN 1149-5) Electrostatic properties -Material performance and design requirements

This standard specifies the requirements to be met by the materials used in and the design of electrostatically conductive protective clothing forming part of a fully earthed system to avoid ignitable discharge. The antistatic function is defined as minimising the risk of flammable discharge (explosion). The requirements may not be sufficient in a combustible atmosphere

enriched with oxygen. Protective clothing certified by this standard is not considered protection against mains voltage.



EN 61340

Protection of electronic devices from electrostatic phenomena

Protective clothing with this standard is suitable for the manufacture of

products, which are sensitive to discharges of 100V or more. Persons with ESD protective clothing are therefore protecting products during the manufacturing process from electrical discharges, which can happen with clothing that is not suitable for EPA, e.g. through friction or electrostatic induction (magnetic field, field effects) and/or material separations, and are therefore preventing damage to the component.



EN 13034 Type 6

Protective clothing against liquid chemicals - Performance requirements for chemical protective clothing off ering limited protective

performance against liquid chemicals

This standard specifies the minimum requirements to be met by protective clothing against chemicals offering limited protective effect, including reusable protective clothing. Protective clothing against chemicals offering limited protective effect is for use where there is a possibility of exposure to minor chemical spraying, liquid aerosols or low-pressure spattering.



EN ISO 20471

(preceding standard: EN 471) Warning clothing - Test methods and requirements

EN 20471 sets out the requirements to be met by protective clothing which visually highlights wearers. This is done to make them clearly visible in dangerous situations under all light conditions during the daytime and when vehicle headlights are shone at them in the darkness. This standard specifies performance requirements to be met by the protective clothing in terms of colour and retro-reflection, along with minimum surface dimensions and requirements to be met by materials used in the smallest possible



aarment size.

EN 17353

Protective Wear - Equipment for enhanced visibility in medium risk situations

This standard specifies the requirements for enhanced visibility equipment for clothing and products capable of visually signalling the presence of the wearer. Enhanced visibility equipment is intended to provide conspicuity to the wearer's presence in medium risk situations in all daylight conditions and/or when illuminated by vehicle headlights or searchlights in the dark. Performance requirements are included for colour

and retroreflectivity, as well as for the minimum area and arrangement of materials in the protective equipment.



EN 343

Protective clothing -Protection against rain

Specifies requirements and test methods for materials and seams

used in clothing to protect against precipitation (e.g. rain, snow-flakes), fog and ground humidity. Waterproofness and resistance to water vapour are the properties that must be tested and indicated on the label. The various classes for resistance to water vapour provide an indication for the recommended wearing time in different ambient temperatures.



EN 13758-2

Solar UV protective properties; EN 13758 Part 1: Method of test for apparel fabrics; EN 13758 Part 2: Classification and marking of apparel

The European standard 13758-1 defines the method for determination of permeability of ultraviolet solar radiation for textiles; EN 13758-2 sets out the classification and identification of the clothina As solar radiation causes skin diseases, only covered surface areas are protected of Type UV-A and UV-B radiation.



EN 14058

Protective clothing - Garments for protection against cool environments

This European standard specifies the requirements and test methods for wear behaviour of garments for protection against cool environments. Use of tested garments in environments with an air temperature of -5 °C and higher. Identification should include classification of overall heat transfer resistance.



EN 342

Protective clothing - Ensembles and garments for protection against cold.

This standard defines the test methods and performance requirements for protective clothing against cold of -5 °C or lower. It tests the thermal insulation and air permeability of the clothina. The test result states how long the wearer of the protective clothing can remain at certain temperatures when stationary or when performing tasks involving small or moderate amounts of movement.

Insulation values TEMPEX® Cold Protection: Please note our insulation values table for our TEMPEX® cold protective clothing on page 225. It shows the duration of use of the relevant garments in relation to physical performance and temperature.





Gloves as protection in cold environments

This standard defines the test methods and performance requirements for gloves used as protection in cold environments. It measures the insulation performance of the material in the event of contact with a cold object. resistance to the gradual permeation of cold, and thermal resistance in the event of direct contact with a cold object. The 3-digit code next to the standard pictogram indicates the performance levels, where 0 is the weakest and 4 is the best performance. The water resistance is defined with two performance levels: 0 = water permeation after 30 minutes, 1 = no water permeation after 30 minutes.



EN 15384 Protective clothing for the fire brigade for wildland firefighting This European Standard specifies

methods of test and minimum performance requirements for protective clothing, designed to protect the wearer's body, except the head, hands and feet, to be worn in wildland firefighting and associated activities. This clothing is not intended to provide protection during fire entrapment.



EN 407 Gloves as protection against thermal risks

Gloves tested in accordance with this standard provide protection against

heat and/or flames. The standard provides six testing options: combustion behaviour, contact heat, convective heat, radiant heat, small splashes of molten metal and larger quantities of molten metal. The actual level of protection depends on which test is carried out during certification and which performance level is achieved, where 1 is the lowest and 4 is the highest. "X" means not tested, "0" means below the minimum requirement.



and performance requirements for gloves used as protection against mechanical risks. It provides four testing options: abrasion resistance, cut resistance, tear propagation force and penetration force. The actual level of protection depends on which test is carried out during certification and which performance level is achieved, where 1 is the lowest and 4 (resp. 5) is the highest. "X" means not tested, "0" means below the minimum requirement.



EN ISO 20345 Personal protective equipment – safety footwear This standard defines basic

requirements and voluntary additional requirements for safety footwear for general purposes such as mechanical risks, slip resistance, thermal risks and ergonomic features. The letters SB and S1 to S5 indicate the requirements that have been met.



EN 166 Personal eye protection

This standard defines functional requirements for different Types of personal eye protection equipment and

includes basic requirements for all eye protection equipment such as the size of the minimum field of view, flammability, UV resistance or protection against dust, splashes of molten metal and electric arcs. This standard applies to all Types of personal eye protection equipment for protection against a range of hazards encountered in industry or in laboratories.

EN 171

Personal eye protection/infrared protective filter

This standard defines protection levels and transmission requirements for infrared protective filters The filters defined in this standard are not suitable for the (in)direct observation of electric arcs.



EN 397 Industrial hard hats

Industrial hard hats are primarily intended to protect the wearer against falling objects and their consequences,

such as brain injuries and skull fractures. This European standard defines general requirements, test methods and test conditions as well as requirements pertaining to the protective function (e.g. shock absorption and penetration resistance) of industrial hard hats.

EN 50365

Electrically insulating helmets for use on low voltage installations

This standard defines the requirements for electrically insulating helmets for protection when working on or near parts under alternating voltage of up to 1000 V (AC) or direct voltage up to 1500 V (DC). If it is used in combination with other electrically insulating PPE, the helmet should prevent dangerous electric current passing through the head as well as electric shocks. All helmets must also meet the requirements according to EN 397.

Hupf 2

Manufacturing and testing description for universal protective clothing for firemen (Part 2 - Firemen's trousers)

Hupf 2 specifies the minimum requirements to achieve sufficient basic protection for all firemen to protect them against general risks of firefighting service. It applies to the firemens' protective clothing described therein and contains a revision of safety requirements based on the current EN ISO 11612:2015 with regard to materials, sizes, design and marking, as well as adapted test methods

The firemen trousers shall comply with the applicable EN ISO 11612 "Protective clothing Clothing for protection against heat and flame", the applicable EN ISO 13688 "Protective clothing, General requirements" and this "Manufacturing and testing description for a universal protective clothing for firemen (HuPF)". The protective clothing for firemen is intended to protect the wearer from the hazards of firefighting activities together with the other personal protective equipment required in each case.

All products pictured in this catalogue are certified according to the product specified

Products with reflective stripes can provide better visibility. They are not automatically certified according to



EN ISO 20471

or



but only if the product is labelled accordingly.

> SIZES AND CARE

| MEN | | | | | | | | | | | | | | | | | | | | |
|---|------|-------|---------|-----|----------|-------|-----|-----|------|-----|------|------|------|-----|------|-----|--------|-----|-------|------|
| Unisex | 3XS | 2X: | 5 . | XS | | S | 1 | М | | L | > | KL | 22 | ΚL | 3) | XL | 4) | XL | 5XL | |
| Regular sizes | | | 40 | 42 | 44 | 46 | 48 | 50 | 52 | 54 | 56 | 58 | 60 | 62 | 64 | 66 | 68 | 70 | | |
| Long sizes men | | | 86 | 88 | 90 | 94 | 98 | 102 | 106 | 110 | 114 | 118 | 122 | 126 | 130 | 134 | 138 | 142 | | |
| Short sizes men | | | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | | |
| Double sizes | | | 38/40 | 42 | /44 | 46. | /48 | 50 | /52 | 54 | /56 | 58 | /60 | 62 | /64 | 66. | /68 | 70/ | /72 | |
| Long double sizes | | | 82/86 | 88 | 8/90 94/ | | /98 | 102 | /106 | 110 | /114 | 118. | /122 | 126 | /130 | 1 | 134/13 | 8 | | |
| Shirt collar width | | | 35 | 736 | 37 | 7/38 | 39. | /40 | 41. | /42 | 43 | /44 | 45. | /46 | 47, | /48 | 49, | /50 | 51/52 | 53/5 |
| WOMEN | | | | | | | | | | | | | | | | | | | | |
| Unisex | 3XS | 2X: | 5 | XS | | S | 1 | М | | L |) | KL | 22 | KL | 3) | XL | 4) | XL | | |
| Regular sizes | | 30 | 32 34 | 36 | 38 | 40 | 42 | 44 | 46 | 48 | 50 | 52 | 54 | 56 | 58 | 60 | | | | |
| Long sizes ladies | 1 | | | 72 | 76 | 80 | 84 | 88 | 92 | 96 | 100 | 104 | 108 | | | | | | | |
| Short sizes ladies | | | | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | | | | | | | |
| Double sizes | 2 | 28/30 | 32/34 | 36 | /38 | 40 | /42 | 44 | /46 | 48 | /50 | 52 | /54 | 56 | /58 | • | | | | |
| JNDERWEAR | | | | | | | | | | | | | | | | | | | | |
| Regular sizes | | | | | | 4 | | 5 | - | 6 | | 7 | | 3 | (| 9 | 1 | 0 | | |
| HEADGEAR | | | | | | | | | | | | | | | | | | | | |
| | | | 0.450 | 3/6 | 0 | 4/62 | 5/ | 64 | 6/66 | 7 | 7/68 | 8/70 | o | | | | | | | |
| | 0/54 | 1/56 | 2/58 | 3/0 | ,0 | ., 02 | | | | | | | | | | | | | | |
| tection&Cleanroom | 0/54 | | 2/58 | | 3/60- | | | | | | | | | | | | | | | |
| Head Cover Cold Protection & Cleanroom Visor Cap Cleanroom BELTS | | | | | | | | | | | | | | | | | | | | |
| tection&Cleanroom Visor Cap Cleanroom BELTS | | | | | 3/60- | | 14 | 40 | 150 | | | | | | | | | | | |
| tection&Cleanroom Visor Cap Cleanroom | 1/54 | -56 | 2/57-59 | | 3/60- | -63 | 14 | | 150 | | | | | | | | | | | |
| tection&Cleanroom Visor Cap Cleanroom BELTS Belt length | 1/54 | -56 | 2/57-59 | | 3/60- | -63 | | | 150 | | | | | | | | | | | |

43/44

45/46

47/48

50

Note: Sizes of older models may correspondingly deviate from these values.

Sizes available from stock. Sizes produced after receipt of order; usually not on stock. Please contact our sales staff for more information.

Sizes below each other correspond to each other, see framed example size M.



The 21 TO WEAR® icon indicates products which are available via our high-speed delivery service 21 TO WEAR® within 21 days. Please find more information at www.21towear.com

CUSTOMISED SIZES

HB Protective Wear offers a comprehensive selection of sizes for its collections. However, if you or your staff members require a customised size not included in the stated sizes, we will pleased to manufacture such garment to your stated body dimensions.

Socks





WASHING

The numbers stated in the wash tub correspond to the maximum washing temperatures and must not be exceeded. The single bar below the wash tub requires mild treatment with reduced washing amount and low speed during spin-drying. The double bar means very mild treatment with reduced mechanical load (e.g. wool).













30

30

BLEACHING







TUMBLE DRYING

The points state the drying level in the tumble dryer.











IRONING









PROFESSIONAL DRY CLEANING

The letters are intended for the textile care person. They state the applicable solvents. The bar below the circle requires limitation of mechanical load, moisture addition and/or temperature when cleaning











PROFESSIONAL WET CLEANING

This symbol identifies articles that can be treated by wet cleaning procedures. It is stated in the second line below the symbol for dry cleaning. The bars below the circle require limitation of mechanical load during wet cleaning. The double bar identifies an even milder procedure.











NOTE ON FLEECE MATERIAL

Fleece material may produce lint initially, depending on the design. This will stop after a few washes.

NOTE ON FLUORESCENT COLOURS

Fluorescent colours which are constantly exposed to UV radiation will fade more quickly. High-visibility clothing should therefore not be stored in direct sunlight.

•••••

NOTE ON TEMPEX® COLD PROTECTION GARMENTS

In order for you to be able to take advantage of your high-quality protective equipment for as long as possible, it is important to keep the following instructions in mind.



- Please hang up the clothing after each use and dry it in a sufficiently heated and well-ventilated room.
- Avoid pressing the garments during storage e.g. in narrow lockers.
- Never hang or lay the clothing onto hot heat sources.
- The garments should never be exposed to temperatures above +50 °C.
- We absolutely recommend regular professional cleaning or washing according to the instructions on the label of the garment.

THE PRO LABEL: **GARMENTS SUITED FOR INDUSTRIAL LAUNDRY**



HB products with this label are suitable for industrial laundry and meet the requirements of ISO 15797 for washing and drying processes in industrial laundry. Only textiles that are resistant to the conditions of these care

procedures can be labelled with a care symbol for industrial laundry.

Drying symbols:



Suitable for drum drying (tumbler)



Suitable for tunnel finisher

Washing symbol:



The numbers refer to the eight ISO 15797 washing processes

LEGEND



MULTI-RISK PROTECTION

Collections and items marked with "Multi-Risk" are certified according to minimum 4 EN standards. Therefore these are suited for work areas with multiple application fields.



FEMALE CUT

Tailored with fitted waist and especially made for women.



HIGH-SPEED DELIVERY SERVICE

These products are available in 21 days (Germany). Our PPE service for urgent needs. Abroad delivery takes few days more.



LIGHT-WEIGHT FABRIC

If you see this icon the product line is manufactured with extraordinarily light-weight fabrics.



GARMENT WEIGHT

The garment weight tells you how much exactly weighs the item, based on a medium size (M or 52).



DEEP FREEZING COLD STORE PLUS

Clothing for low-movement tasks at temperatures down to -49 °C



DEEP FREEZING COLD STORE

Clothing for high-movement tasks at temperatures down to -49 °C



COOLING CHILLROOM

Clothing for work in moderately cold conditions



READY TO WEAR

This collection can be configured individually (216 colour combinations, 12 equipment versions) and will be with you within 21 days.



SUSTAINABILITY

Products with this icon are made of sustainable eco-friendly materials like organic cotton or recycled PET bottles.



ERGONOMIC DESIGN

Product line with ergonomically optimised cut for more freedom of movement.



BREATHABILITY

This product offers a pleasant wearing and climate comfort thanks to its fast drying material and a quick moisture transport.

ATPV = Arc Thermal Performance Value:

Thermal characteristic value for the impact energy on a textile material at which there is a 50 % possibility of seconddegree burns.

EBT50 = Energy Breakopen Threshold:

Energy threshold at which there is a 50 % chance that the textile material will break open.

ELIM = Incident Energy Limit

Impact energy limit: Mean value of three determined values that lie below the Stoll curve (basis is the ATPV) and are additionally not broken up (basis is the EBT50). Protects the wearer 100 % compared to ATPV and EBT50.

All values - ATPV and EBT50 - are specified in cal/cm 2 or kJ/m 2 = amount of heat per unit area and show the load limits of the material or the material layer structures. The higher the value, the better the protection.

HAF = Heat Attenuation Factor:

In addition to EBT and ATPV, the heat attenuation factor, the HAF value, is determined. It indicates the percentage of heat that can be kept out when it strikes a flame-retardant material. Specified in %.

4kA - 7kA/4kA - 7kA

Our arc fault protective clothing is embroidered on the outside with these kilo-ampere (kA) specifications, so that the wearer can directly identify which protection the garment provides.

- 4kA: the garment has class 1 arc fault protection all round.
- 7kA/4kA: the garment has class 2 arc fault protection in the 2-layer areas (jacket front, sleeves and trouser front).
- 7kA: the garment has arc fault protection class 2 all around.

Reflective stripes

Products with reflective stripes are not automatically certified according to EN ISO 20471 or EN 17353, but only if they are marked accordingly in the label.



EN ISO 20471



EN 17353



END USER D-A-CH & INTERNATIONAL

CUSTOMER SERVICE

Ulrich Becker

Energy, Metal, Steel & Petroleum Industry

Phone +49 2639 8309-62 eMail ubecker@hb-online.com

Gisela Ragnit

Automotive, International
Phone +49 2639 8309-620
eMail gragnit@hb-online.com

Romina Standtke

Fire & Rescue, Cold Protection, General Industries

Phone +49 2639 8309-75 eMail rstandtke@hb-online.com

SALES SUPPORT

Lea Janzen

Phone +49 2639 8309-77 eMail ljanzen@hb-online.com

DISTRIBUTION D-A-CH & INTERNATIONAL

CUSTOMER SERVICE

Nico Schäfer

Southern Germany & CH
Phone +49 2639 8309-68
eMail nschaefer@hb-online.com

Elisa Kern

Northern Germany

Phone +49 2639 8309-79 <u>eMail</u> <u>ekern@hb-online.com</u>

Nico Heinich

Central Germany

Phone +49 2639 8309-618 eMail nheinich@hb-online.com

Margit Michel

A & International

Phone +49 2639 8309-61 eMail mmichel@hb-online.com

Gabi Ehlscheid

Phone +49 2639 8309-617 eMail gehlscheid@hb-online.com

SALES SUPPORT

Susanne Krämer

Phone +49 2639 8309-76 eMail skraemer@hb-online.com

ADDRESS

HB Protective Wear GmbH & Co. KG

Maischeider Straße 19 D-56584 Thalhausen

Phone +49 2639 8309-0 Fax +49 2639 8309-99

eMail info@hb-online.com

www.hb-online.com

TEXTILE SERVICES & LAUNDRIES

CUSTOMER SERVICE

Christiane Muscheid

Phone +49 2639 8309-622 <u>eMail</u> cmuscheid@hb-online.com

Ivonne Pick

Phone +49 2639 8309-60 eMail ipick@hb-online.com

Max Zimmermann

Phone +49 2639 8309-619

eMail mzimmermann@hb-online.com

be safe. we care.

HB Protective Wear GmbH & Co. KG

Maischeider Straße 19 · D-56584 Thalhausen

Phone +49 2639 8309-0 · Fax +49 2639 8309-99

info@hb-online.com · www.hb-online.com